


# INSTALLATION

Release 2019.1 – October 2019



For material suppliers and end-users who suffer from long and costly development cycles, e-Xstream engineering offers Digimat, The nonlinear multi-scale material & structure modeling platform, an innovative and efficient software suite to accurately predict the nonlinear behavior of composite materials and structures used across the industries.



# Contents

<b>Contents</b>	<b>3</b>
<b>I Installation of Digimat software</b>	<b>5</b>
<b>I.1 Getting started</b>	<b>7</b>
I.1.1 Digimat installation - quick & easy . . . . .	8
I.1.2 Installation of Digimat on a Windows machine . . . . .	11
I.1.3 Step-by-step: MSC license server . . . . .	15
I.1.4 Step-by-step: Digimat software . . . . .	76
I.1.5 Step-by-step: Digimat documentation . . . . .	98
I.1.6 Installation of Digimat on a linux machine . . . . .	103
<b>I.2 Licensing system</b>	<b>107</b>
I.2.1 Licensing system . . . . .	108
I.2.2 Digimat licensing usage . . . . .	110
I.2.3 Set-up of the licensing system . . . . .	112
I.2.4 Configuration of the licensing system . . . . .	114
I.2.5 MSC One licensing system . . . . .	116
I.2.6 MSC One licensing system . . . . .	117
<b>I.3 Digimat licensing management</b>	<b>119</b>
I.3.1 Licensing location . . . . .	120
I.3.2 Licensing status . . . . .	121
<b>I.4 Digimat settings</b>	<b>123</b>
I.4.1 The DIGIMAT_Settings.ini file . . . . .	124
I.4.2 Structure of the DIGIMAT_Settings.ini file . . . . .	125
I.4.3 Digimat environment variables . . . . .	129
I.4.4 Additional settings for network installations of Digimat . . . . .	131
<b>I.5 Digimat-CAE Interfaces</b>	<b>133</b>
I.5.1 Digimat-CAE/Abaqus . . . . .	134
I.5.2 Digimat-CAE/ANSYS . . . . .	140
I.5.3 Digimat-CAE/Marc . . . . .	148
I.5.4 Digimat-CAE/MSC Nastran SOL400 . . . . .	152
I.5.5 Digimat-CAE/SAMCEF . . . . .	153
I.5.6 Digimat-CAE/LS-DYNA . . . . .	157
I.5.7 Digimat-CAE/PAM-CRASH . . . . .	162
I.5.8 Digimat-CAE/MSC Nastran SOL1XX . . . . .	165
I.5.9 Digimat-CAE/OptiStruct . . . . .	166
I.5.10 Digimat-CAE/PERMAS . . . . .	167
I.5.11 Digimat-CAE/nCode DesignLife . . . . .	168
I.5.12 Digimat-CAE/ANSYS Fluent . . . . .	169

<b>II</b>	<b>Software</b>	<b>173</b>
<b>II.1</b>	<b>New capabilities &amp; changes in the software</b>	<b>175</b>
II.1.1	Digmat 2019.1 . . . . .	178
II.1.2	Digmat 2019.0 . . . . .	182
II.1.3	Digmat 2018.1 . . . . .	187
II.1.4	Digmat 2018.0 . . . . .	191
II.1.5	Digmat 2017.1 . . . . .	196
II.1.6	Digmat 2017.0 . . . . .	200
II.1.7	Digmat 2016.1 . . . . .	204
II.1.8	Digmat 2016.0 . . . . .	209
II.1.9	Digmat 6.1.1 . . . . .	213
II.1.10	Digmat 6.0.1 . . . . .	213
II.1.11	Digmat 5.1.2 . . . . .	217
II.1.12	Digmat 5.1.2 Student Edition . . . . .	219
II.1.13	Digmat 5.1.1 . . . . .	221
II.1.14	Digmat 5.0.1 . . . . .	227
II.1.15	Digmat 4.5.1 . . . . .	230
II.1.16	Digmat 4.4.1 . . . . .	231
II.1.17	Digmat 4.3.1 . . . . .	235
II.1.18	Digmat 4.2.1 . . . . .	238
II.1.19	Digmat 4.1.2 . . . . .	241
<b>II.2</b>	<b>Supported systems</b>	<b>243</b>
II.2.1	Licensing systems . . . . .	244
II.2.2	Operating systems . . . . .	244
II.2.3	Digmat GUI . . . . .	244
II.2.4	Digmat-CAE . . . . .	245
<b>II.3</b>	<b>Supported CAE software</b>	<b>247</b>
II.3.1	Digmat-CAE . . . . .	248
II.3.2	Digmat-FE . . . . .	261
II.3.3	Digmat-MAP . . . . .	262
<b>III</b>	<b>Windows Prerequisites</b>	<b>271</b>
<b>III.1</b>	<b>Installation of prerequisites on Windows platforms</b>	<b>273</b>
III.1.1	Microsoft Windows SDK v7.1 and .NET Framework 4.0 . . . . .	274
III.1.2	Microsoft Visual Studio Express 2012 for Windows Desktop . . . . .	296
III.1.3	Microsoft .NET Framework 4.6.2 . . . . .	301



## **Part I**

# **Installation of Digimat software**



# Installation **I.1**

## Getting started

---

I.1.1	Digmat installation - quick & easy . . . . .	8
I.1.2	Installation of Digimat on a Windows machine . . . . .	11
	Workflow & details . . . . .	11
	Database installation . . . . .	14
I.1.3	Step-by-step: MSC license server . . . . .	15
I.1.4	Step-by-step: Digimat software . . . . .	76
I.1.5	Step-by-step: Digimat documentation . . . . .	98
I.1.6	Installation of Digimat on a linux machine . . . . .	103

---

### I.1.1 Digimat installation - quick & easy

---

The following chapter is intended to give a quick and general overview over the single steps of the Digimat installation. A general overview over the installation procedure is followed by a typical example of a local Digimat installation on a Windows computer. For detailed procedures please refer to the dedicated chapters.

**It is highly recommended to follow the described procedures as given in the overview step by step to receive a stable installation of Digimat software!**

Files for testing Digimat 2019.1 installation can be obtained by contacting

[digimat.support@mscsoftware.com](mailto:digimat.support@mscsoftware.com).




Figure I.1.1: General overview over steps required to receive a stable installation of Digimat software.




Figure I.1.2: General overview over steps required to receive a stable installation of Digimat software.

---

## I.1.2 Installation of Digimat on a Windows machine

---

This section demonstrates the most straightforward way to create a **FULL standard installation of the Digimat software on a Windows machine**. It also covers the installation of a remote database on a computer server.

A full installation requires four steps best performed in the following order:

1. Installation of the MSC license server
2. Installation of Digimat
3. Linking with CAE software
4. Installation of Intel-MPI service for fiber orientation estimation

---

### Workflow & details

---

#### 1. Installation of the MSC license server

- Floating license system
- Server running on the current machine
  - Automated start with every boot of the machine
- It is recommended to reboot the machine as a last step of this installation!

#### 2. Installation of Digimat

- Setup of a floating license pointing to the MSC license server
- Installation of ALL Digimat modules
  - Usage of a non-default Digimat working directory
- Setup of standard paths to
  - Adobe Reader executable (required for the Digimat manual)
  - Patran installation (required for Digimat-RP)
  - MSC Nastran installation (required for Digimat-RP)
  - Marc Mentat installation (required for Digimat-RP, to use Digimat to Marc Mentat plug-in and for Digimat-FE interface with Marc)
  - ANSYS installation (required for Digimat-RP and Digimat-FE interface with ANSYS Workbench)
  - Abaqus installation (required for Digimat-RP and Digimat-FE interface with Abaqus CAE)
  - LS-DYNA installation (required for Digimat-FE interface with LS-DYNA)
  - Permas installation (required for Digimat-RP)
- Creation of local material database (cf. next subsection)
- Installation of Visual C/C++ redistributable files during installation procedure
- It is recommended to reboot the machine as a last step of this installation!
  - After reboot the user is up and running for the usage of all Digimat standalone modules.

#### 3. Linking with CAE software

- Linking Digimat with the external CAE software like Abaqus, ANSYS, Marc, LS-DYNA or others has to be carefully set up and tested.
- Please note that depending on the solver type and platform special linker software might be required.

- The detailed linking procedure with CAE solvers will not be dealt with in this chapter
  - Please refer to the individual section of the required CAE code in Chapter I.5.

#### 4. Installation of Intel-MPI service for fiber orientation estimation

When installing Digimat-RP/Moldex3D for fiber orientation estimation, Intel-MPI 4.0 service is automatically installed to allow parallel computation for fiber orientation estimation. The executables associated to the service are located in directory "C:\Program Files\Intel MPI 4.0\x64". It appears in Windows task manager with the name "impi\_smpd" (see Figure I.1.3), corresponding to the executable named "smpd.exe". Only one instance of this service can run on a computer. So, if another instance of the service is running when installing Digimat, this instance will be replaced by the one installed by Digimat-RP/Moldex3D.




Figure I.1.3: Intel-MPI service in task manager.

*Remark:* Intel-MPI service is not uninstalled when uninstalling Digimat.

Compatibility of Intel-MPI 4.0 with other versions of Intel-MPI:

- Intel-MPI 4.0 service can be used with software using Intel-MPI 3.1 and following versions.
- Fiber orientation estimation using Intel-MPI 4.0 cannot run with older versions of Intel-MPI service (e.g., 3.1).
- Fiber orientation estimation using Intel-MPI 4.0 can run with version 4.1.3 of Intel-MPI service.
- Software using Intel-MPI 4.1 (e.g., ANSYS 16.0 and Actran) can normally use Intel-MPI 4.0 service provided by Digimat-RP/Moldex3D. If it is not the case and if these software are installed before Digimat, it is then necessary to remove Intel-MPI 4.0 service and re-install Intel-MPI 4.1 service (see below for procedure).

To remove an existing Intel-MPI service:

- Open a Command prompt as an administrator.
- Find the directory of Intel-MPI service to be removed. This directory can be found by clicking on properties of the existing service (e.g., "C:\Program Files\Intel MPI 4.0\x64"), see Figures I.1.4 and I.1.5. The name of the executable associated to the service can also be found in the properties of the service. By supposing that the name of the executable is "smpd.exe", Type in the command prompt:
  - cd "C:\Program Files\Intel MPI 4.0\x64"
  - Type smpd.exe -stop
  - Type smpd.exe -remove.

To install a new Intel-MPI service:

- Open a Command prompt as an administrator.
- Go to directory of Intel-MPI service to be installed.
- Type smpd.exe -install. Please note that the name of the executable to run can be slightly different from "smpd.exe", but always contains "smpd" (e.g., "ismpd.exe").

In case of conflicts with another Intel-MPI service, please contact [digimat.support@mscsoftware.com](mailto:digimat.support@mscsoftware.com).






Figure I.1.4: Intel-MPI service.




Figure I.1.5: Intel-MPI service installation directory.

## Database installation

---

Material data can be easily accessed from databases in several Digimat modules, Digimat-MX in particular. Hence such a database must be created to enable material data access in 2 different ways.

- **Local database:** The database is physically located on the disk of the (only) computer used to connect to it. Such configuration is relevant when a single user needs material data access.
- **Remote database:** The database is physically located on a computer server to which several Digimat-MX installations installed on distant computers can connect. Such configuration is relevant when several users need to share material data.

A **local database** is exclusively created *during* the Digimat installation process in a directory besides Digimat installation directory (e.g., C:\MSC.Software\Digimat\_LocalDatabases\XXXX.X\postgresql). As the new – so-called built-in – local database is likely intended to become the default one, together with the new Digimat installation, its creation deactivates – but does not modify – any database created with an earlier Digimat version on which a server is running. Such an active database may exist especially with Digimat 2016.0 and earlier versions, which enabled advanced local databases administration similar to remote databases administration. Hence, stopping any running server and unregistering any active service prior to Digimat installation would prevent from any inconvenience, e.g., abrupt disconnection.

The built-in local database creation involves 3 possible actions.

- Select the component "Local material database" (cf. Figure [I.1.16](#); selected by default).
- Request to reset a previous database of the same Digimat version if such a database exists (cf. Figure [I.1.17](#); not requested by default). In such a case, the existing database is deleted before creating the new one (cf. Section ??).
- Request to migrate a previous database of an earlier Digimat version if such a database exists (cf. Figure [I.1.18](#); not requested by default). In such a case, the private grades of the existing database are imported at the end of Digimat installation via Digimat-MX local databases administration window (cf. Section ?? and Figure [I.1.39](#)).

A **remote database** can be created *after* Digimat installation, via Digimat-MX remote database administration (cf. Section ?? and Section ??). Such a database is usefully associated to a Windows service. In addition, its creation requires to stop the postgresql server of all remote databases currently running.

The creation of a remote database may even constitute the only purpose of Digimat installation, i.e., on a computer server. In such a case, any server (resp. service) running on a remote database of an earlier Digimat version already existing on the computer server must be stopped (resp. unregistered) with the corresponding Digimat-MX version prior to the uninstallation of the earlier version and the installation of the new version.

Install successively Digimat and the remote database as follows.

- Install Digimat and select only the Digimat-MX component (cf. Figure [I.1.16](#)). In particular, do not select the component "Local material database".
- Open Digimat-MX and do not connect to any database.
- Open the remote databases administration window via the menu "Administration" / "Remote databases" / "Databases".
- Select "New" / "Create". (Define a service if appropriate.)
- Choose the new database and select "Server" / "Start" or "Service->Start".
- Close Digimat-MX.

To continue working with a remote database of an earlier Digimat version already existing on the computer server, upgrade it as follows (cf. Section ??).

- Open Digimat-MX and do not connect to any database.
- Open the remote databases administration window via the menu "Administration" / "Remote databases" / "Databases".
- Choose the existing database to upgrade and select "Server" / "Upgrade".
- Choose the upgraded database and select "Server" / "Start" or "Service" / "Create" and "Service->Start".
- Close Digimat-MX.

### **I.1.3 Step-by-step: MSC license server**

---

# MSC **Licensing** Helium

## **User's Guide**

---

## Corporate

MSC Software Corporation  
4675 MacArthur Court, Suite 900  
Newport Beach, CA 92660  
Telephone: (714) 540-8900  
Toll Free Number: 1 855 672 7638  
Email: [americas.contact@mscsoftware.com](mailto:americas.contact@mscsoftware.com)

## Europe, Middle East, Africa

MSC Software GmbH  
Am Moosfeld 13  
81829 Munich, Germany  
Telephone: (49) 89 431 98 70  
Email: [europe@mscsoftware.com](mailto:europe@mscsoftware.com)

## Japan

MSC Software Japan Ltd.  
Shinjuku First West 8F  
23-7 Nishi Shinjuku  
1-Chome, Shinjuku-Ku  
Tokyo 160-0023, JAPAN  
Telephone: (81) (3)-6911-1200  
Email: [MSCJ.Market@mscsoftware.com](mailto:MSCJ.Market@mscsoftware.com)

## Asia-Pacific

MSC Software (S) Pte. Ltd.  
100 Beach Road  
#16-05 Shaw Tower  
Singapore 189702  
Telephone: 65-6272-0082  
Email: [APAC.Contact@mscsoftware.com](mailto:APAC.Contact@mscsoftware.com)

## Worldwide Web

[www.mscsoftware.com](http://www.mscsoftware.com)

## Disclaimer

MSC Software Corporation reserves the right to make changes in specifications and other information contained in this document without prior notice.

The concepts, methods, and examples presented in this text are for illustrative and educational purposes only, and are not intended to be exhaustive or to apply to any particular engineering problem or design. MSC Software Corporation assumes no liability or responsibility to any person or company for direct or indirect damages resulting from the use of any information contained herein.

User Documentation: Copyright © 2019 MSC Software Corporation. Printed in U.S.A. All Rights Reserved.

This notice shall be marked on any reproduction of this documentation, in whole or in part. Any reproduction or distribution of this document, in whole or in part, without the prior written consent of MSC Software Corporation is prohibited.

This software may contain certain third-party software that is protected by copyright and licensed from MSC Software suppliers. Additional terms and conditions and/or notices may apply for certain third party software. Such additional third party software terms and conditions and/or notices may be set forth in documentation and/or at <http://www.mscsoftware.com/thirdpartysoftware> (or successor website designated by MSC from time to time).

The MSC Software Logo, MSC, Actran, Adams, MSC Apex, MSC One, Digimat, Dytran, Easy5, MSC Fatigue, Marc, MSC Nastran, Patran, SimDesigner, Simufact, SimXpert, Sinda, and Simulating Reality are trademarks or registered trademarks of the MSC Software Corporation and/or its subsidiaries in the United States and/or other countries.

NASTRAN is a registered trademark of NASA. FlexNet Manager is a trademark or registered trademark of Flexera Software, Inc. All other trademarks are the property of their respective owners.

June 10, 2019

ZZ:HE:Z:LIC:Z:DC-USR-PDF

## Documentation Feedback

At MSC Software, we strive to produce the highest quality documentation and welcome your feedback. If you have comments or suggestions about our documentation, write to us at: [documentation-feedback@mscsoftware.com](mailto:documentation-feedback@mscsoftware.com).

Please include the following information with your feedback:

- Document name
- Release/Version number
- Chapter/Section name
- Topic title (for Online Help)
- Brief description of the content (for example, incomplete/incorrect information, grammatical errors, information that requires clarification or more details and so on).
- Your suggestions for correcting/improving documentation

You may also provide your feedback about MSC Software documentation by taking a short 5-minute survey at: <http://msc-documentation.questionpro.com>.

Note:	The above mentioned e-mail address is only for providing documentation specific feedback. If you have any technical problems, issues, or queries, please contact <a href="#">Technical Support</a> .
-------	--



# Contents

## MSC Licensing User's Guide

### Preface

Technical Support .....	5
Internet Resources .....	5

### 1 Installing MSC Licensing

Installation on Microsoft Windows Systems .....	8
Installation Pre-requisites .....	8
MSC Licensing Installation on Windows .....	8
Upgrade/Uninstall the Existing Windows Installation .....	18
Installation on Linux Systems .....	19
Installation Pre-requisites .....	19
MSC Licensing Installation on Linux system .....	19
Upgrade/Uninstall the Existing Linux Installation .....	29
Operating System Requirements .....	29
License Server Specifications .....	30
License Server Diagnostics (MSC Nastran Only) .....	30

### 2 Usage Reporting Tool

Usage Reporting Overview .....	32
Usage Reporting Details .....	32
Daily Detailed Usage (DDU) Log File .....	32
Daily Summary Usage (DSU) Log File .....	37
Automatic Upload .....	39
Off Network Scenarios .....	40
NODATA Reporting .....	40
GLIC Value in NODATA .....	40
BURST POOL Reporting .....	40
Triad Servers .....	41
Flexera Debug Log Files .....	41
License Server Product Updates .....	41
Manual Usage Reporting .....	41



Windows .....	42
Linux .....	42
Platform Notes .....	42

### 3 General Information - MSC Licensing

Introduction to FLEXlm .....	44
Types of Licenses .....	44
FLEXlm Components .....	44
Determining Hostid of License Server .....	46
License Request Process .....	46
Manual Configuration of License Server .....	46
Getting Started Checklist .....	47
Testing Your TCP/IP Connection .....	47
Internet Domain Name Server (DNS) .....	47
Updating Your License (Linux) .....	47
Manual Installation of MSC License Server Using a New LINUX Server .....	48
Obtain a License File for Your Server .....	48
Place the License File on the Server .....	48
Check Paths and Server Names in the license.dat File .....	48
Start the Manager Daemons .....	50
Set Up Clients to Access the Floating License .....	50
Manual Installation of MSC Licensing Using a New Windows Server .....	50
Obtain a License File for Your Server .....	50
Place the License File on the Server .....	50
Using Lmttools.exe to Configure FLEXlm .....	51
Set Up Clients to Access the Floating License .....	52
Replacing Codes on an Existing LINUX Server .....	52
Edit the New License File .....	52
Replace License File .....	52
Restart Daemon .....	52
Replacing Codes on an Existing Windows Server .....	52
Edit The New License File .....	52
Replace License File .....	53
Stop and Restart the FLEXlm Service .....	53
Restarting MSC Licensing Server on Linux .....	53
Stop the FLEXlm Service .....	53
Restart the FLEXlm Service with MSCLIC_INI file .....	53
Uninstalling FLEXlm on LINUX .....	53
Uninstall the License Server .....	53
Remove the Server .....	54

Uninstalling FLEXIm on Windows ..... 54

    Reinstalling FLEXIm ..... 54

Additional Documentation..... 54

# Preface

- Technical Support
- Internet Resources

## Technical Support

For technical support phone numbers and contact information, please visit:

<http://www.mscsoftware.com/Contents/Services/Technical-Support/Contact-Technical-Support.aspx>

### Support Center

<http://simcompanion.mscsoftware.com>

Support Online. The Support Center provides technical articles, frequently asked questions, and documentation from a single location.

## Internet Resources

MSC Software ([www.mscsoftware.com](http://www.mscsoftware.com))

MSC Software corporate site with information on the latest events, products, and services for the CAD/CAE/CAM marketplace.

### MSC Software Download Center

<https://mscsoftware.subscribenet.com>



# 1

## Installing MSC Licensing

---

- Installation on Microsoft Windows Systems
- Installation on Linux Systems
- Operating System Requirements

## Installation on Microsoft Windows Systems


### Installation Pre-requisites

1. All older versions of the MSC License Server must be uninstalled before installing latest MSC License Server. The installer will try to detect the old installation and inform the user to uninstall/remove the old server.
2. Download the MSC Licensing installation package from the MSC Software Download Center. This installer supports 64-bit versions of Windows.
3. Run the installation executable with the option 'Run as Administrator'. Certain features of the licensing installation require Administrator privileges even though the license server does not require Administrator privileges for normal operation.
4. To complete the installation of MSC Licensing you will need a valid MSC License file.


### MSC Licensing Installation on Windows

Follow these steps to install the MSC License Server on your Windows system:

1. Run the installation executable with the option 'Run as Administrator'. If your system already has the older version of the MSC Licensing Server then it shows the following message. Click **Yes** to continue.




2. Review the information and click **Next** to continue the installation.






3. Review the installer requirements and click **Next** to continue.



**Note:** You must have a valid, unexpired MSC license file before the MSC License Server can be installed. This screen provides the HostID that MSC uses to generate the license file. If you do not have an MSC license file, contact your MSC representative before continuing with the installation.

4. It is recommended to accept the default folder locations. To change the locations, click **Browse** and choose the directories to install the MSC License Server executables and store the MSC Licensing Log Files. Click **Next** to continue.



The default destination for the License Manager Executable folder:


C:\Program Files\MSC.Software\MSC Licensing\Helium

The default destination for License Manager Log File folder:

C:\MSC.Software\MSC Licensing\Helium\LOG

This is appropriate for most installations. Use **Browse** to select an alternate destination folder. You must have permission to write to the selected folder.


5. Click **Browse** and select the license file that was provided by MSC Software.




The License files details are given bellow:

Fields	Details
License File Reference ID	Unique Reference Number for the specified license file. This number may be helpful for support requests.
Product Type	<div><div></div> MSC One</div> <div><div></div> MasterKey Plus</div> <div><div></div> Seat Based License</div>
License Type	<div><div></div> Lease</div> <div><div></div> Perpetual</div>
Usage Reporting Requirement	<div><div></div> Automatic</div> <div><div></div> Manual</div> <div><div></div> No Reporting Required</div>

The following error message appears if one or more feature entries in the license file expired. Click **OK** to continue.




6. The MSC Licensing program includes a Usage Reporting Tool that provides valuable usage summary information to MSC to improve our products. A full description of the usage data sent to MSC is provided in [Chapter 2: Usage Reporting Tool](#) of this User Guide. No personal data is collected as part of this program. To participate, Click **Next** to continue the installation.



In cases where the customer is required to report usage and deactivates the Automatic Usage Reporting option, the following screen will appear to inform the user of the Manual Reporting Requirement.

7. Read the Information and click **Next** to continue the installation.



8. Specify the License Server Setting and click **Next** to continue the installation.

MSC Licensing Helium

### License Server Settings

Please define the desired license manager settings.

Port: 27500

Hostname: IND-VAISHALI

Option File Path(Optional): Browse

Select the privilege level for license manager access. (e.g. Server Start/Stop Functions)

Access: ☒ Admin/Supervisor ☐ Any

☒ Start the server automatically


MSC Software

< Back Next > Cancel


Specify the License Server Setting as follows:

- Specify an alternate port number (the default value is 27500; any number from 1 to 64000 is acceptable).
- Specify an alternate hostname (For example, fully qualified hostname or IP address).
- Optional: Browse and select the option file and path.
- Specify the privilege level for license manager access.
- The license manager will start automatically. Uncheck this box to install the license manager without the automatic starting.

9. Review the installation settings and click **Next** to complete the installation.




10. Click **OK** to finish the installation of the MSC License Server.



The installer creates a program group on the Start menu containing the Imtools utility. This utility can be used to start, stop, and restart the license server, and make other changes to the license server configuration.



11. Select the desktop icons to be created and click **Finish** to complete the installation.




**Note:** The MSC\_LICENSE\_FILE environment variable setting is displayed on the screen. Use this setting on the client machines to access the MSC License Manager.



## Upgrade/Uninstall the Existing Windows Installation

This allows the user to modify, repair or remove the current installation. Click one of the options shown below and click **Next** to continue.



## Installation on Linux Systems


### Installation Pre-requisites

1. Verify that a Java runtime environment is installed on the system. Java can be downloaded from [www.java.com](http://www.java.com).
2. Download the MSC Licensing installation package for your platform from MSC's Software Download Center.
3. The installer package for Linux platform supports both GUI and terminal-mode installations. MSC recommends that the installer be run in a GUI environment.
4. Run the installer to begin the installation. Use of a root account or sudo is not required. However, running the installation as root allows the installer to use system resources that require root privileges.

### MSC Licensing Installation on Linux system

Follow these steps to install the MSC License Server on your Linux system:


1. This begins the installation setup wizard on Linux. Click **Yes** to continue.




2. Review the information and click **Next** to continue the installation.



3. If your system already has the older version of the MSC Licensing Server then it will show the following message. Click **Yes** to continue.




4. Review the installer requirements and click **Next** to continue.



**Note:** You must have a valid, unexpired MSC license file before the MSC License Server can be installed. This screen provides the HostID that MSC uses to generate the license file. If you do not have an MSC license file, contact your MSC representative before continuing with the installation.

5. It is recommended to accept the default folder locations. To change the locations, click **Browse** and choose the directories to install the MSC License Server executables and store the MSC Licensing Log Files. Click **Next** to continue.



The default destination for License Manager Executable folder:


/msc/MSC.Software/MSC Licensing

The default destination for License Manager Log File folder:


/msc/MSC.Software/MSC Licensing/LOG

This is appropriate for most installations. Use **Browse** to select an alternate destination folder. You must have permission to write to the selected folder.


6. Click **Browse** and select the location of the license file that was provided by MSC Software.



The following error message appears if one or more feature entries in the license file expired. Click **OK** to continue.




7. Click **Next** to continue the installation.



The License files details are given bellow:

Fields	Details
License File Reference ID	Unique Reference Number for the specified license file. This number may be helpful for support requests.
Product Type	<ul style="list-style-type: none"><li>■ MSC One</li><li>■ MasterKey Plus</li><li>■ Seat Based License</li></ul>
License Type	<ul style="list-style-type: none"><li>■ Lease</li><li>■ Perpetual</li></ul>
Usage Reporting Requirement	<ul style="list-style-type: none"><li>■ Automatic</li><li>■ Manual</li><li>■ No Reporting Required</li></ul>


8. The MSC Licensing program includes a Usage Reporting Tool that provides valuable usage summary information to MSC to improve our products. A full description of the usage data sent to MSC is provided in Chapter 2 of this User Guide. No personal data is collected as part of this program. To participate, click **Next** to continue the installation.




In cases where the customer is required to report usage and deactivates the Automatic Usage Reporting option, the following screen will appear to inform the user of the Manual Reporting Requirement.



Read the Information and click **Next** to continue the installation.




9. Specify the License Server Setting and click **Next** to continue the installation.




Specify the License Server Setting as follows:

- Specify an alternate port number (default value is 27500 and it has a limit from 1-64000).
- Specify an alternate hostname (For example, fully qualified hostname or IP address).
- Optional: Browse and select the option file path.
- Specify the privilege level for license manager access.
- The license manager will start automatically. Uncheck this box to install the license manager without the automatic starting.

10. Review the installation settings and click **Next** to complete the installation.




11. Click **OK** and this finishes the installation of MSC License Server.



The installer creates a sample script that can be used to start the license server after a system reboot. This script and a README file with important details are written to a directory named **startup\_script** under the installation directory you selected.

12. Click **Finish** to complete the installation.



### Terminal/Console Mode


If you do not have access to a GUI environment, you can run the installer in a standard terminal window by adding the arguments **--mode console** to the installer command line.

Console mode is similar to GUI mode, with these important differences:

- In console mode, file and directory browsing is not available. You must manually enter these items.
- To select an option from a list, enter the text found between the brackets for that option.

## Upgrade/Uninstall the Existing Linux Installation

This allows the user to Upgrade/Uninstall the current installation. Click one of the option as shown below and click **Next** to continue.



## Operating System Requirements

The following table lists the minimum operating system version required to run the MSC license server and related tools:

Platform	Hardware	Supported Operating Systems
linux64	x64	RHEL 6.7, 7.1 and 7.3 SUSE ES 11 SP4 and 12 SP1
win64	x64	Windows 7 Professional, Enterprise, Ultimate Windows 10 Professional, Enterprise Windows Server 2016

## License Server Specifications

All MSC applications support use of the standard FLEXlm environment variables for specifying the license servers to be used for license requests. 1

For each method, the actual license specification can consist of one or more strings containing either a license server or the fully qualified path name of a license file.

The environment variable `MSC_LICENSE_FILE` is the preferred way to set a license server specification. All MSC applications also support use of the `LM_LICENSE_FILE` environment variable. If both of these are set, the value of `MSC_LICENSE_FILE` is used.

Some MSC applications also support other methods for setting the license specification. For example, MSC Nastran uses the `AUTH` keyword (on either the command line or in an RC file) for setting the license specification. If `AUTH` is used, it overrides the values on `MSC_LICENSE_FILE` and/or `LM_LICENSE_FILE`.

## License Server Diagnostics (MSC Nastran Only)

MSC Nastran users can set the `AUTHINFO` keyword to enable licensing diagnostics. The value of `AUTHINFO` can be a whole number from 0 (no diagnostics) to 9 (very detailed diagnostics). The diagnostics are printed to the MSC Nastran `.log` file.

---

Older versions of MSC Nastran can have problems with `AUTHINFO` settings greater than 6.

---

# 2

## Usage Reporting Tool

---

- Usage Reporting Overview
- Usage Reporting Details
- Manual Usage Reporting

## Usage Reporting Overview

The MSC Licensing installer includes a Usage Reporting Tool.

Where applicable, the Usage Reporting Tool logs information about each check-in in a Daily Detailed Usage (DDU) log file on the license server. Each day after midnight (local time), the DDU log file is converted to a Daily Summary Usage (DSU) file. If the automatic reporting option is enabled, the DSU file is automatically transmitted via the internet to an MSC-designated data repository. If the customer chooses the manual reporting option, the customer should follow the instructions in this guide to manually upload the DSU files to the MSC-designated data repository.

The DDU and DSU files are ASCII text files which can be viewed by the customer. The format of the files and descriptions of the contents are described in more detail below.

For customers using the Burst token pools for on-demand capacity, additional data will be included in the usage reporting to record the number of burst tokens used for the reporting period. See the [BURST POOL Reporting](#) section for more details.

## Usage Reporting Details

### Daily Detailed Usage (DDU) Log File

During the course of the day, all license feature check-ins are recorded in sequence in the Daily Detailed Usage (DDU) log file. This file is located in the “MSC Licensing/Helium/LOG” directory. The standard file name of the Daily Detailed Usage log file is:

“mscusage\_YYYY-MM-DD.ddu”

Below is a sample of the format for the DDU file.

```
D,171129,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,H
H,YYMMDD,HHMMSS,DURATION,MSCID,CID,SEQ,USERH,FEAT,NLIC,LICINUSE,BASEMAX,LICM
AX,CHWM,HWM,BCHWM,BHWM,CK1,CK2,VERS
T,171129,112022,I
Q,171129,112404,,0026b98999609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,0,3520808a,MSC
ONE:FFT_Actran_Acoustics,28,78,1,80,8,78,1,28,df997ff8d4f7b30ca3af939c07ac49
9a,,H
Q,171129,112404,,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,1,3520808a,MSCONE
:FFT_Actran_Acoustics,28,78,1,80,8,78,1,28,df997ff8d4f7b30ca3af939c07ac499a,
,H
U,171129,112507,64,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,8,3520808a,FFT_
Actran_Python,1,1,0,30,1,1,0,0,410df0bc,d6d98ef6,H
U,171129,112507,65,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,9,3520808a,MSCO
NE:FFT_Actran_VA,14,78,1,80:30,8,78,4,56,9f3e10fc,b7e9266,H
U,171129,112515,64,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,10,3520808a,FFT
_Actran_Sequential,1,1,0,30,1,1,0,0,efff4751,68a6621a,H
U,171129,112515,68,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,11,3520808a,FFT
_Actran_PreProcess,1,1,0,30,1,1,0,0,e6a8bcc5,2c848e69,H
U,171129,112515,72,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,12,3520808a,MSC
ONE:FFT_Actran_VI,7,64,1,80:30,8,78,1,7,12f9f954,27fd5772,H
```

```
U,1711129,112515,73,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,13,3520808a,MS
CONE:FFT_Actran_VA,14,57,1,80:30,8,78,4,56,c8bcf0ee,85e84001,H
P,1711129,112637,,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,2,3520808a,MS
CONE:FFT_Actran_Acoustics,28,43,1,80,8,78,1,28,df997ff8d4f7b30ca3af939c07ac499a,
,H
U,1711129,112637,155,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,14,3520808a,MS
CONE:FFT_Actran_VA,14,43,1,80:30,8,78,4,56,997d7014,a7ab7335,H
P,1711129,112807,,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,3,3520808a,MS
CONE:FFT_Actran_Acoustics,28,29,1,80,8,78,1,28,df997ff8d4f7b30ca3af939c07ac499a,
,H
U,1711129,112807,245,0026b98609df,2CCOD_1UI95_24ENF8WV_1I6ARTD,15,3520808a,MS
CONE:FFT_Actran_VA,14,29,1,80:30,8,78,4,56,bfebe11b,920eb039,H
```



The format of the DDU file, excluding the header, is described in the following table:

Table 2-1 Daily Detailed Usage (DDU) File Format

Daily Detailed Usage (DDU) File Format							
Field Number	First Field = Entry Tag						
	D = Date Stamp	T = Time Stamp	G = Group Record	R = Reread Record	U = Usage Record	Q = Queue Record	P = Processed Queue Record
2	Date	Date	Group Feature	Date	Date	Date	Date
3	Host ID	Time	Max Token	Time	Time	Time	Time
4	OS ID	Type	Base Token		Checkout Duration	Checkout Duration*	Checkout Duration*
5	Data Version ID		Data Version ID		Host ID	Host ID	Host ID
6					OS ID	OS ID	OS ID
7					Sequence Number	Sequence Number*	Sequence Number*
8					User Hash	User Hash	User Hash
9					Group:Feature	Group:Feature	Group:Feature
10					Feature Token Draw	Feature Token Draw	Feature Token Draw
11					Tokens in Use	Tokens in Use	Tokens in Use
12					Token Tag	Token Tag	Token Tag
13					Token Pool Size [:Base Pool Size]	Token Pool Size	Token Pool Size
14					Token Pool CHWM	Token Pool CHWM	Token Pool CHWM
15					Token Pool HWM	Token Pool HWM	Token Pool HWM
16					Feature CHWM	Feature CHWM	Feature CHWM
17					Feature HWM	Feature HWM	Feature HWM
18					Check Sum 1	Check Sum 1*	Check Sum 1*
19					Check Sum 2	Check Sum 2*	Check Sum 2*
20					Data Version ID	Data Version ID	Data Version ID

The first field of each line will commonly be either H (Header Entry), D (Date Stamp), T (Time Stamp), U (Usage Record), Q (Queue Record), P (Processed Queue Record), G (GROUP features) and R (REREAD event).

The fields for the Date Stamp entry are:

Date	= Date using the YYMMDD format.
Host ID	= Host ID of the license server.
OS ID	= Internal MSC ID to assign usage to specific agreement.
Data Version ID	= Version of Usage Reporting Tool.

The fields for the Time Stamp entry are:

Date	= Date using the YYMMDD format.
Time	= Time using the HHMMSS format. The hours use 24-Hr format.
Type	= Initial Time Stamp (I=Initial) or Periodic Time Stamp (P=Periodic).

The field entries for the Usage Record, Queue Record, and Processed Queue Record are:

Date	= Date using the YYMMDD format.
Time	= Time using the HHMMSS format. The hours use 24-Hr format.
Checkout Duration	= Duration of the feature checkout in seconds.
Host ID	= Host ID of the license server.
OS ID	= Internal MSC ID to assign usage to specific agreement.
Sequence Number	= Sequence number to the usage record in the daily Log.
User Hash	= One-way hash of the user name. No personally identifiable information is stored.
Group:Feature	= The name of the token pool (MSCONE) and feature that is checked in.
Feature Token Draw	= The token draw of the feature.
Tokens in Use	= The number of tokens checked out before the feature was checked in.
Token Tag	= Tag to signify whether a feature draws tokens (1) or is a standalone seat (0).
Token Pool Size [:Base Pool Size]	= Number of total MSC One tokens on the license server [: The Base Pool Size]
Token Pool CHWM	= Maximum number of all features checked out of the token pool.
Token Pool HWM	= Maximum number of tokens checked out of the token pool.
Feature CHWM	= Maximum number of the specific feature checked out of the token pool.
Feature HWM	= Maximum number of tokens checked out of the token pool for the feature.

Check Sum 1	= Check Sum # 1 to test for file tampering.
Check Sum 2	= Check Sum # 2 to test for file tampering.
Data Version ID	= Version of Usage Reporting Tool.

Note that for P and Q records that the duration field is empty, the sequence number is incremented differently than Q records, check field sum 1 field uses longer format, and check field sum 2 field is empty.

When the DDU file is processed by the summarizer routine, the filename extension will be changed to "DDP". The "P" stands for processed.

The fields for the G line entry are:

G,gfeature,max\_users,base,dataver

where

Fields	Description
gfeature	= Group feature [ MSC One / CAMPUS }
max_users	= Total token pool size
base	= Base token size
dataver	= Version of Usage Reporting Tool

**Note:**

1. Burst and/or growth token values are not included on G lines;
2. If a license file contains more than one GROUP target feature, such as both MSCONE and CAMPUS, then one G line is written for each GROUP target. (This can occur if an end-user manually combines an MSC One license file with a MasterKey+ license file; this combination is not officially supported by MSC Software, but there's no technical way to prevent it from occurring.)
3. GROUP targets that are referenced less than two times do not result in G lines. Seat-based licenses that include Nastran and/or Adams features contain MD-based features that use a GROUP entry targeting the non-MD feature; this is done so that use of either the MD or non-MD feature pulls from the same seat pool. (For example, the NASTRAN feature has a companion 1-seat MD\_NASTRAN feature definition that uses a GROUP : NASTRAN , 1 entry; when MD\_NASTRAN is checked out, it pulls from the NASTRAN feature's license pool.
4. The summarizer uses G lines only for NODATA situations. G lines in the DDU are used to construct the U NODATA lines for each GROUP when a NODATA reporting period is processed.
5. G lines are written only for GROUPs that are referenced by two or more FEATURES which include IDENT lines.

The fields for the R line entry are:

R lines indicate the time and date of a REREAD event.

R, ts, ur

where

Fields	Description
ts	YYMMDD - see the section "Fields common to multiple entries" for complete details
ur	HHMMSS - see the section "Fields common to multiple entries" for complete details.

## Daily Summary Usage (DSU) Log File

At the end of each day, the Daily Detailed Usage Log File is summarized with the results written to the Daily Summary Usage (DSU) log file. The DSU log file is also located in the "MSC Licensing/ Helium/ LOG" directory. The standard file name of the Daily Summary Usage log is:

"mscusage\_YYYY-MM-DD.dsu"

Below is a sample of the format for the DSU file.

```
H, yymmdd, mscid, osid, feature, count, smins, uniqusers, usermaxcnt, usermaxsmin, lic
cnt, glic, hwm, chwm, bhwm, bchwm, blv, ck1, ck2, vers
S, 171129, 0026b98609df, 2CCOD_1UI95_24ENF8WV_1I6ARTD, FFT_Actran_Python, 2, 3, 1, 2
, 3, 0, 30, 1, 1, 0, 0, 1, 4f59c4cf, 4e890a70, H
S, 171129, 0026b98609df, 2CCOD_1UI95_24ENF8WV_1I6ARTD, MSCONE:FFT_Actran_Acousti
cs, 3, 216, 1, 11, 350, 1, 80, 78, 8, 28, 1, 28, 605e6bd1, ffbcd54, H
S, 171129, 0026b98609df, 2CCOD_1UI95_24ENF8WV_1I6ARTD, MSCONE:Overall, 12, 407, 1, 1
2, 407, 1, 80, 78, 8, 30, 50, 48, c8372ae2, 6450b022, H
```

The format of the DSU file, excluding the header, is described in the following table:

Daily Summary Usage (DSU) File Format		
Field Number	First Field = Entry Tag	
	S = Usage Summary	T = Time Stamp
2	Date (YYMMDD)	Date
3	Host ID	Time
4	OS ID	Check Sum
5	Group:Feature	
6	Count	
7	Token-Minutes	
8	Unique Users	
9	MaxUser Count	
10	MaxUser Minutes	
11	Token Tag	
12	Token Pool Size	
13	Token Pool HWM	
14	Token Pool CHWM	
15	Feature HWM	
16	Feature CHWM	
17	Feature Token Draw	
18	Check Sum 1	
19	Check Sum 2	
20	Data version ID	

The first field of each line will be either an H (Header Entry), S (Usage Summary), or T (Time Stamp).

The fields for the Usage Summary entry are:

Date	= Date using the YYMMDD format.
Host ID	= Host ID of the license server.
OS ID	= Internal MSC ID to assign usage to specific agreement.
Group:Feature	= The name of the token pool (MSCONE) and feature that is checked in.
Count	= The total number of features check-ins during the reporting period.
Token Minutes	= The total token-minutes the feature was used during the reporting period.
Unique Users	= The number of unique users of the feature.
MaxUser Count	= Number of Checkouts for User with Maximum Checkouts.
MaxUser Minutes	= Number of Token-minutes for User with Maximum Token-Minutes.
Token Tag	= Tag to signify whether a feature draws tokens (1) or standalone seats (0).
Token Pool Size	= Number of total MSC One tokens on the license server.
Token Pool HWM	= Maximum number of tokens checked out of the token pool.
Token Pool CHWM	= Maximum number of all features checked out of the token pool.
Feature HWM	= Maximum number of tokens checked out of the token pool for the feature.
Feature CHWM	= Maximum number of the specific feature checked out of the token pool.
Feature Token Draw	= The token draw of the feature.
Check Sum 1	= Check Sum # 1 to test for file tampering.
Check Sum 2	= Check Sum # 2 to test for file tampering.
Data version ID	= Version of Usage Reporting Tools.

The fields for the Time Stamp entry are:

Date	= Date using the YYMMDD format.
Time	= Time using the HHMMSS format. The hours use 24-Hr format.
Check Sum	= Check Sum to test for file tampering.

When the DSU file is processed by the uploading routine, the filename extension will be changed to “DSP”. The “P” stands for processed.

## Automatic Upload

If the Usage Reporting Tool is enabled for automatic usage reporting, the DSU log file will be transmitted daily to the MSC-designated data repository. Standard HTTPS web encryption technology is used for the transmission of the data.

The DDP and DSP files will be retained on the customer's license server after the transmission and may be used by the customer to understand usage.

For manual uploading, please see the “**Manual Usage Reporting**” section of this document.

## Off Network Scenarios

If the license server is temporarily off-line during the time that the transmission is scheduled to happen, the files will be saved until the license server is back on-line. The summary files that have not been transmitted will be automatically processed at that time.

## NODATA Reporting

In some cases, for a given reporting period such as on a weekend or holiday period, there will be no usage data to report. In such cases, the license server will still report, but the usage will be a 'NODATA' report. An example of the “NODATA” report is shown below.

```
H, yymmdd, mscid, osid, feature, count, smins, uniqusers, usermaxcnt, usermaxs
min, liccnt, glic, hwm, chwm, bhwm, bchwm, blv, ck1, ck2, vers
S, 190528, a44cc86fa245, 38N55_2TIGX_1S19BJJF45_17OK433-641N-
MAN, MSCONE:NODATA, 0, 0, 0, 0, 0, 0, 80, 0, 0, 30, 50, 0, 0, 0, He
T, 190528, 200030, d41d8cd98f00b204e9800998ecf8427e
```

It is important to still report during a period of no usage so that the non-usage period will not be mistaken for failure to report.

## GLIC Value in NODATA

To support this task, a new data line is added to the DDU file, to provide details on the size of GROUP target pools.

When a license file contains a GROUP target feature (such as MSCONE for MSC One licenses, or CAMPUS for MasterKey+ licenses), additional G line is written in the DDU file when the vendor daemon is initialized. For more information please refer G line section - [Daily Detailed Usage \(DDU\) File Format](#).

## BURST POOL Reporting

MSC Software supports a special licensing method known as BURST POOL licensing. With BURST POOL licensing, the customer's license contains details about the number of BASE tokens and the number of BURST POOL tokens. When the customer uses more than the BASE number of tokens, the excess usage is reported to MSC as BURST POOL usage.

Customers using MSC Software's BURST POOL licensing will have some minor differences in certain usage data files, specific to the BURST POOL. The following sections describe these differences.

### DDU Files - BURST POOL

For BURST POOL users, the LICMAX field in the DDU file contains a sub-field with the BASE token value, shown in bold:

```
U,170905,200402,121,00505696c16d,K_K_4EIHx8BX_T4V3B2,4,b886258,MSCONE:FFT_Ac  
tran_Acoustics,28,84,1,100:50,3,84,3,84,ed58ccc9,3e9f881f,H
```

where the 100 represents the total size of the combined pool (BASE + BURST) and the 50 represents the BASE pool amount. This change applies to the U, P, and Q entries in the DDU file.

### DSU Files - BURST POOL

For BURST POOL users, the MSCONE:Overall line contains details about the BURST POOL and its usage for the reporting period:

```
S,171019,00505696c16d,K_K_4EIHx8BX_T4V3B2,MSCONE:Overall,1,27,0,1,27,1,460,1  
3,1,10,450,3,75bf5b5,182388ac,H
```

The “Token Pool Size” field (shown as 460 in the example) contains the combined pool size (BASE + BURST). The “Token Pool HWM” field (shows as 13 in the example, just after the 460) contains the number of BURST POOL tokens used during the reporting period. The “Feature HWM” field (shown as 10 in the example) contains the size of the BASE POOL. The “Feature CHWM” field (shown as 450 in the example) contains the size of the BURST POOL.

## Triad Servers

The Usage Reporting Tool supports the triad server environment. In a triad server, all three servers will report the usage. In some cases, there will be no usage to report from one or more servers in the triad. For triad servers that do not have any usage data, the “NODATA” report discussed in the previous section will be sent.

Note that in the GUI mode of the installer, the SERVER lines in the license.dat file will be incorrect when a TRIAD license file is provided. The host names for all three servers will be set to the fqdn of the installation system. These must be manually corrected for the case of a TRIAD license file. For Linux, the console mode will set the three license SERVER lines correctly.

## Flexera Debug Log Files

While the Usage Reporting Tool creates additional log files (e.g., the DDU and DSU files), the traditional Flexera debug log files are still available. The Flexera debug log files are not used by the Usage Reporting Tool.

## License Server Product Updates

Occasionally, MSC will release updates to the MSC Licensing software. Customers may be notified of these updates through the standard e-mail notifications from the MSC Solutions Download Center. The MSC Licensing software does not use automatic product updates. All product updates will need to be downloaded and installed manually by the customer when made available by MSC.

## Manual Usage Reporting

For customers whose internal or external security requirements prevent the license server system from accessing internet sites directly, an alternate method is available. Below are the instructions for performing manual usage reporting on the same machine as the license server or from a secondary machine.



## Windows

1. To run the Uploader, enter these commands:

```
cd C:\MSC.Software\MSC Licensing\Helium  
uploader -p %LOGDIR%
```

where %LOGDIR% is the folder that contains the DSU files to be uploaded.

<b>Note:</b>	Write permissions to the %LOGDIR% folder are required. The 'mscusage.mpl' file contains the Uploader execution status.
--------------	--

## Linux

1. To run the Uploader, enter these commands:

```
cd /msc/MSC.Software/MSC Licensing/Helium  
./uploader -p %LOGDIR%
```

where %LOGDIR% is the directory that contains the DSU files to be uploaded.

<b>Note:</b>	Write permissions to the %LOGDIR% directory are required.
--------------	---

## Platform Notes

### SuSE Linux

On SuSE Linux systems, the Uploader works in IPv4 and dual-stack IPv4/IPv6 network environments. However, the Uploader cannot be used on systems running in an IPv6-only network configuration.

# 3

## General Information - MSC Licensing

---

- Introduction to FLEXlm
- License Request Process
- Manual Configuration of License Server
- Getting Started Checklist
- Determining Hostid of License Server
- Testing Your TCP/IP Connection
- Internet Domain Name Server (DNS)
- Updating Your License (Linux)
- Manual Installation of MSC License Server Using a New LINUX Server
- Manual Installation of MSC Licensing Using a New Windows Server
- Replacing Codes on an Existing LINUX Server
- Replacing Codes on an Existing Windows Server
- Restarting MSC Licensing Server on Linux
- Uninstalling FLEXlm on LINUX
- Uninstalling FLEXlm on Windows
- Additional Documentation

## Introduction to FLEXlm

FLEXlm is a network license manager which is used to control the use of software products. FLEXlm allows software licenses to be available (float) anywhere on a network, instead of being tied to specific machines. Floating licensing benefits both users and system administrators. Users can make more efficient use of fewer licenses by sharing them on the network. You can control who uses the licensed application and the node or nodes where the licenses are available.

## Types of Licenses

A *concurrent* license limits the maximum number of simultaneous users of a given set of license features within a given site. A token based (*eg. MasterKey Plus and MSC One*) license is essentially the same, but allows access to all included license features, which is limited only by a maximum token count that can be used at any one time. Both of these licenses are referred to as *floating*. Please contact your MSC Software sales representative for more details on licensing options.

Typically, an MSC License Server (a separate program from the product installer) is installed on a network server to administer the licenses. The program files are then either loaded on individual computers or on the network server.

A *node-locked* license is used to run a product on a given computer. The number of product applications running at any given moment is limited by the number of seats licensed.

Both types of licenses use the license management software, which is designed to prevent tampering with the system date. If the system date is modified after product has been installed, the product license will be invalidated. Furthermore, a new license will not fix this problem. See the troubleshooting section in the Release Guide for further information.

<b>Caution:</b>	Please do NOT reset the system date after the installation. This can invalidate the license. Re-validation can be a difficult and cumbersome process.
-----------------	---

## FLEXlm Components

The four main components of FLEXlm are:

- License File (the product license file is called `license.dat`).
- Application Program (<product>).
- License Server (MSC).
- Vendor Daemon (MSC).

### License File

Licensing data is stored in a text file called the license file. The license file is typically named `license.dat`. The license file is created by the MSC Software licensing staff and sent via email to the system administrator. It contains information about the server nodes and vendor daemons, and one line of data (called a `FEATURE` line) for each licensed feature. A feature line contains an encryption code based on the data in that line, the

*hostids* ("host-id", or a unique identifier for a computer) specified in the server lines, and other vendor-specific data.

**Multiple License Servers:** Set the `MSC_LICENSE_FILE` variable to reference multiple servers using a separator character between file names; on Linux this character is a colon (":") and on Windows it is a semicolon (";"). The order of the license servers in the `MSC_LICENSE_FILE` variable is the order that license servers will be checked for a license request.

## Application Program

The application that employs FLEXlm licensing is linked with the program module that provides the communication with the license daemons. During execution, the application program communicates with the vendor daemon to request a license.

## License Server

Typically, an MSC License Server is installed on a network server to administer the floating licenses within a local area network. The program files are then either loaded on individual computers or on the network server. For a single or standalone installation, the server is installed on the same machine as the application. The server manages the License Manager and Vendor daemons.

Please note that the FLEXlm version of the MSC License Server must be greater than or equal to the FLEXlm version linked into the application programs.

## License Manager Daemon

The license daemon, usually called `lmgrd`, handles the initial contact with the client application programs, passing the connection on to the vendor daemon. It also starts and restarts the vendor daemons. FLEXlm permits multiple redundant license manager daemons on different server nodes, allowing you to make your license available if any two out of three server nodes is running. Also, you do not have to split your licenses among multiple servers or rely on any one machine.

## Vendor Daemon

In FLEXlm, licenses are handled by running processes. There is one process, called the vendor daemon, for each vendor that has a FLEXlm-licensed product on the network. The MSC Software vendor daemon is called MSC. The MSC daemon keeps track of how many licenses are checked out and who has them. Note that the MSC daemon serves many other MSC Software products, including MSC Nastran, Patran, and Adams, among others. If the MSC daemon terminates for any reason, all users would lose their licenses. Users normally regain their license when the daemon restarts.

Client programs communicate with the vendor daemon through TCP/IP sockets. This enables client programs and daemon processes to be on separate nodes in a network. The traffic between the client and the daemon is machine independent, which means that any process can run on any machine type or operating system, allowing a *heterogeneous* network.

## Determining Hostid of License Server

Before running any FLEXlm-licensed program using floating licenses, you must set up your license server node or nodes. You must select which node or nodes to run your license servers on and provide the `hostid` of those machines for installation.

To obtain a license file from MSC, you need to determine the `hostid` of the machine that will function as your license server.

Execute the `lmhostid` command from the command prompt:

```
<flexlm install folder>\lmutil lmhostid
```

This will list the possible 'hostid's' of the machine.

Please choose the Ethernet adapter local area connection `hostid`, wireless is not preferred.

(Using command `ipconfig /all` you could check the adapter type)

After sending the `hostid` of your server machines to MSC Software support, the support staff will send you a license file that enables the application software.

Once you have received a license file, you must install it on your system and start up the license server.

## License Request Process

When the application program calls the FLEXlm client library to request a license, the following process occurs:

1. The license module in the client application finds the license file, which includes the host name and port number of the license manager daemon (`lmgrd`).
2. The client establishes a connection with the license manager daemon and tells it what vendor it needs to talk to.
3. The license manager daemon determines which machine and port correspond to the master vendor daemon (if multiple redundant daemons are running) and sends that information back to the client.
4. The client establishes a connection with the specified vendor daemon (MSC) and sends its request for a license.
5. The vendor daemon checks to see if any licenses are available and sends a grant or denial back to the client.
6. The license module in the client returns to its caller with the grant or denial, and the application takes the appropriate action.

## Manual Configuration of License Server

You can configure most FLEXlm parameters by setting:

- The location of the license file.
- The location of all executables.
- The location of all log files.

- The TCP/IP port number of clients looking for the license manager.

In addition, you can reserve licenses for specific users, nodes, or groups and control other license-related options.

## Getting Started Checklist

As system administrator, you are responsible for setting up licensing on your system or network. If you are an end user of the application and you are not involved in installing it, then you can skip this section.

In general, installing FLEXlm licensing requires the following steps:

1. Select your license server nodes and get their hostids.
2. Send the host ids to your MSC license administrator and obtain a license file (or the data to enter in the license file) in return.
3. Determine how the new license file relates to any other license files that may already be on your system, and install it appropriately.
4. Start `lmgrd` (the license daemon) manually, or set it up to run automatically at startup, using the separately installed software (MSC Licensing FLEXlm) on the server.

## Testing Your TCP/IP Connection

The concurrent license management require that you are able to establish a TCP/IP network connection between your computer and the License Server. First, you need to know the `hostname` of the License Server. To determine the appropriate `hostname`, examine the existing concurrent license file and look for the `SERVER` command line. The first argument is the `hostname`. You can test if your computer can communicate with the License Server by entering the command

```
ping hostname
```

If you get a return reply, then you have a TCP/IP connection established.

## Internet Domain Name Server (DNS)

In addition to establishing a TCP/IP network connection between your computer and the License Server, the License Server host (computer name) needs to be found by your internet domain name server (DNS). If the host computer is inside a local-area-network (LAN) this is often automatic. If the host is not registered, you may need to add it to your `/etc/hosts` or equivalent file.

## Updating Your License (Linux)

The License Server must be updated with the new license before it is used. Do **not** overwrite the existing license file. Verify that the license has a valid path for the `DAEMON` line, and a valid `SERVER` hostname in the license file. The `DAEMON` line should have a path to the installed `MSC.exe` vendor daemon, normally found in folder:

```
/msc/MSC.Software/MSC Licensing/Helium
```

The DAEMON line should look similar to the following:

```
DAEMON MSC /msc/MSC.Software/MSC Licensing/Helium/MSC.exe
```

If the path to the daemon is incorrect, edit the license file and correct the path. The SERVER line should look similar to:

```
SERVER <hostname> <value> <port>
```

## Manual Installation of MSC License Server Using a New LINUX Server

### Obtain a License File for Your Server

```
# /MSC.Software/MSC Licensing/Helium/lmutil lmhostid
```

Send the hostid to your MSC Software Corporation sales representative to obtain your permanent license. Flexlm utilities are available at:

[https://mscsoftware.subscribenet.com/control/mnsc/product?child\\_plnID=593623](https://mscsoftware.subscribenet.com/control/mnsc/product?child_plnID=593623)

### Place the License File on the Server

The mscsetup utility automatically installs the license.dat file if you provide it during installation.

The license file may be located anywhere on your license server. MSC recommends locating it in /MSC.Software/MSC Licensing/Helium/license.dat.

Clients with network-licensed MSC software installations are encouraged to employ the most recent versions of the FLEXlm and MSC licensing daemons (lmgrd, lmutil, msc). These binaries maintain downward compatibility, and regular upgrades are recommended, regardless of whether or not the current software application level requires the upgrade. Updates are available at:

[https://mscsoftware.subscribenet.com/control/mnsc/product?child\\_plnID=593623](https://mscsoftware.subscribenet.com/control/mnsc/product?child_plnID=593623)

### Check Paths and Server Names in the license.dat File

Check that the license.dat file for your installation contains the correct server and port settings.

Below is an example of a license file supplied by MSC:

```
SERVER this_host 12345678 27500
DAEMON MSC /your_path/msc
#
# MSC License Reference ID: 59TG
#
#-#
#-# This license file is restricted to use by clients in the same location as the
license server
#-#
#
# MSC Nastran
#
FEATURE NASTRAN MSC 2017.0628 28-jun-2017 1 ED97453C93A6 \
```

```

VENDOR_STRING=PID:10652 ISSUED=29-jun-2016 ck=141 \
SN=1203862-a6382ca550b364f60e0f-2c2f
FEATURE NA_Thermal MSC 2017.0628 28-jun-2017 1 BB8A3B089AF1 \
VENDOR_STRING=PID:3002,3003 ISSUED=29-jun-2016 ck=189 \
SN=1138845-f6205ec4fbe7329339be-3b30
FEATURE NA_DMAP MSC 2017.0628 28-jun-2017 1 FD652933FAC7 \
ISSUED=29-jun-2016 ck=139 SN=1164504-093d6d6ae7ef8dd13594-a859
FEATURE NA_Dynamics MSC 2017.0628 28-jun-2017 1 CC25C4107563 \
ISSUED=29-jun-2016 ck=101 SN=915407-253bbea2e116836e48d0-da03
FEATURE NA_Nonlinear MSC 2017.0628 28-jun-2017 1 E16DB1DC662A \
VENDOR_STRING=PID:3003,10464 ISSUED=29-jun-2016 ck=149 \
SN=1110362-157249f70365b7a14431-7704

```

- SERVER must be in all caps followed by the hostname, then the lmhostid, then the port the daemon will run on.
- The hostname can be determined by typing “hostname” on the machine you wish to be your license server. Replace “UNKNOWN” on the SERVER line with this hostname.
- Verify the lmhostid listed on the SERVER line by running 'lmutil lmhostid' command. If the lmhostid is not correct, new codes must be generated. Contact your local MSC sales office.
- The default port is defaulted to 27500 but can be any free port. If you don't know what ports are free, use the default.
- DAEMON must be in all caps, followed by MSC which also must be in all CAPS. This is followed by the path to the msc vendor daemon executable.
- The executable is found in the '/MSC.Software/MSC Licensing/Helium/' directory.

Here is an example of the changes needed to be made for the above file. In the example, the server name is ind-Ashu and the default installation directory was used.

```

SERVER ind-Ashu 12345678 27500
DAEMON MSC C:\MSC.Software\MSC Licensing\Helium\msc.exe
#
# MSC License Reference ID: 59TG
#
#-#
#-# This license file is restricted to use by clients in the same location as the
license server
#-#
#
# MSC Nastran
#
FEATURE NASTRAN MSC 2017.0628 28-jun-2017 1 ED97453C93A6 \
VENDOR_STRING=PID:10652 ISSUED=29-jun-2016 ck=141 \
SN=1203862-a6382ca550b364f60e0f-2c2f
FEATURE NA_Thermal MSC 2017.0628 28-jun-2017 1 BB8A3B089AF1 \
VENDOR_STRING=PID:3002,3003 ISSUED=29-jun-2016 ck=189 \
SN=1138845-f6205ec4fbe7329339be-3b30
FEATURE NA_DMAP MSC 2017.0628 28-jun-2017 1 FD652933FAC7 \
ISSUED=29-jun-2016 ck=139 SN=1164504-093d6d6ae7ef8dd13594-a859
FEATURE NA_Dynamics MSC 2017.0628 28-jun-2017 1 CC25C4107563 \
ISSUED=29-jun-2016 ck=101 SN=915407-253bbea2e116836e48d0-da03
FEATURE NA_Nonlinear MSC 2017.0628 28-jun-2017 1 E16DB1DC662A \
VENDOR_STRING=PID:3003,10464 ISSUED=29-jun-2016 ck=149 \
SN=1110362-157249f70365b7a14431-7704

```



## Start the Manager Daemons

On the license server, start the license manager daemon with the `FLEXlm` script. Do not execute this as root since it may create a security risk on your network.

```
% /MSC.Software/MSC Licensing/Helium/lmgrd -c license.dat -l lmgrd.log
```

If the `license.dat` file is located in `/MSC.Software/MSC Licensing/Helium`, this script will start the following daemons:

- `lmgrd` - the server daemon
- `msc` - the vendor daemon

## Set Up Clients to Access the Floating License

For setting the file location on clients, set the `MSC_LICENSE_FILE` environment variable to “<port>@<hostname>”.

## Manual Installation of MSC Licensing Using a New Windows Server

### Obtain a License File for Your Server

To obtain a license file from MSC, you need to determine the `hostid` of the machine that will function as your license server.

Execute the '`MSC_Licensing_FLEXlm_Helium_windows64.exe`' available and select manual option to extract the required utilities.

[https://mscsoftware.subscribenet.com/control/mnsc/product?child\\_plnID=593623](https://mscsoftware.subscribenet.com/control/mnsc/product?child_plnID=593623)

Execute the `lmhostid` command from the command prompt:

```
"c:\Program Files\MSC.Software\MSC Licensing\Helium\lmutil" lmhostid
```

This will list the possible 'hostid's' of the machine.

Please choose the Ethernet adapter local area connection `hostid`, wireless is not preferred.

(Using command `ipconfig /all` you could check the adapter type)


### Place the License File on the Server

The license file may be located anywhere on your license server. MSC recommends locating it in “`c:\Program Files\MSC.Software\MSC Licensing\Helium\license.dat`”

## Using Lmtools.exe to Configure FLEXlm

You can use the Lmtools.exe utility to start/stop, configure, and diagnose your FLEXlm license server. You can access the Lmtools utility from the shortcut in the Start menu at Start>Programs>MSC.Software>Lmtools

### Start/Stop/Reread Advanced Settings



By clicking the Edit Advanced settings button on the LMTOOLS Start/Stop/Reread tab, you can:

- Restrict lmdown so that it only works logged into the system hosting the license server. This prevents the license server from being shutdown from a remote machine.
- Disable lmdown utility, use task manager prevents the lmdown utility from running on the machine hosting the license server. The license server can only be shutdown using the task manager.
- Disable lremove of license file. By selecting this, licenses checked out by users cannot be removed from the license server.
- Start Server - This starts the license server on the host machine.
- Stop Server - This asks the license server to stop on the host machine.
  - Force Server Shutdown - By selecting this button, the license server will be forced to stop regardless of what the server is doing.
- ReRead License File - Forces the licence server to reread the license file. This can be used when you get a new license file and do not want to stop and restart the license server.

**Note:** MSC does not support re-reads involving change of license type (for example, seat based to GROUP).

## Set Up Clients to Access the Floating License

The `MSC_LICENSE_FILE` environment variable provides the location of licenses. It can be set in `Control Panel\System\Environment` to `<port>@<hostname>.`

## Replacing Codes on an Existing LINUX Server

### Edit the New License File

Place the new codes as a license file in the same directory as the existing `license.dat` file. Name it `license_new.dat`. Change the `SERVER` and `DAEMON` lines in the new license file to include the same port number, server name, and paths as the existing file. For example:

```
SERVER server1 123465 27500
DAEMON MSC "/msc/MSC.Software/MSC Licensing/Helium/msc.exe"
```

### Replace License File

Rename the existing `license.dat` file to `license_old.dat`, and rename the new file to the current license file name (i.e. `license.dat`):

```
# mv license.dat license_old.dat
# mv license_new.dat license.dat
```

### Restart Daemon

Restart the daemons as follows:

```
# msc/MSC.Software/MSC Licensing/Helium/lmutil lmdown -c <path>/license.dat
# MSC.Software/MSC Licensing/Helium/lmgrd -c <path>/license.dat
```

## Replacing Codes on an Existing Windows Server

Follow these steps if you have an existing installation and have received new codes (as a renewal, change, etc.).

### Edit The New License File

Place the new codes as a license file in the same directory as the existing `license.dat` file. Name it `license_new.dat`. Change the `SERVER` and `DAEMON` lines in the new license file to include the same port number, server name, and paths as the existing file. For example:

```
SERVER server1 123465 27500
DAEMON MSC "c:\Program Files\MSC.Software\MSC Licensing\Helium\msc.exe"
```

## Replace License File

Use Windows Explorer to rename the existing license.dat file to license\_old.dat, and the new file to the current license file name (i.e. license.dat).

## Stop and Restart the FLEXlm Service

Using lmttools.exe, available at: "c:\Program Files\MSC.Software\MSC Licensing\Helium\"

1. Click on service/license file and select CONFIGURATION USING SERVICES.
2. Select appropriate license server in box below (if you have more than one).
3. Click ON START/STOP/REREAD Tab.
4. Select stop server and then after a minute start server.

This should restart the flexlm server to use new file.

## Restarting MSC Licensing Server on Linux

Follow these steps to restart the MSC Licensing Server on Linux:

### Stop the FLEXlm Service

```
[user@machine:Helium] ./lmutil lmdown -q -c cu12f03.dat
lmutil - Copyright (c) 1989-2015 Flexera Software LLC. All Rights Reserved.
```

Port@Host	Vendors
1) 1700@cu12f03	MSC
1 FlexNet License Server shut down	

### Restart the FLEXlm Service with MSCLIC\_INI file

```
export MSCLIC_INI=mscllic.ini
./lmgrd -c license.dat -l lmgrd.log
```

## Uninstalling FLEXlm on LINUX

To uninstall FLEXlm on LINUX, follow this procedure.

### Uninstall the License Server

To uninstall the server run this command:

```
/MSC.Software/MSC Licensing/Helium/uninstall
```

## Remove the Server

To manually uninstall the FLEXlm server remove the following files:

- /MSC.Software/MSC Licensing/Helium/uninstall
- /MSC.Software/MSC Licensing/Helium/MSC
- /MSC.Software/MSC Licensing/Helium/lmgrd

You will also need to remove the entry for the "msc" daemon from /etc/inittab.

The FLEXlm installation is now completely removed.

## Reinstalling FLEXlm

If you do not wish to remove the FLEXlm files manually, you can instead reinstall the FLEXlm server. In order to override the previous installation you must install FLEXlm in the same location with the same options as your previous installation. This program allows the user to Modify/Repair/Remove.

## Uninstalling FLEXlm on Windows

To uninstall FLEXlm on Windows, follow either one of the following procedures.

- Execute same MSC Licensing installer (which was used to install it) and then select **Remove**.
- Go to **Control Panel > Programs and Features > MSC Licensing Helium** and then click **Uninstall**.
- Click one of the option Modify/Repair/Remove.

## Reinstalling FLEXlm

If you do not wish to remove the FLEXlm, you can instead reinstall the FlexLM server.

In order to override the previous installation, execute same MSC Licensing installer (which was used to install it). This program allows the user to Modify/Repair/Remove.

## Additional Documentation

To obtain additional information on the FLEXlm license manager, visit the Flexera Software website at

<http://www.flexerasoftware.com/>

To ensure that the license server is running, you should:

- Open the *Services* tool of Windows, and check that *MSC License Manager* is running.
- Open the log file of the license server, located in *C:\MSC.Software\MSC Licensing\Helium\LOG\lmgrd.log*. If the server did start successfully, you should see something similar to this:

```

9:42:53 (lmgrd) -----
9:42:53 (lmgrd) Please Note:
9:42:53 (lmgrd)
9:42:53 (lmgrd) This log is intended for debug purposes only.
9:42:53 (lmgrd) In order to capture accurate license
9:42:53 (lmgrd) usage data into an organized repository,
9:42:53 (lmgrd) please enable report logging. Use Flexera's
9:42:53 (lmgrd) software license administration solution,
9:42:53 (lmgrd) FlexNet Manager, to readily gain visibility
9:42:53 (lmgrd) into license usage data and to create
9:42:53 (lmgrd) insightful reports on critical information like
9:42:53 (lmgrd) license availability and usage. FlexNet Manager
9:42:53 (lmgrd) can be fully automated to run these reports on
9:42:53 (lmgrd) schedule and can be used to track license
9:42:53 (lmgrd) servers and usage across a heterogeneous
9:42:53 (lmgrd) network of servers including Windows NT, Linux
9:42:53 (lmgrd) and UNIX.
9:42:53 (lmgrd) -----
9:42:53 (lmgrd)
9:42:53 (lmgrd) Server's System Date and Time: Fri Oct 11 2019 09:42:53 Romance Daylight Time
9:42:53 (lmgrd) pid 12356
9:42:53 (lmgrd) SLOG: Summary LOG statistics is enabled.
9:42:54 (lmgrd) Done rereading
9:42:54 (lmgrd) FlexNet Licensing (v11.16.3.0 build 246844 x64_n6) started on PPJ-PC2015 (IBM PC) (10/11/2019)
9:42:54 (lmgrd) Copyright (c) 1988-2019 Flexera. All Rights Reserved.
9:42:54 (lmgrd) World Wide Web: http://www.flexerasoftware.com
9:42:54 (lmgrd) License file(s): C:\MSC.Software\Digimat\licenseHelium.dat
9:42:54 (lmgrd) lmgrd tcp-port 27500
9:42:54 (lmgrd) (@lmgrd-SLOG@) =====
9:42:54 (lmgrd) (@lmgrd-SLOG@) === LMGRD ===
9:42:54 (lmgrd) (@lmgrd-SLOG@) Start-Date: Fri Oct 11 2019 09:42:54 Romance Daylight Time
9:42:54 (lmgrd) (@lmgrd-SLOG@) PID: 12356
9:42:54 (lmgrd) (@lmgrd-SLOG@) LMGRD Version: v11.16.3.0 build 246844 x64_n6 ( build 246844 (ipv6))
9:42:54 (lmgrd) (@lmgrd-SLOG@)
9:42:54 (lmgrd) (@lmgrd-SLOG@) === Network Info ===
9:42:54 (lmgrd) (@lmgrd-SLOG@) Listening port: 27500
9:42:54 (lmgrd) (@lmgrd-SLOG@)
9:42:54 (lmgrd) (@lmgrd-SLOG@) === Startup Info ===
9:42:54 (lmgrd) (@lmgrd-SLOG@) Is LS run as a service: Yes
9:42:54 (lmgrd) (@lmgrd-SLOG@) Server Configuration: Single Server
9:42:54 (lmgrd) (@lmgrd-SLOG@) Command-line options used at LS startup: -c C:\MSC.Software\Digimat\licenseHelium.dat
9:42:54 (lmgrd) (@lmgrd-SLOG@) -l C:\MSC.Software\MSC Licensing\Helium\LOG\lmgrd.log -z -s local
9:42:54 (lmgrd) (@lmgrd-SLOG@) License file(s) used: C:\MSC.Software\Digimat\licenseHelium.dat
9:42:54 (lmgrd) (@lmgrd-SLOG@) =====
9:42:54 (lmgrd) SLOG: FNPLS-INTERNAL-VL1-4096
9:42:54 (lmgrd) Starting vendor daemons ...
9:42:54 (lmgrd) License server manager (lmgrd) startup failed:
9:42:54 (lmgrd) File not found, C:\Program Files\MSC.Software\MSC Licensing\Helium
9:42:54 (lmgrd) Started MSC (pid 14200)
9:42:54 (MSC) FlexNet Licensing version v11.16.3.0 build 246844 x64_n6
9:42:54 (MSC) Loading feature details 3
9:42:54 (MSC) Loading feature details 3
9:42:54 (MSC) SLOG: Summary LOG statistics is enabled.
9:42:54 (MSC) SLOG: FNPLS-INTERNAL-CKPT1
9:42:54 (MSC) SLOG: VM Status: 255
9:42:54 (MSC) SLOG: FNPLS-INTERNAL-CKPT5
9:42:54 (MSC) SLOG: TPM Status: 0
9:42:54 (MSC) SLOG: FNPLS-INTERNAL-CKPT6
9:42:54 (MSC) Server started on PPJ-PC2015 for: EX_DIGIMAT_MF
9:42:54 (MSC) EX_DIGIMAT_FE_MODELER EX_DIGIMAT_FE_SOLVER EX_DIGIMAT_VA_GUI
9:42:54 (MSC) EX_DIGIMAT_VA_SOLVER EX_DIGIMAT_MX EX_DIGIMAT_MX+
9:42:54 (MSC) EX_DIGIMAT_MAP EX_DIGIMAT_RP_GUI EX_DIGIMAT_CAE_STRUCTURAL
9:42:54 (MSC) EX_DIGIMAT_CAE_MOLDING EX_DIGIMAT_RP_MOLDEX3D EX_DIGIMAT_HC
9:42:54 (MSC) EX_DIGIMAT_AM_SLS_GUI EX_DIGIMAT_AM_STANDARD_SOLVER EX_DIGIMAT_AM_FFF_GUI
9:42:54 (MSC) EX_DIGIMAT_AM_GUI EX_DIGIMAT_AM_ADVANCED_SOLVER EX_DIGIMAT_CAE_FATIGUE
9:42:54 (MSC) EX_DIGIMAT_CAE_DRAPING EX_DIGIMAT_CAE_CASTING EX_DIGIMAT_CAE_CT
9:42:54 (MSC) EX_DIGIMAT_CAE_ADDITIVE EX_DIGIMAT_CAE_TOKEN EX_DIGIMAT_FE_SOLVER_TOKEN

```

```

9:42:54 (MSC) EX_DIGIMAT_CAE_LINEAR
9:42:54 (MSC) EXTERNAL FILTERS are OFF
9:42:54 (lmgrd) MSC using TCP-port 19980
9:42:54 (MSC) Initialization
9:42:54 (MSC) (@MSC-INFO@) === Date ===
9:42:54 (MSC) (@MSC-INFO@) 2019-10-11
9:42:54 (MSC) (@MSC-INFO@)
9:42:54 (MSC) (@MSC-INFO@) === Component Versions ===
9:42:54 (MSC) (@MSC-INFO@) MSC created executables:
9:42:54 (MSC) (@MSC-INFO@) 1) MSC.exe vendor daemon (msc.exe):
9:42:54 (MSC) (@MSC-INFO@) Flexera internal version = 11.16.3.0 x64_n6
9:42:54 (MSC) (@MSC-INFO@) MSC internal version = Helium (Build 659671)
9:42:54 (MSC) (@MSC-INFO@) 2) summarizer: Helium (Build 659671) x64_n6
9:42:54 (MSC) (@MSC-INFO@) 3) uploader: Helium (Build 659671) x64_n6
9:42:54 (MSC) (@MSC-INFO@) Flexera created executables:
9:42:54 (MSC) (@MSC-INFO@) 1) lmgrd.exe: 11.16.3.0 x64_n6
9:42:54 (MSC) (@MSC-INFO@) 2) lmtools.exe: 11.16.3.0 x64_n6
9:42:54 (MSC) (@MSC-INFO@) 3) lmutil.exe: 11.16.3.0 x64_n6
9:42:54 (MSC) (@MSC-INFO@)
9:42:54 (MSC) (@MSC-INFO@) === Usage Reporting Tool Status ===
9:42:54 (MSC) (@MSC-INFO@) Usage Reporting Activated: yes
9:42:54 (MSC) (@MSC-INFO@) Summarizer Activated: yes
9:42:54 (MSC) (@MSC-INFO@) Uploader Activated: no
9:42:54 (MSC) (@MSC-INFO@) Usage Reporting Tool Log File: C:\MSC.Software\MSC Licensing\Helium\LOG/mscusage.mpl
9:42:54 (MSC) (@MSC-INFO@)
9:42:54 (MSC) (@MSC-INFO@) === License File Information === (Actual details pending)
9:42:54 (MSC) (@MSC-INFO@) MSC License File Reference: 6XJD
9:42:54 (MSC) (@MSC-INFO@) 6XJD: Maint Date=2019-02-21; End Date=2019-12-31:
9:42:54 (MSC) (@MSC-INFO@)
9:42:54 (MSC) (@MSC-INFO@) === Token Pool Information === (Actual details pending)
9:42:54 (MSC) (@MSC-INFO@) MSC One Tokens: Base = 1000
9:42:54 (MSC) (@MSC-INFO@)
9:42:54 (MSC) SLOG: Statistics Log Frequency is 240 minute(s).
9:42:54 (MSC) SLOG: TS update poll interval is 600 seconds.
9:42:54 (MSC) SLOG: Activation borrow reclaim percentage is 0.
9:42:54 (MSC) (@MSC-SLOG@) =====
9:42:54 (MSC) (@MSC-SLOG@) === Vendor Daemon ===
9:42:54 (MSC) (@MSC-SLOG@) Vendor daemon: MSC
9:42:54 (MSC) (@MSC-SLOG@) Start-Date: Fri Oct 11 2019 09:42:54 Romance Daylight Time
9:42:54 (MSC) (@MSC-SLOG@) PID: 14200
9:42:54 (MSC) (@MSC-SLOG@) VD Version: v11.16.3.0 build 246844 x64_n6 ( build 246844 (ipv6))
9:42:54 (MSC) (@MSC-SLOG@)
9:42:54 (MSC) (@MSC-SLOG@) === Startup/Restart Info ===
9:42:54 (MSC) (@MSC-SLOG@) Options file used: None
9:42:54 (MSC) (@MSC-SLOG@) Is vendor daemon a CVD: No
9:42:54 (MSC) (@MSC-SLOG@) Is FlexNet Licensing Service installed and compatible: No
9:42:54 (MSC) (@MSC-SLOG@) FlexNet Licensing Service Version: -NA-
9:42:54 (MSC) (@MSC-SLOG@) Is TS accessed: No
9:42:54 (MSC) (@MSC-SLOG@) TS access time: -NA-
9:42:54 (MSC) (@MSC-SLOG@) Number of VD restarts since LS startup: 0
9:42:54 (MSC) (@MSC-SLOG@)
9:42:54 (MSC) (@MSC-SLOG@) === Network Info ===
9:42:54 (MSC) (@MSC-SLOG@) Listening port: 19980
9:42:54 (MSC) (@MSC-SLOG@) Daemon select timeout (in seconds): 1
9:42:54 (MSC) (@MSC-SLOG@)
9:42:54 (MSC) (@MSC-SLOG@) === Host Info ===
9:42:54 (MSC) (@MSC-SLOG@) Host used in license file: PPJ-PC2015
9:42:54 (MSC) (@MSC-SLOG@) HostID node-locked in license file: 9890969f897a
9:42:54 (MSC) (@MSC-SLOG@) HostID of the License Server: "9890969f897a 0a002700000f"
9:42:54 (MSC) (@MSC-SLOG@) Running on Hypervisor: None (Physical)
9:42:54 (MSC) (@MSC-SLOG@) =====
9:42:54 (MSC) Loading feature details 3
9:42:54 (MSC) Usage records are being written to C:\MSC.Software\MSC Licensing\Helium\LOG/mscusage_2019-10-11.ddu

```

If the server is running and you still have issue to start the products, check the firewall configuration of your license server, and open the right ports.

### I.1.4 Step-by-step: Digimat software

---




Figure I.1.6: Two files are mandatory to be downloaded from the FTP server: the Digimat installer and the installer for third-party components. For the installation of the documentation, the respective third package is also required. Moldex3D OEM has to be downloaded if user intends to use Digimat-RP and the estimation of the orientation. The global installer **Install Digimat x64 2019.1.exe** will lead through the complete procedures for installing Digimat on Windows 64bit platforms.





Figure I.1.7: Opening prompt of the Digimat installer. Follow the given instructions step-by-step.



### Release Notes Digimat 2019.1 – October 2019




Figure I.1.8: Upon execution of the Digimat installer, the release notes will be shown in a separate PDF viewer.




Figure I.1.9: Please read carefully the software license agreement. It must be agreed to before being able to continue with the installation procedure.




Figure I.1.10: The IP address for communication with the MSC license service has to be given, preceded by the @. If needed, user can also specify explicitly the port used by the license server, e.g., 27500@192.168.1.1. Port specification should only be used if it is explicitly specified in the license server. In case of a nodelocked license file, user has to fill the full path to this license file using the "browse" button.




Figure I.1.11: The destination folder for the Digimat installation has to be given. A 2019.1 directory will be automatically created.




Figure I.1.12: Choice of installing Digimat documentation. If user chooses to not Digimat documentation, it is still possible to install Digimat documentation step after complete Digimat installation.




Figure I.1.13: If the option "Digimat documentation is already installed" is selected, user has to point to the Digimat documentation directory. So the settings of Digimat will be automatically updated to point to this documentation. Note that user cannot point to a Digimat documentation prior to Digimat 2016.0.




Figure I.1.14: The path to an existing installation of Adobe Reader has to be defined. This is to ensure the correct performance of the software help showing the Digimat documentation.




Figure I.1.15: The destination folder for the Digimat working directory has to be given. This directory can be located anywhere on the computer and shared also between different versions of Digimat. Note that, if Digimat-HC component is selected, working directory cannot contain spaces.




Figure I.1.16: The required Digimat modules can be chosen individually to save disk space for the installation. In the default case as used here all modules will be installed. If Moldex3D installer has been downloaded, it will be installed by default, unless user deselect the sub-component "Moldex3D integrated into Digimat-RP".




Figure I.1.17: The local material database can be reset (cf. Section I.1.2).




Figure I.1.18: To be fully operational, the new built-in local database may require the migration of an existing local database at the end of Digimat installation (cf. Section I.1.2 and Figure I.1.39).




Figure I.1.19: If Digimat-VA component is selected and if a previous version of Digimat-VA database is found, user can import it inside the new database 2019.1.




Figure I.1.20: If user wants to import a previous version of Digimat-VA database, the path to this Digimat-VA database must be given.






Figure I.1.21: The local material database can be attached (cf. Section I.1.2).




Figure I.1.22: The path of an existing Marc installation is requested. This is to ensure smooth performance of Digimat-RP with Marc. If not using this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section [I.4.1](#).




Figure I.1.23: The path of an existing Marc Mentat installation is requested. This is to ensure smooth performance of Digimat-RP with Marc Mentat and to automatically write the Digimat to Marc Mentat plugin. If not using this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section I.4.1.




Figure I.1.24: The path of an existing MSC Nastran installation is requested. If not using this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section I.4.1.




Figure I.1.25: The path of an existing Patran installation is requested. If not using this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section [I.4.1](#).




Figure I.1.26: The path of an existing Abaqus installation is requested. This is to ensure smooth performance of Digimat-RP and the Digimat-FE interface with Abaqus CAE. If not using either the Digimat-FE module or this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section [I.4.1](#).




Figure I.1.27: The path of an existing Abaqus-CAE installation is requested. This is to ensure smooth performance of Digimat-RP and the Digimat-FE interface with Abaqus CAE. If not using either the Digimat-FE module or this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section I.4.1.




Figure I.1.28: The path of an existing ANSYS installation is requested. This is to ensure smooth performance of Digimat-RP and the Digimat-FE interface with ANSYS Workbench. If not using either the Digimat-FE module or this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section I.4.1.




Figure I.1.29: The path of an existing Altair installation is requested. If not using this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section [I.4.1](#).




Figure I.1.30: The path of an existing PERMAS installation is requested. If not using this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section [I.4.1](#).




Figure I.1.31: The path of an existing LS-DYNA installation is requested. This is to ensure smooth performance of Digimat-FE interface with LS-DYNA implicit. If not using either the Digimat-FE module or this FEA solver the step can be skipped and the input field left blank. If needed this path can be specified in a later step via Digimat settings as explained in section [I.4.1](#).




Figure I.1.32: An individual name for the Digimat shortcut can be specified.




Figure I.1.33: A desktop icon can be created. User can also choose to install Visual 2012 C/C++ redistributable files together with Digimat. These files are required to run Digimat computations. In this case, Visual C/C++ redistributable files will be installed.






Figure I.1.34: A summary of the installation details is given and can be checked. Proceeding with the "Install" button will start the installation of Digimat.




Figure I.1.35: The installation of the Digimat core software is executed.




Figure I.1.36: The installation of the Microsoft Visual C++ 2012 redistributables is executed.




Figure I.1.37: Third party products are installed. Third party components must be installed in order to be able to run the Digimat software.




Figure I.1.38: As a last step, the Digimat documentation is installed (if chosen).




Figure I.1.39: If the migration of a previous local database in the new local database is required (cf. Figure I.1.18), the directory of this database must be selected prior to the actual database import (cf. Section ??).




Figure I.1.40: During database import from previous Digimat version, the type of "composite" grades can be converted to "chopped fiber(short)".




Figure I.1.41: During database import from previous Digimat version, data belonging to different users are addressed specifically.




Figure I.1.42: Successful database import from previous Digimat version.




Figure I.1.43: In the end of the installation procedure additional information is given for Abaqus users. This let you know how to update the abaqus\_v6.env file to be able to use the Digimat-CAE/Abaqus interface. If Digimat-CAE/Abaqus is required, we strongly recommend to read [I.5.1](#) before proceeding with the linking procedure to the Abaqus solver.



Figure I.1.44: Upon finalization of the installation the user can choose to reboot the computer immediately. **Please note that to ensure safely a fully functional installation of Digimat the reboot of the machine is mandatory!**

### I.1.5 Step-by-step: Digimat documentation

---

Since Digimat 2016.0, it is possible to install Digimat documentation before, after or automatically during Digimat software installation. It is also possible to use existing Digimat documentation when installing Digimat software (see figure I.1.13). When installing Digimat documentation separately from main Digimat software, the following step by step procedure must be followed.




Figure I.1.45: Opening prompt of the Digimat documentation installer. Follow the given instructions step-by-step.




Figure I.1.46: The destination folder for the Digimat documentation installation has to be given. A 2019.1 directory will be automatically created.




Figure I.1.47: User has to point to an existing Digimat directory. So the settings of Digimat will be automatically updated to point to this documentation directory. This field can remain blank if Digimat will be installed in a second step. In that case, when installing Digimat software, user has to select this Digimat documentation installation directory (see figure I.1.13). Note that user cannot point to a Digimat prior to Digimat 2016.0.




Figure I.1.48: The required Digimat documentation modules can be chosen individually to save disk space for the installation. In the default case as used here all modules will be installed.




Figure I.1.49: An individual name for the Digimat documentation shortcut can be specified.






Figure I.1.50: A summary of the installation details is given and can be checked. Proceeding with the "Install" button will start the installation of Digimat documentation.




Figure I.1.51: The installation of the Digimat documentation is executed.




Figure I.1.52: Finalization of the installation.

## I.1.6 Installation of Digimat on a linux machine

---

This section demonstrates the most straightforward way to create an **installation of the Digimat software on a Linux machine**.

It supposes that a Digimat license server has already been installed (see section [I.1.3](#)).

- Step 1 : Unzip installer in a temporary directory (see Figure [I.1.53](#)):  
unzip Digimat2019.1-r25963-3044-2325-Linux64bit.zip
- Step 2 : Execute Digimat installation script: ./DigimatInstall (see Figure [I.1.54](#))
- Step 3 : If accept license agreement, type 1 (see Figure [I.1.55](#))
- Step 4 : If accept the general conditions, type 1 (see Figure [I.1.56](#))
- Step 5 : Select Digimat installation directory (see Figure [I.1.57](#))
- Step 6 : Digimat installation in progress (see Figure [I.1.58](#))
- Step 7 : Introduce Digimat license adress (see Figure [I.1.59](#))
- Step 8 : End of Digimat installation (see Figure [I.1.60](#))

```
[ppj@centos7x64 temp]$ unzip Digimat2019.1-r25963-3044-2325-Linux64bit.zip
Archive:  Digimat2019.1-r25963-3044-2325-Linux64bit.zip
 extracting: Digimat2019.1Installer.zip
  inflating: README.TXT
  inflating: digimat_INSTALL.pdf
  inflating: DigimatInstall
[ppj@centos7x64 temp]$
```

Figure I.1.53: Unzip installation file.

```
[ppj@centos7x64 temp]$ ./DigimatInstall

#####
Digimat 2019.1 install script
#####

Options :
1. Install Digimat 2019.1
2. Exit script

Enter your choice :
```

Figure I.1.54: Execute installation script.

```
Please read the following license agreement.
You must accept the terms of this agreement before continuing with the installation.

Options :
1. Continue
2. Exit

Enter your choice :
1
```

Figure I.1.55: License agreement.

```

14.8 All notices will be in writing. Notices permitted or required under this Agreement shall be delivered personally (including courier service), by certified or registered mail, return receipt requested, or by confirmed facsimile transmission. Notices shall be effective upon receipt. If notice is sent to MSC, it shall be directed to the attention of the Legal Department.
14.9 Customer acknowledges and agrees that any and all consulting services performed or to be performed by MSC for Customer are independent of Customer's purchase and use of the Software licenses. Customer further agrees that payment for Software licensed hereunder is in no way dependent or in any other way associated with the commencement, completion or delivery of consulting services.
14.10 The English language version of this Agreement is legally binding in case of any inconsistencies between the English version and any translations.

Contacts:

http://www.e-Xstream.com
info@e-Xstream.com
-----

Do you accept the agreement ?
Options :
1. Yes (Continue)
2. No (Exit)

1

```

Figure I.1.56: General conditions.

```

Digimat 2019.1 installation requires 3.6 GB of disk space

Write permissions are required in target installation directory

Enter target installation directory (example : /msc). A directory /Digimat/2019.1 will be automatically created :

```

Figure I.1.57: Select Digimat installation directory.

```

inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/SCA/libMXP_22_0.so
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libDeFeaPSRelated.so
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libicudata.so
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libicudata.so.60
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libicu18n.so
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libicu18n.so.60
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libicuio.so
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libicuio.so.60
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libicuuc.so
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libicuuc.so.60
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libJavaSCAModule.so
inflating: /home/ppj/Digimat/2019.1/Digimat/lib/xfg/libkernel_io.so

```

Figure I.1.58: Digimat installation progress.

```
Unzipping of Digimat completed.

Creation of DIGIMAT_Settings.ini file in /home/ppj/Digimat/2019.1/Digimat/exec

Please enter host name or ip address of license server (syntax : @host, @ip_address, port@host, ...) or full path to license file :
█
```

Figure I.1.59: License server adress.

```
In order to complete Digimat installation, environment variable DIGIMAT_BIN_20191 should be set to the directory containing DIGIMAT_Settings.ini (i.e., /home/ppj/Digimat/2019.1/Digimat/exec)

Please, note that, since Digimat 6.0.1, Digimat third-party libraries for Digimat-CAE analyses have been moved from /home/ppj/Digimat/DigimatCAE/2019.1/lib to /home/ppj/Digimat/2019.1/Digimat/lib. The paths used in your queuing system to define the position of these libraries must be updated to this new position to be able to run Digimat-CAE coupled analysis.
```

Figure I.1.60: End of Digimat installation.



# Installation **1.2**

## Licensing system

---

I.2.1	Licensing system . . . . .	<b>108</b>
	Floating licenses . . . . .	108
	Floating licenses and redundant license servers . . . . .	109
	Node-locked licenses . . . . .	109
I.2.2	Digmat licensing usage . . . . .	<b>110</b>
	License features . . . . .	110
	Usage of licenses . . . . .	110
I.2.3	Set-up of the licensing system . . . . .	<b>112</b>
	Windows . . . . .	112
	Linux . . . . .	112
	Manual start of the license server . . . . .	112
I.2.4	Configuration of the licensing system . . . . .	<b>114</b>
	Encryption key management . . . . .	114
I.2.5	MSC One licensing system . . . . .	<b>116</b>
	Encryption key management . . . . .	116
I.2.6	MSC One licensing system . . . . .	<b>117</b>
	Encryption key management . . . . .	117

---

### I.2.1 Licensing system

---

Digmat licensing is based on the MSC license manager. It enables the following types of licensing:

- paid-up or lease agreement
- floating (seat-based or MSC One) or node-locked (file based) licenses. Masterkey license system is not supported for Digimat products.

For an overview over the currently supported version of the licensing system, please refer to the appendix [II.2.1](#). For information about the current limitations in the set up of licensing systems, please refer to appendix [??](#).

#### Floating licenses

---

Floating licenses enable to have access, from anywhere on a network, to Digimat licenses. Such system, providing licenses to Digimat when a job is executed, is called a license server. So that this works properly, the license server must continuously run on one of the network computers. If the license server is down for any reason, the licenses will not be accessible and Digimat jobs will not run.

The license server is basically made of three parts.

- **lmgrd** is the license manager. It deals with requests coming from the software (in this case Digimat products), and redirects these requests to the vendor specific server. It also manages all the vendor specific servers under its responsibility.
- **VENDOR MSC** is the **MSC** specific server. It answers to requests coming from **lmgrd** based on the vendor specific license files and the history of use of the licenses.
- **license.dat** is the **e-Xstream engineering** specific license file. It contains information about the licensed Digimat products available to the user. Floating license files start with the following two headlines
  - SERVER ...
  - VENDOR MSC...

while it is not the case for node-locked licenses.

If those two heading lines are not present, this means the license file actually contains node-locked licenses. If this is not what you were expecting to receive, it is suggested to contact the support team of **e-Xstream engineering** at [digmat.support@mscsoftware.com](mailto:digmat.support@mscsoftware.com).

**In order to have a valid-working licensing installation, these three components must have been installed and lmgrd must be running!**

When running a Digimat job, a first request is sent to **lmgrd** in order to check out the required licenses, which depends on the Digimat product that is executed.

After this first request is addressed to **lmgrd**, periodic connections are made by the Digimat product with **lmgrd** to check that the server and license status are still valid. These periodic connections are called 'heartbeats' and are usually made every minute.

If the connection to the license server is lost by the Digimat product (in other words if several heartbeats failed), a reconnection strategy is started. Depending on the Digimat product running, the number of reconnection attempts as well as the time interval between two tries varies. This information is printed in the log file or in dialog boxes used by the Digimat product. If the reconnection does not occur for some reason, the product exits, abruptly stopping any on-going simulation.

If no more licenses are available, queuing system will be automatically triggered for Digimat-CAE structural analysis. Queuing system will be valid during 10 hours. If, after 10 hours, no license is available, process will stop.



*Remark:* If requesting more CAE tokens than total available in license file (e.g., license file has only 3 parallel CAE tokens and analysis tries to run with 8 CPUs), queuing system will be triggered and will remain during 10 hours before stopping execution. It is needed to manually stop the executable in this case.

Licensing utilities are provided with MSC license system (**lmttools** and related utilities). These can be used to manage the license server by allowing server starts and stop actions, as well as license changes.

### Floating licenses and redundant license servers

---

In the single license server configuration, licenses are not available when the license server is down, disconnected from the network or if the **lmgrd** daemon has been shut down.

If it is mandatory for licenses to be available all the time, then a redundant server setup can be the solution. In that case, three servers (and exactly three) are running rather than one. If at least two of the three servers are available, users are able to checkout licenses. These three redundant servers must be well interconnected, as they will exchange information periodically, i.e., heartbeats, and at each license checkout.

For redundant server configuration, the license file contains three SERVER lines. Compared to the single server configuration, these SERVER lines must contain a port number at the end of the line.

The three servers will find each other using their host names. Therefore, domain name information for the three servers must be up to date.

To start the servers, the procedure is the same as for the single server configuration, and must be repeated on each of the redundant servers.

On the client side, the address of the three servers must be used to benefit from the redundancy.

### Node-locked licenses

---

Floating licenses are not mandatory. It is also possible as well as sometimes useful to use a single node-locked license file, especially for laptops when not having constant access to a network that would provide a floating license. If using node-locked licenses, the installation of a license server is not required. Notice though that a node-locked license points towards the physical address of a computer, which means it is attributed to a single specific computer and cannot be transferred on other ones.

## I.2.2 Digimat licensing usage

---

In the following, the Digimat specific usage of the MSC licensing system will be described.

### License features

---

A sample license feature exhibits the following structure and underlying information.

```
FEATURE EX_DIGIMAT_MF MSC 2018.0915 15-sep-2018 10 97D99962A5CD \
ISSUED=19-mar-2018 ck=135 \
SN=1310166-2307296e44eb55ad2285-6ba1-b8debee3b70d316f2d90552ee1e6eed41f
```

- *EX\_DIGIMAT\_MF*: It refers to the feature name. It refers to a product of the Digimat suite, or to an interface between Digimat and an external code.
- *2018.0915*: It refers to the maintenance end date (the format being yyyy.mmdd) . This tells for which versions of the software the license is valid. Every Digimat release has an official release date that is compared against that maintenance date in order to allow or block its usage.
- *15-sep-2018*: This is the end date, i.e., date until which the license feature is valid.
- **10**: This is the total number of seats available for the corresponding license feature.

### Usage of licenses

---

Digimat licenses usage depends on the features considered.

- When starting any product of Digimat platform (except Digimat-CAE GUI), the existence of a feature is verified but also the availability of a seat of the required license feature. If no seat is available, those products cannot be opened. If a seat is available, it will immediately be checked-out and the product will open.
- At the start-up of the Digimat-CAE GUI, a check on the existence of a structural license is performed: it could also be one of the three features referring to structural analyses:
  - EX\_DIGIMAT\_CAE\_STRUCTURAL
  - EX\_DIGIMAT\_CAE\_LINEAR
  - EX\_DIGIMAT\_CAE\_FATIGUE

If any of these exists, the GUI opens successfully. Then, when defining the interface code the user intends to work with, the existence of the license feature of the selected interface is again verified. It could also be one of the global flexible license features. If none exists, the interface cannot be selected. A similar verification is performed when selecting the injection interface format.

Up to now, no license feature is consumed. This is done when executing the Digimat-CAE job to generate the interface files. It is also done when executing a coupled structural Digimat job. In such case, the license features, both structural and injection, are checked out during the entire simulation. They are checked in once the job is over.

In case of *parallel computation*, one structural feature seat is first used, and for the other  $n-1$  processors used for the parallel computation,  $n-1$  Digimat tokens are checked out. For example, a Digimat-CAE/LS-DYNA parallel run on 4 processors consumes 1 seat of a structural feature as well as 3 Digimat tokens. When performing parallel computations using distributed storage devices, Digimat requires the DIGIMAT2CAE\_Working\_Directory setting to be defined in your DIGIMAT\_Settings.inifile (see Section 1.4.1). This setting has to indicate a global, unique, location which can be accessed by all the processes.

**If this setting is not defined, it can result in an overconsumption of license features!**

- Finally, in the case of Digimat-MX, one EX\_DIGIMAT\_MX+ (tried first) or EX\_DIGIMAT\_MX feature seat is consumed at the moment the GUI opens. No more seat is required at any time. When performing a reverse-engineering, no EX\_DIGIMAT\_MF seat is required though the Digimat executable is used.
- To encrypt files, a EX\_DIGIMAT\_MX+ feature is required.
- To use encrypted files and decrypt them in the Digimat products, user needs the EX\_DIGIMAT\_CRYPT feature. Without this, the user cannot use the encrypted files provided in the Digimat-MX database by the material suppliers.

For more information, please contact the support team at [digimat.support@mscsoftware.com](mailto:digimat.support@mscsoftware.com).

### I.2.3 Set-up of the licensing system

---

In order to set-up Digimat licensing, the executable **mssc\_licensing\_11.16.3.exe** available at MSC Download Center (MSC licensing page) needs to be run from the installation medium and the installation steps followed. This setup allows to

- install **MSC**, **lmgrd** as well as license management tools;
- start **lmgrd**.

For a step-by-step example for the standard installation of the MSC license server via the provided installer, please refer to section [I.1.3](#).

If a **lmgrd** server is already running on a computer, only **MSC** can be installed and the previous installation of **MSC** server be used to manage **MSC**.

**e-Xstream engineering recommends proceeding with the complete installation and using a separate lmgrd process, not a previously installed one!**

For further details, please consult the **mssc\_licensing\_11.16.3\_doc\_user.pdf** user guide available on MSC Download Center (MSC licensing page).

#### Windows

---

Under Windows, **lmgrd** should be started at the end of the installation procedure. **lmgrd** is installed as a Windows service. Windows services are restarted automatically after a reboot. Notice that it is *required to be logged as administrator* in order to install a Windows service.

#### Linux

---

Under Linux, **lmgrd** should also be started at the end of the installation procedure but this starting process will be active only till the next reboot of the Linux machine. Each time the Linux machine is rebooted, the **lmgrd** must be restarted manually (see below). There is no option as for Windows operating system to activate automatically this **lmgrd** restart.

*Remark:* The **lmgrd** server can be installed and run on a computer working with a different operating system from the one on which the Digimat software suite itself is installed and run.

#### Manual start of the license server

---

Under both operating systems, Windows as well as Linux, the license server can be started manually. The command to start the process is the following:

```
lmgrd -c Digimat.lic -l DIGIMAT.log
```

After **lmgrd** start-up, a DIGIMAT.log file is created and keeps track, among others, of the license server status as well as check-ins and check-outs of Digimat licenses.

For debugging purposes, the license server can also be started in an interactive mode. To do so, please type

```
lmgrd.exe -c Digimat.lic -l digimat.log -z
```

## I.2.4 Configuration of the licensing system

---

During Digimat installation, a valid MSC license file path is requested (see [I.1.10](#)). Value given is the written in the *DIGIMAT\_Settings.ini* file (see Section [I.4.1](#)). Most classical values are:

- **Floating licenses:**

**port@host** where “host” refers to the IP address or the host name of the computer on which runs the license server, and ‘port’ is the port to be used to establish the connection between the application and the license server (note that a port is not mandatory). Multiple license servers can be defined with different *@host* references separated by ‘:’ under Linux and ‘;’ under Windows. Example:  
 MSC\_LICENSE\_FILE = 27500@WorkStation1:@192.168.1.10

- **Node-locked license file:**

The full path to the license file and its name are required.

In the case that no value for MSC license path has been entered during Digimat installation, it is needed to define in your operating system the MSC\_LICENSE\_FILE environment variable.

### General management of MSC\_LICENSE\_FILE in Digimat:

- When running any Digimat product from **Digimat platform**,

MSC\_LICENSE\_FILE defined as environment variable is automatically appended to the value of MSC\_LICENSE\_FILE defined in *DIGIMAT\_Settings.ini*. So, if MSC\_LICENSE\_FILE defined in environment variable is different from key defined in *DIGIMAT\_Settings.ini*, the 2 values will be appended in a new MSC\_LICENSE\_FILE environment variable. So license will be checked on the whole set of license path defined in this new MSC\_LICENSE\_FILE environment variable.

- When running any Digimat product from **command line**,

MSC\_LICENSE\_FILE must be defined in global environment variable. Value defined in *DIGIMAT\_Settings.ini* won't be taken into account.

- When running any Digimat product from **plug-ins**,

MSC\_LICENSE\_FILE must be defined in global environment variable. Value defined in *DIGIMAT\_Settings.ini* won't be taken into account.

Setting the correct license location can be done by using the 'Set license location' option in the 'License' menu of the Digimat platform (see Section [I.3.1](#)). When doing this, the value of *DIGIMAT\_Settings.ini* will then be updated accordingly. Administrator rights can be needed for this operation.

## Encryption key management

---

The encryption keys needed to decrypt the material files are not managed via the license file. The keys are handled by the Digimat Platform and written in the Digimat configuration file.

Here is the procedure to be performed prior to being able to decrypt any material files :

- The encryption keys are delivered by e-Xstream engineering within files named *key\_number.priv*. If not already received please contact your Digimat support. You will have at least two encryption keys to handle, one to decrypt material files that were encrypted for you only, and one to decrypt material files that can be decrypted by everyone.

- Go to the Digimat platform to have access to the license management functionalities (see [I.3.1](#)). There you will have access to a button named **Import encryption key**. Click on the button, select your .priv file, click **OK** and then click the **Apply** button. Perform this procedure as many time you have received different encryption key files.

## I.2.5 MSC One licensing system

---

Digmat also support MSC One licensing system. MSC One licensing is such that it allows most MSC products to use a shared pool of license tokens.

All Digmat capabilities are working in the same way as with the traditional licensing system explained in the previous section, except that :

- The encryption keys needed to decrypt material files are not managed through licensing but using the Platform (see [I.2.6](#)).
- The fiber orientation estimator embedded in Digmat-RP is not available.

That licensing system is based on FlexLM 11.16 and is supported under the following operating systems :

- Windows 7 64-bit
- Windows 10 64-bit
- Linux 64-bit
- Linux IPF 64-bit
- IBM AIX 32 and 64-bit
- HP-UX PA-RISC
- HP-UX IPF 64-bits
- Solaris SPARC 64-bit
- Solaris 8664
- SGI IRIX 64-bit

Installation and usage of MSC One license system is identical to ones of seat-based license systems (please refer to sections [I.2.2](#) and [I.2.3](#)).

## Encryption key management

---

The encryption keys needed to decrypt the material files are not managed via the license file. The keys are handled by the Digmat Platform and written in the Digmat configuration file.

Here is the procedure to be performed prior to being able to decrypt any material files :

- The encryption keys are delivered by e-Xstream engineering within files named `key_number.priv`. If not already received please contact your Digmat support. You will have at least two encryption keys to handle, one to decrypt material files that were encrypted for you only, and one to decrypt material files that can be decrypted by everyone.
- Go to the Digmat platform to have access to the license management functionalities (see [I.3.1](#)). There you will have access to a button named **Import encryption key**. Click on the button, select your `.priv` file, click **OK** and then click the **Apply** button. Perform this procedure as many time you have received different encryption key files.

To be able to encrypt material data, `EX_DIGIMAT_MX+` must be in license file. This last feature is not provided by default when using MSC One licensing.



## I.2.6 MSC One licensing system

---

Digmat also support MSC One licensing system. MSC One licensing is such that it allows most MSC products to use a shared pool of license tokens.

All Digmat capabilities are working in the same way as with the traditional licensing system explained in the previous section, except that :

- The encryption keys needed to decrypt material files are not managed through licensing but using the Platform (see [I.2.6](#)).
- The fiber orientation estimator embedded in Digmat-RP is not available.

That licensing system is based on FlexLM 11.16 and is supported under the following operating systems :

- Windows 7 64-bit
- Windows 10 64-bit
- Linux 64-bit
- Linux IPF 64-bit
- IBM AIX 32 and 64-bit
- HP-UX PA-RISC
- HP-UX IPF 64-bits
- Solaris SPARC 64-bit
- Solaris 8664
- SGI IRIX 64-bit

Installation and usage of MSC One license system is identical to ones of seat-based license systems (please refer to sections [I.2.2](#) and [I.2.3](#)).

### Encryption key management

---

The encryption keys needed to decrypt the material files are not managed via the license file. The keys are handled by the Digmat Platform and written in the Digmat configuration file.

Here is the procedure to be performed prior to being able to decrypt any material files :

- The encryption keys are delivered by e-Xstream engineering within files named `key_number.priv`. If not already received please contact your Digmat support. You will have at least two encryption keys to handle, one to decrypt material files that were encrypted for you only, and one to decrypt material files that can be decrypted by everyone.
- Go to the Digmat platform to have access to the license management functionalities (see [I.3.1](#)). There you will have access to a button named **Import encryption key**. Click on the button, select your `.priv` file, click **OK** and then click the **Apply** button. Perform this procedure as many time you have received different encryption key files.

To be able to encrypt material data, `EX_DIGIMAT_MX+` must be in license file. This last feature is not provided by default when using MSC One licensing.



# Installation **I.3**

## Digimat licensing management

I.3.1	Licensing location . . . . .	120
I.3.2	Licensing status . . . . .	121

### I.3.1 Licensing location

The licensing location can be directly defined by using the "License" option of the Digimat platform (see Figure I.3.1).




Figure I.3.1: "License" option in the Digimat platform

This opens a small window (see Figure I.3.2) allowing to define the location of the license and, when using MSC One licensing, to import an encryption key which will be written in the `DIGIMAT_Settings.ini` file. This importation is not needed when using seat-based licensing since the key is already in the license file.




Figure I.3.2: Setting the licensing location via the Digimat GUI.

## I.3.2 Licensing status

Another feature is also available under the "License" option – the query of the licenses status (see Figure I.3.2). This option gives user information about the status of the licenses on the current license server. Licenses in use are seen as checked out licenses. When they are released, a check-in feature is written in the log file.



# Installation **I.4**

## **Digimat settings**

---

I.4.1	The DIGIMAT_Settings.ini file . . . . .	124
I.4.2	Structure of the DIGIMAT_Settings.ini file . . . . .	125
	Remarks . . . . .	128
I.4.3	Digimat environment variables . . . . .	129
I.4.4	Additional settings for network installations of Digimat . . . . .	131

---

### 1.4.1 The DIGIMAT\_Settings.ini file

Digimat settings are set by the `DIGIMAT_Settings.ini` file which contains a list of key-values. This file is read by Digimat each time the platform is launched to let them become the current settings. The entire Digimat installation can be parameterized by these settings.

Digimat looks in the following directories for the `DIGIMAT_Settings.ini` file:

1. in the current working directory, i.e., the directory in which the computation is run;
2. in the directory pointed to by the environment variable `DIGIMAT_BIN_20191`.

**Note that Digimat will use the first `DIGIMAT_Settings.ini` file that it finds!** Since it first looks in the current working directory, it allows using a local settings file, and if none is defined, it is not problematic as long as it can find the global settings file defined in the folder where the `DIGIMAT_BIN_20191` variable is pointing to.

The `DIGIMAT_Settings.ini` file can be modified from the platform settings menu (see Figure 1.4.1) or directly via a text editor.




Figure 1.4.1: Definition of Digimat settings.



## I.4.2 Structure of the DIGIMAT\_Settings.ini file

---

The DIGIMAT\_Settings.ini file is made of sections delimited by a line '[SectionKeyWord]', each section containing a list of lines 'key = value'.

For the current version, this file is made of a unique section which is identified by the [Default] tag as a header to the file content. The list of keys that can be used is the following:

- **DIGIMAT\_Directory**: path to the working directory used by the Digimat platform.
- **Acrobat\_Exec**: path to Adobe Reader executable, including its name.
- **Number\_of\_processors**: Number of processors of computer where Digimat is installed.
- **Working\_Directory**: path to the working directory used by Digimat.
- **log\_output**: path to the location where Digimat will output its log messages. This is one of the keys a user could most probably be brought to change. The different choices are:
  - **Default**: the Digimat messages will be output to the default location which means, for example:
    - \* in the .log file of the analysis/job if using Digimat-MF or a Digimat-CAE interface;
    - \* the dos screen when using the interface to ANSYS, ...
  - Any valid path to a file, including its name. The log messages will be output to the indicated file.
- **WISETEX\_Directory**: path to Wisetex binaries.
- **DIGIMATMF\_Directory**: path to the Digimat-MF binaries.
- **DIGIMATMF\_Working\_Directory**: path to the working directory used by Digimat-MF.
- **DIGIMATFE\_Directory**: path to the Digimat-FE binaries.
- **DIGIMATFE\_Working\_Directory**: path to the working directory used by Digimat-FE.
- **DIGIMATFE\_Solver\_Directory**: path to Digimat-FE solver directory.
- **LS-Dyna\_SMP\_Exec**: path to LS-DYNA executable used by Digimat-FE.
- **MAP\_Directory**: path to the Digimat-MAP binaries.
- **MAP\_Working\_Directory**: path to the working directory used by Digimat-MAP.
- **DIGIMATHC\_Directory**: path to the Digimat-HC binaries.
- **DIGIMATHC\_Working\_Directory**: path to the working directory used by Digimat-HC.
- **ASTER\_Directory**: path to the ASTER binaries.
- **DIGIMATRP\_Directory**: path to the Digimat-RP binaries.
- **DIGIMATVA\_Directory**: path to the Digimat-VA binaries.
- **DIGIMATAM\_Directory**: path to the Digimat-AM binaries.
- **DIGIMATVA\_Working\_Directory**:
- **DIGIMAT2CAE\_Directory**: path to the Digimat-CAE binaries.
- **DIGIMAT2CAE\_Working\_Directory**: path to the working directory used by Digimat-CAE.
- **MARC\_Directory**: path to the Marc root directory.
- **MSC\_LICENSE\_FILE**: path to the license server. The IP address must be prefixed by an @ symbol (port@address).
- **ABAQUS\_Directory**: path to the Abaqus root directory.
- **ANSYS\_Directory**: path to the ANSYS root directory.
- **MENTAT\_Directory**: path to the Mentat root directory.
- **MSCNASTRAN\_Directory**: path to the MSC Nastran root directory.
- **PATRAN\_Directory**: path to the Patran root directory.
- **PERMAS\_Directory**: path to the PERMAS root directory.
- **DIGIMATMX\_Directory**: path to the Digimat-MX binaries.
- **DIGIMATMX\_Bin\_Directory**: path to PostgreSQL binaries.
- **DIGIMATMX\_Working\_Directory**: path to the working directory used by Digimat-MX.
- **DIGIMATMX\_DataBase\_Name**: Digimat-MX default database to be opened. The default value is mxdb.
- **DIGIMATMX\_Database\_Cluster**: list of the locations (**localhost** and **server** IP addresses) of servers on which a successful connection has been made. The first listed value is the location of the server on which the last successful connection occurred and it is the default value used by Digimat-MX. If no successful connection ever occurred, **localhost** is the only value.

- **DIGIMATMX\_User**: Digimat-MX user name.
- **DIGIMATMX\_Local\_Installation**: true or false.
- **DIGIMATMX\_Request\_Data\_Format**: length of the content of the email which is automatically created when requesting data to a material supplier from Digimat-MX. The two possible values are **Long** (which is the default) and **Short** (which is usually required when using Lotus Notes as e-mail client).
- **LocalDatabase\_Directory**: path to the built-in local database.
- **DAKOTA\_Directory**: path to Dakota binaries.
- **Manual\_Directory**: path to the Digimat documentation.
- **Examples\_Directory**: path to the Digimat examples directory.
- **DIGIMATMF\_Manual\_Directory**: path to the Digimat-MF documentation. It is used by Digimat when opening the documentation (general or context help page) from the GUI.
- **DIGIMATFE\_Manual\_Directory**: path to the Digimat-FE documentation. It is used by Digimat when opening the documentation (general or context help page) from the GUI.
- **MAP\_Manual\_Directory**: path to the Digimat-MAP documentation. It is used by Digimat when opening the documentation (general or context help page) from the GUI.
- **DIGIMATHC\_Manual\_Directory**: path to the Digimat-HC documentation. It is used by Digimat when opening the documentation (general or context help page) from the GUI.
- **DIGIMAT2CAE\_Manual\_Directory**: path to the Digimat-CAE documentation. It is used by Digimat when opening the documentation (general or context help page) from the GUI.
- **DIGIMATMX\_Manual\_Directory**: path to the Digimat-MX documentation. It is used by Digimat when opening the documentation (general or context help page) from the GUI.
- **DIGIMAT2MARC\_Directory**: path to the directory containing Digimat-CAE/Marc executable (see Section 1.5.3).
- **DIGIMAT2SAMCEF\_Directory**: path to the directory containing Digimat-CAE/SAMCEF executable (see Section 1.5.5).
- **HYPERWORKS\_Directory**: path to the HyperWorks root directory.
- **LSDYNA\_Directory**: path to the directory containing Digimat-CAE/LS-DYNA executable (see Section 1.5.6).
- **LSPREPOST\_Directory**: path to the LS-PrePost root directory.
- **OPTISTRUCT\_Directory**: path to the OptiStruct root directory.
- **PAMCRASH\_Directory**: path to the PAM-CRASH root directory.
- **SAMCEF\_Directory**: path to the Samcef root directory.
- **VISUALVIEWER\_Directory**: path to the Visual-Viewer root directory.
- **GnuPG\_Directory**: path to GnuPG directory. needed to encrypt material properties when using Macro solution in Digimat-RP for LS-DYNA.
- **LSTC\_PGPKEY**: Full path and name of key file needed to encrypt material properties when using Macro solution in Digimat-RP for LS-DYNA. Default location value is Digimat working directory and default name is `lstc_pgpkey.asc`. This entry is generated during Digimat installation. The way to generate this key is explained in section 1.5.6.

All these parameters can be set from the Digimat platform settings manager (see Figure 1.4.1).

An example of a valid DIGIMAT\_Settings.ini file is:

```
[Default]
DIGIMAT_Directory=C:\MSC.Software\Digimat\2019.1\Digimat\exec
Acrobat_Exec=C:\Program Files (x86)\Adobe\Acrobat Reader DC\Reader\AcroRd32.exe
Number_of_processors=16
Working_Directory=C:\MSC.Software\Digimat\working
log_output=Default
WISETEX_Directory=C:\MSC.Software\Digimat\2019.1\Digimat\external32\wisetex
DIGIMATMF_Directory=C:\MSC.Software\Digimat\2019.1\DigimatMF\exec
DIGIMATMF_Working_Directory=C:\MSC.Software\Digimat\working
DIGIMATFE_Directory=C:\MSC.Software\Digimat\2019.1\DigimatFE\exec
DIGIMATFE_Working_Directory=C:\MSC.Software\Digimat\working
DIGIMATFE_Solver_Directory=C:\MSC.Software\Digimat\2019.1\Digimat\external64\FESolver
LS-Dyna_SMP_Exec=C:\Temp\ls-dyna_smp_d_R930_winx64_ifort131.exe
MAP_Directory=C:\MSC.Software\Digimat\2019.1\DigimatMAP\exec
MAP_Working_Directory=C:\MSC.Software\Digimat\working
DIGIMATHC_Directory=C:\MSC.Software\Digimat\2019.1\DigimatHC\exec
DIGIMATHC_Working_Directory=C:\MSC.Software\Digimat\working
```

```
ASTER_Directory=C:\MSC.Software\Digimat\2019.1\DigimatHC\Code_Aster81
DIGIMATRP_Directory=C:\MSC.Software\Digimat\2019.1\DigimatRP\exec
DIGIMATVA_Directory=C:\MSC.Software\Digimat\2019.1\DigimatVA\exec
DIGIMATAM_Directory=C:\MSC.Software\Digimat\2019.1\DigimatAM\exec
DIGIMATVA_Working_Directory=C:\MSC.Software\Digimat\working
DIGIMAT2CAE_Directory=C:\MSC.Software\Digimat\2019.1\DigimatCAE\exec
DIGIMAT2CAE_Working_Directory=C:\MSC.Software\Digimat\working
DIGIMAT2CAE_WBWizard_Format=cdb
MARC_Directory=C:\MSC.Software\Marc\2018.1.0\marc2018.1
MSC_LICENSE_FILE=27500@10.100.103.211
ABAQUS_Directory=C:\SIMULIA\Commands
ANSYS_Directory=C:\Program Files\ANSYS Inc\v193
MENTAT_Directory=C:\MSC.Software\Marc\2018.1.0\mentat2018.1
MSCNASTRAN_Directory=C:\MSC.Software\MSC_Nastran\20190
PATRAN_Directory=C:\MSC.Software\Patran_x64\20170
ALTAIR_Directory=C:\Program Files\Altair\2018
PERMAS_Directory=C:\Program Files\INTES\V16
DIGIMATMX_Directory=C:\MSC.Software\Digimat\2019.1\DigimatMX\exec
DIGIMATMX_Bin_Directory=C:\MSC.Software\Digimat\2019.1\DigimatMX\bin
DIGIMATMX_Working_Directory=C:\MSC.Software\Digimat\working
DIGIMATMX_DataBase_Name=mxdb
DIGIMATMX_Database_Cluster=localhost
DIGIMATMX_User=manager
DIGIMATMX_Local_Installation=false
DIGIMATMX_Request_Data_Format=Long
LocalDatabase_Directory=C:\MSC.Software\Digimat_LocalDatabases\2019.1\postgresql
LocalDatabase_SQLite_Directory=C:\MSC.Software\Digimat_LocalDatabases\2019.1\sqlite
DAKOTA_Directory=C:\MSC.Software\Digimat\2019.1\Digimat\external32\dakota
DIGIMATMX_Crypt_ForAll=3082037D020100300D06092A864886F70D010101050004820367308203630201000281BC0B43EBEEDB6...
GnuPG_Directory = C:\Program Files (x86)\gnupg\bin
LSTC_PGPKEY = C:\MSC.Software\Digimat\working\lstc_pgpkey.asc
Manual_Directory=C:\MSC.Software\Digimat_Documentation\2019.1\doc
Examples_Directory=C:\MSC.Software\Digimat_Documentation\2019.1\examples
DIGIMATMF_Manual_Directory=C:\MSC.Software\Digimat_Documentation\2019.1\doc
DIGIMATFE_Manual_Directory=C:\MSC.Software\Digimat_Documentation\2019.1\doc
MAP_Manual_Directory=C:\MSC.Software\Digimat_Documentation\2019.1\doc
DIGIMATHC_Manual_Directory=C:\MSC.Software\Digimat_Documentation\2019.1\doc
DIGIMAT2CAE_Manual_Directory=C:\MSC.Software\Digimat_Documentation\2019.1\doc
DIGIMATMX_Manual_Directory=C:\MSC.Software\Digimat_Documentation\2019.1\doc
```

---

**Remarks**

---

- The listing order of the keywords does not matter.
- Trailing or leading white spaces, tabulations, or quotations marks ( ' ) are removed from the values.
- The initial keyword [Default] must be defined.
- A path including directories with long names can be written in short notation, e.g.,  
C:\Progra~1\Digimat.

### I.4.3 Digimat environment variables

---

Under Windows platform, DIGIMAT\_BIN\_20191 environment variables is defined when running a product from the Digimat platform or when running product directly from Start Menu. Since Digimat 2018.1, DIGIMAT\_BIN\_20191 is not defined automatically during the installation of Digimat. Value can be changed through the Digimat environment variables manager accessible from the Digimat platform top menu bar only in administrator mode.




Figure I.4.2: Definition of Digimat environment variables

DIGIMAT\_BIN\_20191 environment variable is used to find the DIGIMAT\_Settings.ini file if it is not located in the working directory. When running Digimat products, this environment variable points towards the directory containing the DIGIMAT\_Settings.ini file defined during Digimat installation. User can also defined a global environment variable DIGIMAT\_BIN\_20191 pointing to another location. In this case, when running a Digimat product, this global environment value will override the one that is defined in the Digimat product launching scripts.

*Remark:* When using Digimat-CAE plugins (Abaqus, ANSYS and Mentat), it is mandatory to define the global DIGIMAT\_BIN\_20191 environment variable as pointing to a valid directory containing DIGIMAT\_Settings.ini file, e.g.,

C:\MSC.Software\Digimat\2019.1\Digimat\exec

Under Linux platform, the `DIGIMAT_BIN_20191` environment variable must always be set manually to point on a valid `DIGIMAT_Settings.inifile`.

During Digimat installation, path to the shortcuts folder, containing the file that launches the Digimat platform is added to the system environment variable `PATH`.

---

## I.4.4 Additional settings for network installations of Digimat

---

When using a network-based installation of Digimat, i.e., Digimat being installed on a “server” machine which is being accessed from several “client” machines, the environment variable `DIGIMAT_FONT_CACHE` should be defined on each client machine, with a value corresponding to a directory **local** to the client machine with write access. This directory will contain the files related to the font cache specific to the client machine, which will be automatically created the first time they are needed. This creation operation may take up to several minutes but will happen only once, provided that the font cache directory is not modified or deleted.

*Remark:* Defining the `DIGIMAT_FONT_CACHE` environment variable is only needed for client machines, not for the server machine.





# Installation **1.5**

## Digmat-CAE Interfaces

---

I.5.1	Digmat-CAE/Abaqus . . . . .	<b>134</b>
	Installation procedure . . . . .	134
	Abaqus environment file abaqus_v6.env . . . . .	135
	Running coupled Digimat-CAE/Abaqus analysis . . . . .	137
	Digmat-to-Abaqus plugin installation . . . . .	138
I.5.2	Digmat-CAE/ANSYS . . . . .	<b>140</b>
	Digmat-CAE/ANSYS for Windows . . . . .	140
	Digmat-CAE/ANSYS Workbench ACT plugin for Windows . . . . .	145
	Digmat-CAE/ANSYS for Linux . . . . .	146
	Configuration of Remote Solve Manager . . . . .	146
I.5.3	Digmat-CAE/Marc . . . . .	<b>148</b>
	Installation procedure . . . . .	148
	Windows platforms . . . . .	148
	Linux platforms . . . . .	150
	Installation of the Digimat plugin for Marc Mentat . . . . .	150
I.5.4	Digmat-CAE/MSC Nastran SOL400 . . . . .	<b>152</b>
	Installation procedure . . . . .	152
I.5.5	Digmat-CAE/SAMCEF . . . . .	<b>153</b>
	Installation procedure . . . . .	153
I.5.6	Digmat-CAE/LS-DYNA . . . . .	<b>157</b>
	Installation procedure . . . . .	157
	Linux platforms . . . . .	157
	Windows platform . . . . .	159
	Licensing for Digimat-CAE/LS-DYNA computations . . . . .	161
	Generation of encryption key file for Macro solution . . . . .	161
I.5.7	Digmat-CAE/PAM-CRASH . . . . .	<b>162</b>
	Installation procedure . . . . .	162
	Dynamic libraries . . . . .	162
I.5.8	Digmat-CAE/MSC Nastran SOL1XX . . . . .	<b>165</b>
	Installation procedure . . . . .	165
I.5.9	Digmat-CAE/OptiStruct . . . . .	<b>166</b>
	Installation procedure . . . . .	166
I.5.10	Digmat-CAE/PERMAS . . . . .	<b>167</b>
	Installation procedure . . . . .	167
I.5.11	Digmat-CAE/nCode DesignLife . . . . .	<b>168</b>
I.5.12	Digmat-CAE/ANSYS Fluent . . . . .	<b>169</b>
	Installation procedure . . . . .	169
	Digmat-CAE/ANSYS Fluent for Windows . . . . .	169

---

### I.5.1 Digimat-CAE/Abaqus

---

The objective of this section is to explain how to install the interface between Digimat and Abaqus. For more information concerning supported Abaqus releases and platforms, please refer to the appendix [II.3.1](#).

#### Installation procedure

---

Digimat-CAE/Abaqus is provided as a set of dynamic libraries. These libraries contain Digimat capabilities, allowing the use of Digimat materials in Abaqus analyses. This link can be performed on both Linux and Windows operating systems.

Dynamic libraries are version dependent. For example, this means that libraries provided for Abaqus 2019 cannot be used with previous Abaqus versions.

Dynamic libraries are located in the directory

`DIGIMAT_DIR/DigimatCAE/exec/digi2aba`

of the Digimat installation. `DIGIMAT_DIR` is Digimat installation directory, e.g.,

- Under Windows `C:\MSC.Software\Digimat\2019.1`
- Under Linux `/opt/software/Digimat/2019.1`.

This directory contains subfolders, each subfolder corresponding to a given supported Abaqus versions. Each of these folders contains three dynamic libraries:

- One single precision library for Abaqus/Explicit: `explicitU.dll` (Windows) or `libexplicitU.so` (Linux)
- One double precision library for Abaqus/Explicit: `explicitU-D.dll` (Windows) or `libexplicitU-D.so` (Linux)
- One double precision library for Abaqus/Standard: `standardU.dll` (Windows) or `libstandardU.so` (Linux)

`digi2aba` directory also contains dynamic libraries for Digimat kernel (those libraries are common for all Abaqus versions):

- One single precision library for Abaqus/Explicit:
  - `digi2abaExp.dll` (Windows)
  - `libdigi2abaExp.so` (Linux)
- One double precision library for Abaqus/Explicit:
  - `digi2abaExpDouble.dll` (Windows)
  - `libdigi2abaExpDouble.so` (Linux)
- One double precision library for Abaqus/Standard:
  - `digi2abaStd.dll` (Windows)
  - `libdigi2abaStd.so` (Linux)

Finally, third-party components

- `boost_chrono-mt.dll`
- `boost_filesystem-mt.dll`
- `boost_regex-mt.dll`
- `boost_system-mt.dll`
- `boost_thread-mt.dll`
- `digimathdf5.dll`
- `digimathdf5_cpp.dll`
- `digimathdf5_hl.dll`
- `digimathdf5_hl_cpp.dll`

- digimatMathTools.dll
- digimatPocoFoundation.dll
- impi.dll
- lapi.dll
- tinyxmlSTL.dll

are located in digi2aba directory under Windows and in Digimat/lib directory under Linux. If the location of the dynamic libraries is changed, usub\_lib\_dir variable defined in abaqus\_v6.env file must be changed accordingly (see below for abaqus\_v6.env configuration).

### Abaqus environment file abaqus\_v6.env

---

An environment file abaqus\_v6.env is provided with the Digimat installation for each supported Abaqus version. This file depends on the parallelization that will be used:

- Shared Memory Parallelization SMP: mp\_mode=THREADS
- Distributed Memory Parallelization DMP: mp\_mode=MPI

This environment file depends on targetted Abaqus version. For example, if Abaqus 2019 is targetted, it is needed to use abaqus\_v6.env files located in directory:

```
DIGIMAT_DIR/DigimatCAE/exec/digi2aba/2019/DMP
DIGIMAT_DIR/DigimatCAE/exec/digi2aba/2019/SMP
```

where DIGIMAT\_DIR is Digimat installation directory, e.g., C:\MSC.Software\Digimat\2019.1.

### Abaqus environment file abaqus\_v6.env for Windows platforms

If DIGIMAT\_DIR is Digimat installation directory, e.g., C:\MSC.Software\Digimat\2019.1, and if Abaqus targetted version is 2019, abaqus\_v6.env environment file provided in Digimat installation contains following information:

- Path to Digimat-CAE/Abaqus libraries and its dependencies:
 

```
usub_lib_dir=r"DIGIMAT_DIR\DigimatCAE\exec\digi2Aba\2019"
usub_lib_dir+="DIGIMAT_DIR\DigimatCAE\exec\digi2Aba"
```
- Path to plugin directory:
 

```
plugin_central_dir=r"DIGIMAT_DIR\DigimatCAE\exec\digi2Aba\abaqus_plugins"
```
- Abaqus version:
 

```
os.environ["ABAQUS_VERSION"] = "2019"
```
- Parallelization method information:
  - For SMP computations:
 

```
mp_mode=THREADS
```
  - For DMP computations:
 

```
cpus = globals().get("cpus", locals().get("cpus", 1))
standard_parallel=ALL
os.environ["ABA_MPI_SKIP_BUNCH_NODES"] = "1"
mp_host_list = [[socket.gethostname(), 1]]*cpus
mp_mode=MPI
```

Environment variable ABA\_MPI\_SKIP\_BUNCH\_NODES is needed to force pure DMP computations.

More information about the Abaqus environment file are provided in Abaqus documentation (Environment file settings section).

**Abaqus environment file abaqus\_v6.env for Linux platforms**

If DIGIMAT\_DIR is Digimat installation directory, e.g., /opt/msc/Digimat/2019.1 and if Abaqus targetted version is 2019, abaqus\_v6.env environment file provided in Digimat installation contains following information:

- Path to Digimat-CAE/Abaqus libraries and its dependencies:
 

```
usub_lib_dir='DIGIMAT_DIR/DigimatCAE/exec/digi2aba'
usub_lib_dir+='DIGIMAT_DIR/DigimatCAE/exec/digi2aba/2019'
usub_lib_dir+='DIGIMAT_DIR/Digimat/lib'
```
- Abaqus version:
 

```
os.environ['ABAQUS_VERSION'] = '2019'
```
- Environment variables to be passed to Abaqus computations:
 

```
os.environ['DIGIMAT_BIN_20191'] = 'DIGIMAT_DIR/Digimat/exec'
os.environ['MSC_LICENSE_FILE'] = '27500@hostname'
os.environ['FLEXLM_TIMEOUT'] = '5000000'
mp_environment_export =
tuple(list(mp_environment_export)+['DIGIMAT_BIN_20191'] + ['MSC_LICENSE_FILE']
+ ['FLEXLM_TIMEOUT'])
```

Definition of FLEXLM\_TIMEOUT environment variable can be needed when using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.

- Parallelization method information:
  - For SMP computations:
 

```
standard_parallel=ALL
mp_mode=THREADS
cpus=globals().get('cpus',locals().get('cpus',1))
mp_host_list=[]
```
  - For DMP computations:
 

```
os.environ['ABA_MPI_SKIP_BUNCH_NODES'] = '1'
standard_parallel=ALL
mp_mode=MPI
cpus=globals().get('cpus',locals().get('cpus',1))
mp_host_list=[]
```

Environment variable ABA\_MPI\_SKIP\_BUNCH\_NODES is needed to force pure DMP computations. Environment variable mp\_host\_list=[] must be completed with list of hosts where Digimat-CAE/Abaqus computation will run, e.g., to run on 2 nodes named node1 and node2 and 4 CPUs on each node:

```
mp_host_list = [['node1', 4], ['node2', 4]]
```

- For mixed SMP/DMP computations:
 

```
standard_parallel=ALL
mp_mode=MPI
cpus=globals().get('cpus',locals().get('cpus',1))
mp_host_list=[]
```

Environment variable mp\_host\_list=[] must be completed with list of hosts where Digimat-CAE/Abaqus computation will run, e.g., to run on 2 nodes named node1 and node2 and 4 CPUs on each node:

```
mp_host_list = [['node1', 4], ['node2', 4]]
```

More information about the Abaqus environment file are provided in Abaqus documentation (Environment file settings section).

## Running coupled Digimat-CAE/Abaqus analysis

### Windows platforms

To run Digimat to Abaqus coupled analysis using command line, it is needed to copy the `abaqus_v6.env` of targetted Abaqus version and parallelization method (SMP or DMP) from Digimat installation directory to working directory. Once it is done, following script example can be used:

```
set FLEXLM_TIMEOUT=5000000
set MSC_LICENSE_FILE=27500@localhost
C:\Simulia\Commands\abaqus.bat job=test.inp cpus=N
```

First line is needed when using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for `FLEXLM_TIMEOUT` is 5000000. Definition of `MSC_LICENSE_FILE` is needed if it is not defined as a global environment variable. `N` is the number of threads (SMP) or domains (DMP).

When running Digimat-CAE/Abaqus coupled simulations using Digimat-RP, it is not needed to take care on copying `abaqus_v6.env` file. User has just to select Abaqus location in Digimat-RP settings (see Figure I.5.1) and to select SMP or DMP computation in Digimat-RP GUI when running simulation (see Figure I.5.2).




Figure I.5.1: Setting Abaqus location in Digimat-RP.

### Linux platforms

To run Digimat to Abaqus coupled analysis, it is needed to copy the `abaqus_v6.env` of targetted Abaqus version and parallelization method (SMP or DMP) from Digimat installation directory to working directory.




Figure I.5.2: Choice of parallelization method in Digimat-RP.

abaqus\_v6.env file can also be generated "on the fly" by launching script, based on what is provided in Digimat installation.

As soon as abaqus\_v6.env file exists in working directory, coupled Digimat-CAE/Abaqus simulation can run using command:

```
/opt/DassaultSystemes/SIMULIA/Commands/abaqus job=test.inp cpus=N
```

where N is the targetted number of threads (SMP) or domains (DMP).

## Digimat-to-Abaqus plugin installation

The path to the Abaqus installation must be specified during the installation of Digimat. The Digimat plugins are automatically installed for this version of Abaqus, e.g., if Abaqus targetted version is 2019, the required script files are copied to the folder:

```
C:\SIMULIA\CAE\2019\abaqus_plugins
```

To use the plugins in another version of Abaqus, you can either:

- Copy the abaqus\_plugins folder to the appropriate Abaqus installation folder
- Add (or edit) the following line in the default abaqus\_v6.env file:

```
plugin_central_dir = r"DIGIMAT_DIR\DigimatCAE\exec\digi2Aba\abaqus_plugins\"
```

where DIGIMAT\_DIR is the Digimat installation directory, e.g., C:\MSC.Software\Digimat\2019.1.

### Remark:

- If you did both operations (e.g. copy the abaqus\_plugins folder and edit the abaqus\_v6.env file), Abaqus will warn you at startup that duplicate scripts files are found, and will use the ones from the abaqus\_plugins folder. So if you want to use a different version of the plugin with Abaqus, you shall modify those abaqus\_plugins files.
- The Abaqus default working directory (typically C:/Temp may contain residual files from previous installations; e.g., an abaqus\_plugins folder, a DIGIMAT\_Settings.ini file, and a abaqus\_v6.env file. These files must be removed manually for the plugin to behave correctly.
- To be able to use plugin, it is mandatory to define global DIGIMAT\_BIN\_20191 environment variable pointing to the Digimat directory containing DIGIMAT\_Settings.inifile, e.g., C:\MSC.Software\Digimat\2019.1\Digimat\exec

- The plugin version and the Digimat version are independent, e.g., you can use a version of the plugin with a different Digimat version:
  - The plugin version is given directly in the plugin script files;
  - The Digimat version used by the plugin (e.g. to generate the interface file, call Digimat-MX, etc.) is determined through the `DIGIMAT_BIN_20191` environment variable;
  - The Digimat version used to run Digimat/Abaqus coupled analyses is given in the `abaqus_v6.env` file by the `usub_lib_dir` line.

## I.5.2 Digimat-CAE/ANSYS

---

The objective of this section is to explain how to install the interface between Digimat and ANSYS.

Digimat-CAE/ANSYS is provided as a set of dynamic libraries. These libraries contain Digimat capabilities, allowing to use Digimat materials in ANSYS analyses.

For more information concerning supported ANSYS releases and platforms, please refer to the appendix [II.3.1](#).

### Digimat-CAE/ANSYS for Windows

---

Dynamic libraries are version dependent. For example, it means that libraries provided for ANSYS 2019R1 cannot be used with previous ANSYS versions. Dynamic libraries are located in the directory

`DIGIMAT_DIR\DigimatCAE\exec\digi2ansys`

of Digimat installation. `DIGIMAT_DIR` is main Digimat installation directory, e.g.,

`C:\MSC.Software\Digimat\2019.1`

This directory contains subfolders, each subfolder corresponding to a given supported ANSYS versions. Each of these folders contains subfolders corresponding to the different supported parallelization versions:

- SMP folder for Shared Memory Parallelization.
- DMP\_INTELMPI folder for Distributed Memory parallelization using Intel-MPI.
- DMP\_PCMPPI folder for Distributed Memory parallelization using Platform-MPI.
- DMP\_MSMPPI folder for Distributed Memory parallelization using Microsoft-MPI.

Each of these folders contains three dynamic libraries needed by ANSYS:

- UserMatLib.dll
- USolBegLib.dll
- USolFinLib.dll

`digi2ansys` directory also contains dynamic library `digi2ansys.dll` containing Digimat kernel. This library is common for all ANSYS versions. Finally, third-party components

- `boost_chrono-mt.dll`
- `boost_filesystem-mt.dll`
- `boost_regex-mt.dll`
- `boost_system-mt.dll`
- `boost_thread-mt.dll`
- `digimathdf5.dll`
- `digimathdf5_cpp.dll`
- `digimathdf5_hl.dll`
- `digimathdf5_hl_cpp.dll`
- `digimatMathTools.dll`
- `digimatPocoFoundation.dll`
- `impi.dll`
- `lapi.dll`
- `tinyxmlSTL.dll`

are located in `digi2ansys` directory.

In order to use Digimat-CAE/ANSYS in command line or via Digimat ACT plugin (see section [I.5.2](#)), following manual operations are needed:



- The PATH environment variable must be updated by prepending it the path to Digimat to ANSYS directory, e.g.,

C:\MSC.Software\Digimat\2019.1\DigimatCAE\exec\digi2Ansys

The procedure to edit the PATH environment variable is detailed below.

**Remark:**

- It is recommended to *prepend* the digi2Ansys directory to the PATH, not to *append* it.
- The PATH should contain only once the digi2Ansys directory.

- The environment variable ANS\_USER\_PATH must be defined and must point to the directory containing the required dynamic libraries. ANS\_USER\_PATH value depends on the parallelization method that will be used for the Ansys solver:

- **SMP**: Point the environment variable to the sub-folder called SMP
- **DMP - Intel-MPI**: Point the environment variable to the sub-folder called DMP\_INTELMPI
- **DMP - Platform-MPI**: Point the environment variable to the sub-folder called DMP\_PCMPPI
- **DMP - MS-MPI**: Point the environment variable to the sub-folder called DMP\_MSMPPI

**Remark:**

- When using ANSYS Workbench, the default MPI library is Intel-MPI.
- If the ANS\_USER\_PATH variable is incorrectly defined, the ANSYS computation may still run, but yield incorrect results (null stress everywhere and deformation localized around boundary conditions).

- MSC\_LICENSE\_FILE environment variable must be defined and must point to the license server address (including port number).
- FLEXLM\_TIMEOUT environment variable can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.

The environment variables can be accessed by Control panel in "System and Security" section. The "Advanced settings" will contain a choice to set "Environment variables...". Please refer to Figures 1.5.3 to 1.5.5 for an example related to Windows 10 operating system.

Alternatively, when using command line, the Windows command prompt can be used to set the environment variables. This is done by executing a command line (C:\Windows\system32\cmd.exe), e.g., for computations using Intel-MPI parallelization:

```
set FLEXLM_TIMEOUT=5000000
set MSC_LICENSE_FILE=27500@localhost
set PATH=DIGIMAT_DIR\DigimatCAE\exec\digi2Ansys;%PATH%
set ANS_USER_PATH=DIGIMAT_DIR\DigimatCAE\exec\digi2Ansys\DMP_INTELMPI
```

where DIGIMAT\_DIR is the Digimat installation directory, e.g.,

C:\MSC.Software\Digimat\2019.1

Definition of FLEXLM\_TIMEOUT environment variable can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000. Definition of MSC\_LICENSE\_FILE is needed if it is not defined as a global environment variable.

If digi2ansys.dll library and third-party libraries

- boost\_chrono-mt.dll
- boost\_filesystem-mt.dll
- boost\_regex-mt.dll
- boost\_system-mt.dll
- boost\_thread-mt.dll
- digimathdf5.dll
- digimathdf5\_cpp.dll
- digimathdf5\_hl.dll
- digimathdf5\_hl\_cpp.dll
- digimatMathTools.dll




Figure I.5.3: Setting the ANS\_USER\_PATH environment variable under Windows 10 operating system - step 1.

- digimatPocoFoundation.dll
- impi.dll
- lapi.dll
- tinyxmlSTL.dll

are moved to another directory, PATH variable has to be updated by adding the location of this new directory.

Distributed computation with MS-MPI can be executed only if the Microsoft MPI is installed. This can be downloaded at the [Microsoft homepage](#).

If a bad version of MS-MPI is used, the computation will stop immediately.

**Multiple installation of Digimat software** In case the user wants to have several versions of Digimat installed in parallel, the PATH (system or user) variable has to be adjusted manually and must point at first to the location of the desired version of Digimat installation for the ANSYS interface, e.g.,

C:\MSC.Software\Digimat\2019.1\DigimatCAE\exec\digi2Ansys.

**Note:** When uninstalling Digimat, this information given in the PATH variable is not deleted.




Figure I.5.4: Setting the ANS\_USER\_PATH environment variable under Windows 10 operating system - steps 2 and 3.




Figure I.5.5: Setting the ANS\_USER\_PATH environment variable under Windows 10 operating system - steps 4 and 5.

### Digimat-CAE/ANSYS Workbench ACT plugin for Windows

Digimat offers an ANSYS Workbench Customization Toolkit (ACT) extension for ANSYS Workbench. This extension simplifies the integration of Digimat materials in an structural analysis, the post-processing of some Digimat history variables, and provides a better integration with Digimat-MAP. It does not require any specific licensing feature.

To install the **DigimatACTplugin** extension, follow this procedure:

1. Open ANSYS Workbench.
2. Browse the "Extensions" menu and select "Install Extension..." (Figure I.5.6).
3. Browse to the "**DigimatACTplugin.wbex**" file, provided in the Digimat directory, in the sub-folder: DigimatCAE\exec\digi2Ansys\workbenchACTplugin.

This will install the extension by copying the corresponding files in ANSYS installation directory:  
%appdata%\Ansys\vXXX\ACT\extensions




Figure I.5.6: Installing the DigimatACTplugin extension for ANSYS Workbench.

For each new ANSYS Workbench session where the Digimat ACT plugin is needed, it must be loaded by browsing the "Extensions" menu, selecting "Manage Extensions...", and ticking the box in front of *DigimatACTplugin* (Figure I.5.7).




Figure I.5.7: Loading the DigimatACTplugin extension for ANSYS Workbench.

*Remark:*

- The Digimat ACT plugin is specific to given ANSYS Workbench and Digimat versions; it needs being reinstalled when upgrading ANSYS or Digimat.
- In complement of definition of `ANS_USER_PATH` environment variable, it is mandatory to define 3 other global environment variables:
  - `DIGIMAT_BIN_20191` environment variable pointing to the Digimat directory containing initial `DIGIMAT_Settings.inifile`, e.g.,  
`C:\MSC.Software\Digimat\2019.1\Digimat\exec`
  - `MSC_LICENSE_FILE` pointing to Digimat license server/file
  - If using geographically distant license server it can be needed to define `FLEXLM_TIMEOUT` environment variable to avoid failing of license checkout if answer of network is too slow. A meaningful value for `FLEXLM_TIMEOUT` is 5000000.

## Digimat-CAE/ANSYS for Linux

---

Under Linux, the Digimat-CAE/ANSYS interface is distributed using the shared library `libansuser.so`. This library is located in Digimat installation directory and depends on targetted parallelization method:

```
DIGIMAT_DIR/DigimatCAE/exec/digi2ansys/INTELMPI
DIGIMAT_DIR/DigimatCAE/exec/digi2ansys/PCMPI
DIGIMAT_DIR/DigimatCAE/exec/digi2ansys/SMP
```

where `DIGIMAT_DIR` is Digimat installation directory, e.g., `/opt/msc/Digimat/2019.1`.

In order to use Digimat-CAE/ANSYS, environment variables `MSC_LICENSE_FILE`, `DIGIMAT_BIN_20191` and `ANS_USER_PATH` must be defined. `MSC_LICENSE_FILE` must point to the adress of Digimat license server. `ANS_USER_PATH` must point to the directory containing the `libansuser.so`. `DIGIMAT_BIN_20191` environment variable must point to a valid `DIGIMAT_Settings.ini` file. library. `FLEXLM_TIMEOUT` environment variable is needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for `FLEXLM_TIMEOUT` is 5000000.

This can be done for example by executing a script containing the following line, e.g., for `INTELMPI` computation:

```
export MSC_LICENSE_FILE=27500@localhost
export DIGIMAT_BIN_20191=/opt/msc/Digimat/2019.1/Digimat/exec
export FLEXLM_TIMEOUT=5000000
export ANS_USER_PATH=/opt/msc/Digimat/2019.1/DigimatCAE/exec/digi2ansys/INTELMPI:
/opt/msc/Digimat/2019.1/Digimat/lib
```

## Configuration of Remote Solve Manager

---

In order to run Digimat/ANSYS coupled analyses through the Remote Solve Manager, it is necessary to modify the following configuration file (assuming a default installation of ANSYS):

```
C:\Program Files\ANSYS Inc\vXXX\RSM\Config\xml\Mechanical_ANSYSJob.xml.
```

This file must be replaced (or edited) following the eponymous file provided in the Digimat sub-folder:

```
DigimatCAE\exec\digi2Ansys\RemoteSolveManager\2019R1.
```

*Remark:* This operation may require administrator rights.

The additional lines will force the Remote Solve Manager to copy the Digimat input files (material file, orientation file, etc...) from the local analysis directory to the remote scratch directory, and to retrieve the Digimat files after computation.

**Remark:** The RSM configuration file must be edited on the local machine, but also on the master node of the remote machine. This is especially important when the remote machine is a multi-node cluster.

### I.5.3 Digimat-CAE/Marc

---

The objective of this section is to explain how to install the interface between Digimat and Marc.

#### Installation procedure

---

Digimat-CAE/Marc is the module containing the Digimat capabilities and the required libraries in order to be used with the Marc implicit solver. For more information on supported versions and platforms, please refer to the appendix [II.3.1](#).

#### Windows platforms

---

The Digimat-CAE/Marc functionalities are embedded inside a new Marc executable `digi2marc.exe` shipped with Digimat installation. The `digi2marc.exe` executable is located in:

```
[DIGIMAT_INSTALL_DIR]\DigimatCAE\exec\digi2marc
```

where `[DIGIMAT_INSTALL_DIR]` is Digimat installation directory, e.g. `C:\MSC.Software\Digimat\2019.1`. User has then to choose Marc version and MPI versions in the directory tree. For example, if Marc 2018.1 is selected using INTEL-MPI,

```
[DIGIMAT_INSTALL_DIR]\DigimatCAE\exec\digi2marc\2018.1\INTELMPI\digi2marc.exe
```

file must be selected.

#### Prerequisites to use Digimat-CAE/Marc interface

Microsoft MPI is requested if user intends to perform parallel computation using MS-Message Passing Interface (MS-MPI). It can be downloaded at the following address: [Microsoft homepage](#).

If `digi2marc.exe` file is moved to another directory, it is required to also move in this directory the following files:

- `digi2marc.dll`
- `vaPlyCalibrator.dll`
- `MeshDataStructure.dll`

and the third-party component libraries:

- `boost_chrono-mt.dll`
- `boost_filesystem-mt.dll`
- `boost_regex-mt.dll`
- `boost_system-mt.dll`
- `boost_thread-mt.dll`
- `digimathdf5.dll`
- `digimathdf5_cpp.dll`
- `digimathdf5_hl.dll`
- `digimathdf5_hl_cpp.dll`
- `digimatMathTools.dll`
- `digimatPocoFoundation.dll`
- `impi.dll`
- `lapi.dll`
- `tinyxmlSTL.dll`



### Launching Digimat-CAE/Marc computations on Windows platforms

For a single processor application, in a DOS command prompt, execute the commands:

```
set FLEXLM_TIMEOUT=5000000
[MARC_INSTALL_DIR]\tools\run_marc.bat -j model.dat
-prog [DIGI2MARC_DIR]\digi2marc
```

where [MARC\_INSTALL\_DIR] is the Marc installation directory and [DIGI2MARC\_DIR] the directory where digi2marc.exe is located. First line is needed when using geographically distant license server to avoid failing of license checkout is answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.

SMP computations can be executed by using the command in a command prompt:

```
set FLEXLM_TIMEOUT=5000000
[MARC_INSTALL_DIR]\tools\run_marc.bat
-j model.dat
-prog {[DIGI2MARC_DIR]\digi2marc}
-nts [N]
```

where [N] is the number of threads. First line is needed when using geographically distant license server to avoid failing of license checkout is answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.

DDM computations using INTELM-MPI can be executed by using the command in a command prompt:

```
set FLEXLM_TIMEOUT=5000000
[MARC_INSTALL_DIR]\tools\run_marc.bat
-j model.dat
-prog {[DIGI2MARC_DIR]\digi2marc}
-nps [N]
```

where [N] is the number of CPUs. First line is needed when using geographically distant license server to avoid failing of license checkout is answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.

DDM run using MS-MPI can be executed by using the command in a command prompt:

```
set FLEXLM_TIMEOUT=5000000
[MARC_INSTALL_DIR]\tools\run_marc.bat
-j model.dat
-prog {[DIGI2MARC_DIR]\digi2marc}
-nps [N] -mpi ms-mpi
```

where [N] is the number of CPUs. First line is needed when using geographically distant license server to avoid failing of license checkout is answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.

### Launching Digimat-CAE/Marc computations using Marc Mentat

To use Marc Mentat to launch computations, it is needed to supersede the original executable marc.exe file:

1. Create a backup of the original file  
[MARC\_INSTALL\_DIR]\bin\win64i8\marc.exe (e.g., marc\_orig.exe);
2. Copy the file digi2marc.exe in the directory [MARC\_INSTALL\_DIR]\bin\win64i8 and rename it marc.exe;
3. Copy in the same directory the files
  - digi2marc.dll
  - vaPlyCalibrator.dll
  - MeshDataStructure.dll

and the third-party component libraries

- boost\_chrono-mt.dll
- boost\_filesystem-mt.dll
- boost\_regex-mt.dll
- boost\_system-mt.dll
- boost\_thread-mt.dll
- digimathdf5.dll
- digimathdf5\_cpp.dll
- digimathdf5\_hl.dll
- digimathdf5\_hl\_cpp.dll
- digimatMathTools.dll
- digimatPocoFoundation.dll
- impi.dll
- lapi.dll
- tinyxmlSTL.dll

## Linux platforms

---

The Digimat-CAE/Marc functionalities are embedded inside a new Marc executable `digi2marc.exec` shipped with Digimat installation. The `digi2marc.exec` executable is located in:

```
[DIGIMAT_INSTALL_DIR]\DigimatCAE\exec\digi2marc\2018.1
```

where `[DIGIMAT_INSTALL_DIR]` is the installation directory of Digimat 2019.1, e.g.,

```
/opt/msc/Digimat/2019.1
```

### Launching Digimat-CAE/Marc computations on Linux platforms

To launch computations under Linux platforms, write a script containing the following lines:

```
export MSC_LICENSE_FILE=[PORT]@[PATH_TO_LICENSE_FILE]
export FLEXLM_TIMEOUT=5000000
[MARC_INSTALL_DIR]/tools/run_marc -j nameProblem.dat -prog
  [DIGIMAT_INSTALL_DIR]/DigimatCAE/exec/digi2marc/2018.1/digi2marc
  -nps [N] -mpi intelmpi
```

where `[PATH_TO_LICENSE_FILE]` is the address of the machine where the license server is installed, `[PORT]` the port used by the Marc license server, `[DIGIMAT_INSTALL_DIR]` the Digimat installation directory and `[N]` the number of CPUs. The `nps` argument is not mandatory for 1 CPU. This argument can be replaced by `nts`, `nfe` or `nsolver` according to the considered parallelization. `-mpi intelmpi` ensures that the used MPI is Intel-MPI and not HP-MPI (not supported). If using geographically distant license server it can be needed to define `FLEXLM_TIMEOUT` environment variable to avoid failing of license checkout if answer of network is too slow. A meaningful value for `FLEXLM_TIMEOUT` is 5000000.

## Installation of the Digimat plugin for Marc Mentat

---

*Remark:*

- **Marc Mentat plug-in is not provided with the current installer. To install the plug-in, please refer to the dedicated installer on MSC Software Download Center.**
- **To be able to run Marc Mentat plug-in, it is mandatory to run Marc Mentat with `-digimat` extra argument.**

The plugin files are stored in

```
[DIGIMAT_INSTALL_DIR]\DigimatCAE\exec\digi2marc\mentat_plugin
```

During the Digimat installation procedure, those files are also copied in a Digimat folder in the Marc Mentat installation directory:

```
[MENTAT_INSTALL_DIR]\digimat
```

If the Marc Mentat installation directory does not contain a Digimat folder, copy it from the Digimat installation (cf. `mentat_plugin` directory here above). This might happen if Marc Mentat was installed after Digimat or if several versions of Marc Mentat are installed in which case the Digimat folder was created only in the installation directory of the latest version.

To be able to use the plugin from within Marc Mentat, perform the following steps.

1. Insert the content of the file

```
[MENTAT_INSTALL_DIR]\digimat\mentatPlugin.xml
```

at the end of the file `[MENTAT_INSTALL_DIR]\menus\menubar.xml` (just before the last line, containing `</menubar>`). Create first a backup of the original file `menubar.xml` (e.g., `menubar_orig.xml`) and possibly disable the "Read only" status in the file properties.

2. Compile the Digimat plugin menu file `digimat.ms` by running the following MS-DOS commands:

```
cd [MENTAT_INSTALL_DIR]\digimat
```

```
[MENTAT_INSTALL_DIR]\bin\mentat -compile main.msb
```

3. Copy the new file `main.msb` in `[MENTAT_INSTALL_DIR]\menus\win64` after having created a backup of the original file `main.msb` (e.g., `main_orig.msb`).

To launch computations set up using the plugin from within Marc Mentat, supersede the original executable `marc.exe` (cf. section about launching Digimat-CAE/Marc computations via Marc Mentat here above).

*Remark:* It is mandatory to define global `DIGIMAT_BIN_20191` environment variable pointing to the Digimat directory containing initial `DIGIMAT_Settings.inifile`, e.g.,

```
C:\MSC.Software\Digimat\2019.1\Digimat\exec
```

If using geographically distant license server it can be needed to define `FLEXLM_TIMEOUT` environment variable to avoid failing of license checkout is answer of network is too slow. A meaningful value for `FLEXLM_TIMEOUT` is 5000000.

---

### I.5.4 Digimat-CAE/MSC Nastran SOL400

---

The objective of this section is to explain how to install the interface between Digimat and MSC Nastran SOL400.

---

#### Installation procedure

---

Digimat and MSC Nastran SOL400 can be coupled together by the use of dynamic libraries. These libraries contain Digimat capabilities, allowing to use Digimat materials in MSC Nastran SOL400 analyses. This link is performed on both Linux and Windows operating systems. Dynamic libraries are distributed by MSC in Nastran installation.

*Remark:* Since Digimat libraries are shipped with the Nastran installer after the Digimat release, please refer to the Nastran SOL400 documentation to know which Digimat version is supported.

*Remark:* FLEXLM\_TIMEOUT environment variable can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.

#### Executing a job under Windows 64-bit using command line

```
MSC_INSTALL_DIR\MSC_Nastran\20XXX\bin\nast20XXX.exe nameOfInputDeck.bdf
```

where MSC\_INSTALL\_DIR is the installation directory of MSC Software.

#### Executing a job under Windows 64-bit using MSC Nastran configuration GUI

Launch MSC Nastran. Then select the input deck to be used and click on Run. Note that, as Digimat commands are not recognized by Patran, it is not possible to launch a coupled Digimat MSC Nastran SOL400 computation from Patran.

#### Executing a parallel job under Windows 64-bit

For Digimat 2019.1, parallel processing using DMP is not stable and currently not recommended. It is recommended to use SMP parallelization.

#### Executing a parallel job under Linux 64-bit

For Digimat 2019.1, parallel processing using DMP is not stable and currently not recommended. It is recommended to use SMP parallelization.

## I.5.5 Digimat-CAE/SAMCEF

---

The objective of this section is to explain how to install the interface between Digimat and SAMCEF/Mecano and SAMCEF/Dynam.

### Installation procedure

---

Digimat-CAE/SAMCEF is the module containing the Digimat capabilities and the required interfaces in order to be linked with the SAMCEF/Mecano implicit solver and SAMCEF/Dynam modal solver. Linking is performed in a static way. For more information on supported versions and platforms, please refer to the appendix [II.3.1](#).

The Digimat material library is embedded inside the SAMCEF/Mecano and SAMCEF/Dynam executables by linking both the libraries together.

### Prerequisites for the link between Digimat and SAMCEF

#### Digimat-CAE/SAMCEF material library

The Digimat-CAE/SAMCEF material library (digi2samcef.obj) is provided with the Digimat installation, typically in:

C:\MSC.Software\Digimat\XXXX.X\DigimatCAE\exec\digi2samcef\v17.2\_i8

*Remark:*

- The Digimat-CAE/SAMCEF material library is only provided for these "i8" versions.
- The Digimat-CAE/SAMCEF material library is only provided for MPICH (linux) and MS-MPI (Windows) parallel computation. Parallel DMP computation with Intel-MPI is not supported.

#### SAMCEF libraries

Official SAMCEF installation CD is shipped with the SAMCEF libraries that are necessary to use Digimat-CAE/SAMCEF. As Digimat interacts with SAMCEF as a user material, the user has to install these user material libraries.

#### Linker

To link Digimat and SAMCEF/Mecano and SAMCEF/Dynam libraries together, a linker is needed. Before linking Digimat-CAE/SAMCEF, therefore the following software must be installed:

- **For Windows 64-bit platform:**
  - Microsoft Visual Studio Express 2012 for Windows Desktop
    - \* See Section [III.1.2](#) on how to install this software
- **For Linux platform:**
  - Need g++ the GNU c++ compiler, shipped with all Linux distributions.

#### Linking between Digimat and SAMCEF under Windows Platform

A link must be performed between SAMCEF and the Digimat material library. This link between Digimat and SAMCEF libraries provides new SAMCEF/Mecano and SAMCEF/Dynam executables called `my_mecano.exe` and `my_dynam.exe`.

To link the SAMCEF/Mecano and SAMCEF/Dynam executables with the Digimat libraries, the following procedure is to be applied.

1. Go to the directory of Samcef version to be used. This directory depends on the Samcef version that user wants to couple with Digimat. For example, if using Samcef 17.2 (i8), the directory `C:\MSC.Software\Digimat\XXXX.X\DigimatCAE\exec\digi2samcef\v17.2_i8` must be selected.
2. Edit the `SAMCEF_DIR` of the file `makefile` to point to the right Samcef installation directory.
3. Double-click on the `nmake_x64.bat` file located next to the `makefile`.
4. Add the following lines in the `samrc.ini` file found in the `Exec` directory of the SAMCEF installation (adapt the Digimat install path, version, and SAMCEF version):

```
module*mm.me: my_mecano
    C:\MSC.Software\Digimat\XXXX.X\DigimatCAE\exec\digi2Samcef\v17.2_i8\my_Mecano.exe
module*md.dy: my_dynam
    C:\MSC.Software\Digimat\XXXX.X\DigimatCAE\exec\digi2Samcef\v17.2_i8\my_Dynam.exe
```

If the location of the executables `my_mecano.exe` and/or `my_dynam.exe` are changed, the `digi2samcef.dll` library and the third-party libraries

- `boost_chrono-mt.dll`
- `boost_filesystem-mt.dll`
- `boost_regex-mt.dll`
- `boost_system-mt.dll`
- `boost_thread-mt.dll`
- `digimathdf5.dll`
- `digimathdf5_cpp.dll`
- `digimathdf5_hl.dll`
- `digimathdf5_hl_cpp.dll`
- `digimatMathTools.dll`
- `digimatPocoFoundation.dll`
- `impi.dll`
- `lapi.dll`
- `tinyxmlSTL.dll`

must also move to this new location

### Linking between Digimat and SAMCEF under Linux Platform

A link must be performed between SAMCEF and the Digimat material library. This link between Digimat and SAMCEF libraries provides two new SAMCEF executables called `my_mecano` and `my_dynam`.

1. Edit the `makefile` located in the `/opt/msc/Digimat/XXXX.X/DigimatCAE/exec/digi2samcef/vXX.X-X_i8` directory to point to the Samcef installation (e.g., `/opt/samcef/v17.2/i8/`).
2. Compile by typing `make my_mecano` and `make my_dynam`.
3. Add the following lines in the `samrc.ini` file found in the `Exec` directory of the SAMCEF installation (adapt the Digimat install path, version, and SAMCEF version):

```
module*mm.me: my_mecano
    /opt/msc/Digimat/XXXX.X/DigimatCAE/exec/digi2samcef/v17.2_i8/my_mecano
module*md.dy: my_dynam
    /opt/msc/Digimat/XXXX.X/DigimatCAE/exec/digi2samcef/v17.2_i8/my_dynam
```

`MSC_LICENSE_FILE` environment variable must be defined in running script to point on MSC license server (including port) `FLEXLM_TIMEOUT` environment variable can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for `FLEXLM_TIMEOUT` is 5000000. This environment variable can be added to the running script like:

```
export FLEXLM_TIMEOUT =5000000
```

### Launching Digimat-CAE/SAMCEF computations

To launch a SAMCEF/Mecano analysis, one must replace the usual `me` by `mm` in the command line, for instance:

```
set FLEXLM_TIMEOUT=5000000
set MSC_LICENSE_FILE=27500@localhost
set PATH=C:\Program Files\Samtech\Samcef\V17.2_x64_i8\Exec;%PATH%
samcef ba,mm,bp [analysisName] n 2 banque=analysis.dat [zone=125000000]
```

where:

- FLEXLM\_TIMEOUT environment variable can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.
- MSC\_LICENSE\_FILE is the address of msc license server (including port)
- analysisName (optional) is the problem name,
- n 2 triggers batch mode,
- analysis.dat is the name of the bank file,
- the zone argument (optional) specifies the size of the memory block allocated for computation.

To launch a SAMCEF/Dynam analysis, one must replace the usual `dy` by `md` in the command line, for instance:

```
set PATH=C:\Program Files\Samtech\Samcef\V17.2_x64_i8\Exec;%PATH%
samcef ba,md,bp [analysisName] n 2 banque=analysis.dat [zone=125000000]
```

It is also required to prepend the SAMCEF execution directory to the PATH Windows environment variable, as shown on the first line of above commands (assuming a default SAMCEF installation directory). This is mandatory since the Digimat-CAE/SAMCEF executable requires some DLLs provided by SAMCEF. Alternatively, one can also directly modify the PATH system environment variable. On Windows, the environment variables can be accessed by right-clicking "computer" and moving to the "Properties" option. The "Advanced settings" will contain a choice to set "Environment variables...". Please refer to Figures I.5.8 to I.5.10 for an example related to Windows 7 operating system.




Figure I.5.8: Edit the PATH environment variable under Windows 7 operating system - step 1.




Figure I.5.9: Edit the PATH environment variable under Windows 7 operating system - steps 2 and 3.




Figure I.5.10: Edit the PATH environment variable under Windows 7 operating system - step 4 and 5.



## I.5.6 Digimat-CAE/LS-DYNA

The objective of this section is to explain how to install the interface between Digimat and LS-DYNA.

### Installation procedure

Digimat-CAE/LS-DYNA is the module containing the Digimat capabilities and the required interfaces in order to be linked with the LS-DYNA FE explicit and implicit solvers. Depending on the platform that is used, linking is performed either in a dynamic or a static way. For more information on supported versions and platforms, please refer to the appendix [II.3.1](#).

### Linux platforms

**Under Linux operating system** Digimat-CAE/LS-DYNA is provided as a dynamic library.

The dynamic Digimat-CAE/LS-DYNA libraries and associated LS-DYNA executables are summarized in tables [I.5.1](#) and [I.5.2](#). Note that library name is independent of targetted MPI.

LS-DYNA version	Precision	MPI	Executable name
R9.3.0	Double	Platform-MPI	ls-dyna_mpp_d_R9_3_0_x64_redhat54_ifort131_sse2_platformmpi_sharelib
		Intel-MPI	ls-dyna_mpp_d_R9_3_0_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib
	Single	Platform-MPI	ls-dyna_mpp_s_R9_3_0_x64_redhat54_ifort131_sse2_platformmpi_sharelib
		Intel-MPI	ls-dyna_mpp_s_R9_3_0_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib
R10.1	Double	Platform-MPI	ls-dyna_mpp_d_r10_1_123355_x64_redhat54_ifort160_sse2_platformmpi_sharelib
		Intel-MPI	ls-dyna_mpp_d_r10_1_123355_x64_redhat54_ifort160_sse2_intelmpi-413_sharelib
	Single	Platform-MPI	ls-dyna_mpp_s_r10_1_123355_x64_redhat54_ifort160_sse2_platformmpi_sharelib
		Intel-MPI	ls-dyna_mpp_s_r10_1_123355_x64_redhat54_ifort160_sse2_intelmpi-413_sharelib
R10.2	Double	Platform-MPI	ls-dyna_mpp_d_R10_2_0_x64_centos65_ifort160_sse2_platformmpi_sharelib
		Intel-MPI	ls-dyna_mpp_d_R10_2_0_x64_centos65_ifort160_sse2_intelmpi-2018_sharelib
	Single	Platform-MPI	ls-dyna_mpp_s_R10_2_0_x64_centos65_ifort160_sse2_platformmpi_sharelib
		Intel-MPI	ls-dyna_mpp_s_R10_2_0_x64_centos65_ifort160_sse2_intelmpi-2018_sharelib

Table I.5.1: LS-DYNA executables files to run with Digimat coupled analysis.

LS-DYNA executables to use with Digimat materials need to be requested from LSTC distributor. Those executables are contained in a `tar.gz` archive. This archive also contains pristine shared library. This pristine shared library must be replaced by shared libraries provided in Digimat installation. Executables depends on LS-DYNA version, targetted precision (single or double precision) and used MPI (Platform-MPI, Intel-MPI). Archive names and sizes are listed in table [I.5.3](#).

### Configure Digimat-CAE/LS-DYNA computations

The following operations have to be performed to be able to use the shared Digimat-CAE/LS-DYNA library on Linux cluster:

- Update `LD_LIBRARY_PATH` to point to LS-DYNA/Digimat coupled libraries and to Digimat third-party libraries:

LS-DYNA version	Precision	Library name
R9.3.0	Double	libmppdyna_d_125554.113060_usermat.so
	Single	libmppdyna_s_125554.113060_usermat.so
R10.1	Double	libmppdyna_d_125554.113060_usermat.so
	Single	libmppdyna_s_125554.113060_usermat.so
R10.2	Double	libmppdyna_d_113025.117897_usermat.so
	Single	libmppdyna_s_113025.117897_usermat.so

Table I.5.2: LS-DYNA library files to run with Digimat coupled analysis.

LS-DYNA version	Precision	MPI	Archive name	Archive size
R9.3.0	Double	Platform-MPI	ls-dyna_mpp_d_R9_3_0_x64_redhat54_ifort131_sse2_platformmpi_sharelib.tar.gz	71261 Ko
		Intel-MPI	ls-dyna_mpp_d_R9_3_0_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib.tar.gz	74963 Ko
	Single	Platform-MPI	ls-dyna_mpp_s_R9_3_0_x64_redhat54_ifort131_sse2_platformmpi_sharelib.tar.gz	54855 Ko
		Intel-MPI	ls-dyna_mpp_s_R9_3_0_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib.tar.gz	58552 Ko
R10.1	Double	Platform-MPI	ls-dyna_mpp_d_r10_1_123355_x64_redhat54_ifort160_sse2_platformmpi_sharelib.tar.gz	81763 Ko
		Intel-MPI	ls-dyna_mpp_d_r10_1_123355_x64_redhat54_ifort160_sse2_intelmpi-413_sharelib.tar.gz	84986 Ko
	Single	Platform-MPI	ls-dyna_mpp_s_r10_1_123355_x64_redhat54_ifort160_sse2_platformmpi_sharelib.tar.gz	60607 Ko
		Intel-MPI	ls-dyna_mpp_s_r10_1_123355_x64_redhat54_ifort160_sse2_intelmpi-413_sharelib.tar.gz	64312 Ko
R10.2	Double	Platform-MPI	ls-dyna_mpp_d_R10_2_0_x64_centos65_ifort160_sse2_platformmpi_sharelib.tar.gz	80798 Ko
		Intel-MPI	ls-dyna_mpp_d_R10_2_0_x64_centos65_ifort160_sse2_intelmpi-2018_sharelib.tar.gz	84271 Ko
	Single	Platform-MPI	ls-dyna_mpp_s_R10_2_0_x64_centos65_ifort160_sse2_platformmpi_sharelib.tar.gz	66400 Ko
		Intel-MPI	ls-dyna_mpp_s_R10_2_0_x64_centos65_ifort160_sse2_intelmpi-2018_sharelib.tar.gz	70280 Ko

Table I.5.3: LS-DYNA archive files to run with Digimat coupled analysis.

```
$ export LD_LIBRARY_PATH=DIGIMAT_DIR/Digimat/lib/:
DIGIMAT_DIR/DigimatCAE/exec/digi2dyna/R10.2/Double/INTELMPI
```

where DIGIMAT\_DIR is Digimat installation directory, e.g., /opt/msc/Digimat /2019.1.

- Ensure that LD\_LIBRARY\_PATH is correctly passed to each computation node. This can be done by adding on MPI command line option
  - For Platform-MPI:
    - e LD\_LIBRARY\_PATH=\$LD\_LIBRARY\_PATH
  - For Intel-MPI:
    - genvall

### Launching Digimat-CAE/LS-DYNA under Linux

To launch a Linux job of Digimat-CAE/LS-DYNA, the very same procedure as to launch a LS-DYNA standalone job can be followed. The only differences are:

- Use the correct version of LS-DYNA, i.e., the one that looks for a user material library (see table I.5.1 for LS-DYNA executable list)
- Make sure that this executable sees the right LD\_LIBRARY\_PATH environment variable as explained above
- If running across multiple nodes, it can be helpful to define a bash script containing all command. An example of such script is given below:

```
#!/bin/bash
export DIGIMAT_BIN_20191 =DIGIMAT_DIR/Digimat/exec
```

```
export MSC_LICENSE_FILE=27500@localhost
export FLEXLM_TIMEOUT=5000000
export LD_LIBRARY_PATH=DIGIMAT_DIR/Digimat/lib:
    DIGIMAT_DIR/DigimatCAE/exec/digi2dyna/R10.2/Double/PCMPI:$LD_LIBRARY_PATH
ls-dyna_mpp_d_R10_2_0_x64_centos65_ifort160_sse2_platformmpi_sharelib$@
exit $?
```

where DIGIMAT\_DIR is the Digimat installation directory, e.g., /opt/digimat/2019.1. FLEXLM\_TIMEOUT definition can be needed when using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000. Make this script executable:

```
chmod a+x launch_script.sh
```

and call this script rather than the LS-DYNA executable, with the very same arguments, i.e.,

```
mpirun -np 4 path_to_my_launch_script.sh i=input.k
```

## Windows platform

---

**Under Windows operating system a static linking procedure must be followed.**

For each version provided, the process to link the Digimat-CAE/LS-DYNA executable is the same:

- Linking procedure is advised to be achieved on a Windows 7 platform. Linking on a Windows 10 platform can fail. If Digimat-CAE/LS-DYNA interface is intended to be used on a Windows 10 platform, user is strongly invited to copy the directory Digimat to LS-DYNA to a Windows 7 machine. Digimat to LS-DYNA directory is located in:

```
C:\MSC.Software\Digimat\2019.1\DigimatCAE\exec\digi2dyna
```

- On the machine where linking procedure is achieved, following operations are needed:
  - Make sure Microsoft Windows SDK v7.1 is installed on the linking machine (See Section III.1.1 on how to install this software). Installation of Microsoft Windows SDK v7.1 must be achieved only once. When upgrading Digimat version, it is not needed to reinstall Microsoft Windows SDK v7.1, but only to update Digimat to LS-DYNA libraries.
  - Get LS-DYNA library libdyna.lib and libansys.lib from your LS-DYNA distributor and copy them in the Digimat directory corresponding to the LS-DYNA version that is intended to be used, e.g.,  
C:\MSC.Software\Digimat\2019.1\DigimatCAE\exec\digi2dyna\R10.2\Double\MSMPI
  - Double-click on the nmake\_x64.bat.
  - An executable should be created named mppdyna.exe or mppdyna\_d.exe depending on the version (single or double precision).
  - Result of link procedure is redirected to out.txt file next to the nmake\_x64.bat file.
  - If the executable is not created, check the following:
    - \* The path to the installation of Microsoft Windows SDK v7.1 in the .bat script if Microsoft Windows SDK v7.1 has not been installed in the default directory.
    - \* Error messages are written in out.txt file. In case of issue, contact [digimat.support@mscsoftware.com](mailto:digimat.support@mscsoftware.com) by including this out.txt file.
  - Once linking procedure is achieved on the Windows 7 machine, Digimat to LS-DYNA directory can be moved to initial Windows 10 installation directory.
- The l1stc\_client.exe executable next to the Digimat-CAE/LS-DYNA one is needed. It can be found in LS-DYNA installation.

**Please notice that LS-DYNA libraries (libdyna.lib and libansys.lib) are NOT provided together with the Digimat software.**

LS-DYNA distributor can be contacted to get access to the library files required for the linking procedure. Requested archive containing the LS-DYNA libraries to use with Digimat material are listed in table I.5.4. Those libraries depends on LS-DYNA version, targetted precision (single or double precision) and used MPI (Platform-MPI, Intel-MPI or MS-MPI).

LS-DYNA version	Precision	MPI	Archive name	Archive size
R9.3.0	Double	Platform-MPI	ls-dyna_mpp_d_R9_3_0_winx64_ifort131_pmpi_lib.zip	100670 Ko
		Intel-MPI	ls-dyna_mpp_d_R9_3_0_winx64_ifort131_impi_lib.zip	100734 Ko
		MS-MPI	ls-dyna_mpp_d_R9_3_0_winx64_ifort131_msmpi_lib.zip	100705 Ko
	Single	Platform-MPI	ls-dyna_mpp_s_R9_3_0_winx64_ifort131_pmpi_lib.zip	85000 Ko
		Intel-MPI	ls-dyna_mpp_s_R9_3_0_winx64_ifort131_impi_lib.zip	85073 Ko
		MS-MPI	ls-dyna_mpp_s_R9_3_0_winx64_ifort131_msmpi_lib.zip	85130 Ko
R10.1	Double	Platform-MPI	ls-dyna_mpp_d_R101_winx64_ifort131_pmpi_lib.zip	120393 Ko
		Intel-MPI	ls-dyna_mpp_d_R101_winx64_ifort131_impi_lib.zip	120375 Ko
		MS-MPI	ls-dyna_mpp_d_R101_winx64_ifort131_msmpi_lib.zip	120436 Ko
	Single	Platform-MPI	ls-dyna_mpp_s_R101_winx64_ifort131_pmpi_lib.zip	95860 Ko
		Intel-MPI	ls-dyna_mpp_s_R101_winx64_ifort131_impi_lib.zip	95846 Ko
		MS-MPI	ls-dyna_mpp_s_R101_winx64_ifort131_msmpi_lib.zip	96149 Ko
R10.2	Double	Platform-MPI	ls-dyna_mpp_d_R10_2_winx64_ifort160_pmpi_lib.zip	113129 Ko
		Intel-MPI	ls-dyna_mpp_d_R10_2_winx64_ifort160_impi_lib.zip	113138 Ko
		MS-MPI	ls-dyna_mpp_d_R10_2_winx64_ifort160_msmpi_lib.zip	113139 Ko
	Single	Platform-MPI	ls-dyna_mpp_s_R10_2_winx64_ifort160_pmpi_lib.zip	93023 Ko
		Intel-MPI	ls-dyna_mpp_s_R10_2_winx64_ifort160_impi_lib.zip	93035 Ko
		MS-MPI	ls-dyna_mpp_s_R10_2_winx64_ifort160_msmpi_lib.zip	93081 Ko

Table I.5.4: LS-DYNA archive files to run with Digimat coupled analysis.

For detailed information on supported versions and platforms, please refer to the appendix II.3.1.

### Prerequisites for the link between Digimat and LS-DYNA

To link Digimat and LS-DYNA libraries together on Windows platforms, a linker is needed. Before linking Digimat-CAE/LS-DYNA, therefore the following software must be installed:

- **For all Windows platforms:**
  - Microsoft Windows SDK v7.1
    - \* See Section III.1.1 on how to install this software
- **For parallel computations on Windows 64 bits platforms**
  - Microsoft MPI (needed for MS-MPI versions)
    - \* An installer can be downloaded at [Microsoft home page](#)
  - Platform MPI (needed for PC-MPI versions)
    - \* An installer can be downloaded at [IBM home page](#). This software is not free.
  - Intel-MPI
    - \* An installer can be downloaded at [Intel home page](#)

### Launching Digimat-CAE/LS-DYNA under Windows

To launch a Windows job of Digimat-CAE/LS-DYNA using command line, the following bat script can be used, for example for LS-DYNA R10.2 in double precision using Platform-MPI on 4 processors:

```
set FLEXLM_TIMEOUT=5000000
set PATH="C:\Program Files (x86)\Platform Computing\Platform-MPI\bin";%PATH%
```

```
set MSC_LICENSE_FILE=27500@localhost
C:\Program Files (x86)\Platform Computing\Platform-MPI\bin\mpirun -np 4
DIGIMAT_DIR\DigimatCAE\digi2dyna\R10.2\Double\PCMPI\mppdyna_d.exe i=input.k
```

where:

- First line can be needed when using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000.
- Second line add PATH to MPI dynamic libraries.
- Third line defines MSC\_LICENSE\_FILE environment variable pointing to MSC license file (including port).
- Last line runs Digimat-CAE/LS-DYNA job.
- DIGIMAT\_DIR is Digimat installation directory, e.g., C:\MSC.Software\Digimat\2019.1.

### Licensing for Digimat-CAE/LS-DYNA computations

---

FLEXLM\_TIMEOUT environment variable can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000. This environment variable can be added to the running script like:

```
set FLEXLM_TIMEOUT =5000000
```

In order to run on 'n' cores an application using Digimat-CAE/LS-DYNA interface, one license for the Digimat-CAE/LS-DYNA interface is needed, as well as 'n-1' Digimat parallel tokens.

If the job also involves, for example, the Digimat-CAE/Moldflow interface, only one license of that additional interface will be required.

### Generation of encryption key file for Macro solution

---

When using Digimat-RP with Macro solution, material properties are encrypted. Generation of key is done by doing following blank run of LS-DYNA in Digimat working directory:

```
C:\Program Files (x86)\Platform Computing\Platform-MPI\bin\mpirun -np 1
DIGIMAT_DIR\DigimatCAE\digi2dyna\R10.2\Double\PCMPI\mppdyna_d.exe pgpkey
```

Then check that the file `lstc_pgpkey.asc` is created. Note that the key file is independant of LS-DYNA version, so, it can be generated with any LS-DYNA executable.

### I.5.7 Digimat-CAE/PAM-CRASH

---

The objective of this section is to explain how to install the interface between Digimat and PAM-CRASH. Digimat-CAE/PAM-CRASH is the material library containing the Digimat linear and nonlinear multi-scale material modeling capabilities:

`libdigimat_N.dll` (under the Windows operating system)

`libdigimat_N.so` (under Linux operating system)

with  $N \in [0, 3]$ .

#### Installation procedure

---

Digimat-CAE/PAM-CRASH is the module containing the Digimat capabilities and the required interfaces in order to be linked with the PAM-CRASH explicit solver. Linking in general is performed either in a dynamic or a static way. For more information on supported versions and platforms, please refer to the appendix [II.3.1](#).

#### Dynamic libraries

---

For Digimat 2019.1, a set of dynamic libraries is provided for the Digimat-CAE/PAM-CRASH interface, both for single and double precision for all supported PAM-CRASH versions. The installation procedure for the dynamic library is straightforward. While installing Digimat to PAM-CRASH, it installs the necessary libraries, including

`libdigimat_N`

that will be loaded by the explicit solver (`psolid.exe`) at runtime. The library `libdigimat_N.dll` and its dependencies contains definition of all possible user defined subroutines. This will allow the user to use all linear and nonlinear small-strain material models capabilities available in Digimat for small-strain analyses. Defining Digimat material model in PAM-CRASH then is just like defining any other PAM-CRASH material model.

To run coupled Digimat to PAM-CRASH computations in command line, it is advised to write a `.bat` file containing all the information needed by PAM-CRASH to allow the call to user subroutine. An example of such launch script is given below to run PAM-CRASH 2017.0 with double precision and 4 CPUs.

```
1. echo off
2. set MSC_LICENSE_FILE=27500@localhost
3. set PATH=DIGIMAT_INST_DIR\DigimatCAE\exec\digi2Pamcrash;
   DIGIMAT_INST_DIR\DigimatCAE\exec\digi2Pamcrash\2017.0\Windows\x86_64\DMP\DP;%PATH%
4. set FLEXLM_TIMEOUT=5000000
5. set OMP_NUM_THREADS=1
6. set PAM_USER_PLUGIN_ROOT=DIGIMAT_INST_DIR\DigimatCAE\exec\digi2Pamcrash\2017.0
7. "C:\Program Files (x86)\ESI Group\Virtual-Performance\2017.0\Solver-64Bit\
   pamcrash.bat" -np 4 -fp 2 test.pc > "test.out"
```

where `DIGIMAT_INST_DIR` is Digimat installation directory, e.g.,

`C:\MSC.Software\Digimat\2019.1`

The first command suppress screen display of command. The second line defines the path to Digimat license path through MSC\_LICENSE\_FILE environment variable. Definition of MSC\_LICENSE\_FILE is needed if it is not defined as a global environment variable. The third command add to PATH environment variable the path to Digimat library digi2pamDouble\_N.dll and Digimat third-party libraries. The fourth command defines FLEXLM\_TIMEOUT environment variable. This can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000. The fifth command specify the number of threads to be used, only 1 thread is supported by Digimat. The sixth command gives to PAM-CRASH the path to the libdigimat\_N.dll file. The last command is the command to run PAM-CRASH analysis, the -fp 2 option sets the precision to double precision. The command sends the output to the .out file. If error is encountered in Digimat, it will be written in this file.

The header of this file must be read carefully before using this launching script.

Running PAM-CRASH 2018.01 and later version is slightly different. An example of such launch script is given below to run PAM-CRASH 2018.0 with double precision and 4 CPUs.

```
1. echo off
2. set MSC_LICENSE_FILE=27500localhost
3. set PATH=DIGIMAT_INST_DIR\DigimatCAE\exec\digi2Pamcrash;
   DIGIMAT_INST_DIR\DigimatCAE\exec\digi2Pamcrash\2018\windows-x86-64;%PATH%
4. set FLEXLM_TIMEOUT=5000000
5. set OMP_NUM_THREADS=1
6. set PAM_USER_PLUGIN_ROOT=DIGIMAT_INST_DIR\DigimatCAE\exec\digi2Pamcrash\2018
7. "C:\Program Files (x86)\ESI Group\Virtual-Performance\2018\Solver-64Bit\bin\
   bin\pamcrash.bat" -np 4 -fp 2 test.pc > "test.out"
```

where DIGIMAT\_INST\_DIR is Digimat installation directory, e.g.,

C:\MSC.Software\Digimat\2019.1

### Launching Digimat-CAE/PAM-CRASH computations on Linux platform

The Digimat-CAE/PAM-CRASH dynamic library libdigimat\_N.so under Linux, with  $N \in [0,3]$ , can be used to run parallel jobs.

To define environment variables needed to run Digimat to PAM-CRASH coupled analysis, user can write a launch script as the one described below:

```
1. #!/bin/bash
2. export PAM_USER_PLUGIN_ROOT=DIGIMAT_INST_DIR/DigimatCAE/exec/digi2pamcrash/2018
3. export LD_LIBRARY_PATH=DIGIMAT_INST_DIR/DigimatCAE/exec/digi2pamcrash/:
   DIGIMAT_INST_DIR/Digimat/lib:$LD_LIBRARY_PATH
4. export PAM_LMD_LICENSE_FILE=27007@host
5. export MSC_LICENSE_FILE=27500@host
6. export FLEXLM_TIMEOUT=5000000
7. export OMP_NUM_THREADS=1
8. export PAMROOT=/opt/pamcrash/2018
9. export PAMHOME=$PAMROOT
10. $PAMROOT/pamcrash_safe/2018/pamcrash -np 4 -fp 2 -lic CRASHSAF test.pc > test.out
```

where DIGIMAT\_INST\_DIR is Digimat installation directory, e.g.,

/opt/msc/Digimat/2019.1 The first command is the header to execute bash scripts. The second command defines the location of the libdigimat\_N.so shared library. The third command add the path to Digimat third-party libraries to LD\_LIBRARY\_PATH environment variable. The next two commands defines the path to Digimat and PAM-CRASH licences (the XXX must be replaced by the address of the license file or license server). The sixth command defines FLEXLM\_TIMEOUT environment variable. This can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for FLEXLM\_TIMEOUT is 5000000. The seventh command specify the number of threads

to be used, only 1 thread is supported by Digimat. The PAMROOT gives the path to PAM-CRASH directory. The last command launch PAM-CRASH computation.



---

## I.5.8 Digimat-CAE/MSC Nastran SOL1XX

---

The objective of this section is to explain how to install the interface between Digimat and MSC Nastran SOL1XX.

---

### Installation procedure

---

Digimat and MSC Nastran SOL1XX can be coupled together without the need for installing anything in particular on top of the classical MSC Nastran and Digimat installations. See appendix [II.3.1](#) for more information on the versions of MSC Nastran which are supported by Digimat 2019.1.

#### Executing a job

Once coupled with one or more Digimat materials, the modified Nastran input deck can be run with Nastran under Windows 64-bit or Linux 64-bit environments like any other input deck, without taking any specific action. Please refer to the MSC Nastran documentation for more information.

For example, to execute a sequential job under Windows 64-bit using the command line, the user needs to type:

```
MSC_INSTALL_DIR/MSC_Nastran/20170/bin/nast2017.exe modifiedInputDeck.bdf
```

where MSC\_INSTALL\_DIR is the installation directory of MSC Software and modifiedInputDeck.bdf is the name of the Nastran input deck created by Digimat-RP after coupling the structural model with one or more Digimat materials.

### I.5.9 Digimat-CAE/OptiStruct

---

The objective of this section is to explain how to install the interface between Digimat and OptiStruct which uses Digimat-RP.

#### Installation procedure

---

When not using the plug-in, Digimat and OptiStruct can be coupled together without the need for installing anything in particular on top of the classical OptiStruct and Digimat installations. See appendix [II.3.1](#) for more information on the versions of OptiStruct which are supported by Digimat 2019.1.

#### Executing a job

Once coupled with one or more Digimat materials, the OptiStruct model can be run with OptiStruct under Windows 64-bit or Linux 64-bit environments like any other OptiStruct model, without taking any specific action. Please refer to the OptiStruct documentation for more information.

For example, to execute a sequential job under Windows 64-bit using the command line, the user needs to type:

```
ALTAIR_INSTALL_DIR/14.0/hwsolvers/scripts/optistruct.bat model_DigimatCoupled.fem
```

where ALTAIR\_INSTALL\_DIR is the Altair installation directory and model\_DigimatCoupled.fem is the name of the OptiStruct model created by Digimat-RP after coupling the structural model with one or more Digimat materials.

---

## I.5.10 Digimat-CAE/PERMAS

---

The objective of this section is to explain how to install the interface between Digimat and PERMAS.

### Installation procedure

---

Digimat and PERMAS can be coupled together without the need for installing anything in particular on top of the classical PERMAS and Digimat installations. See appendix [II.3.1](#) for more information on the versions of PERMAS which are supported by Digimat 2019.1.

#### Executing a job

Once coupled with one or more Digimat materials, the PERMAS model can be run with PERMAS under Windows 64-bit or Linux 64-bit environments like any other PERMAS model, without taking any specific action. Please refer to the PERMAS documentation for more information.

For example, to execute a sequential job under Windows 64-bit using the command line, the user needs to type:

```
INTES_INSTALL_DIR/V16/bin/permas.bat model_DigimatCoupled.uci
```

where INTES\_INSTALL\_DIR is the INTES installation directory and model\_DigimatCoupled.uci is the name of the PERMAS model created by Digimat-RP after coupling the structural model with one or more Digimat materials.

### I.5.11 Digimat-CAE/nCode DesignLife

---

Within the Digimat installation, the dynamic library `digi2ncode.dll` is located in the directory

`[INSTALL_DIR]/XXXX.X/DigimatCAE/exec/digi2ncode`

where `[INSTALL_DIR]` is the Digimat installation directory.

To be able to use Digimat to nCode interface, `DIGIMAT2NCODE_SHARED_LIBS` environment variable needs to be defined. This variable enables nCode to locate Digimat/nCode library, to load it and to run coupled Digimat-CAE/nCode DesignLife analyses.

Path to third-party libraries

- `boost_chrono-mt.dll`
- `boost_filesystem-mt.dll`
- `boost_regex-mt.dll`
- `boost_system-mt.dll`
- `boost_thread-mt.dll`
- `digimathdf5.dll`
- `digimathdf5_cpp.dll`
- `digimathdf5_hl.dll`
- `digimathdf5_hl_cpp.dll`
- `digimatMathTools.dll`
- `digimatPocoFoundation.dll`
- `impi.dll`
- `lapi.dll`
- `tinyxmlSTL.dll`

must also be added to the `PATH` environment variable. If these libraries are moved to another directory, `PATH` variable has to be updated according to this new directory.

*Remark:* `FLEXLM_TIMEOUT` environment variable can be needed if using geographically distant license server to avoid failing of license checkout if answer of network is too slow. A meaningful value for `FLEXLM_TIMEOUT` is 5000000.

---

## I.5.12 Digimat-CAE/ANSYS Fluent

---

The objective of this section is to explain how to install the interface between Digimat and ANSYS Fluent.

### Installation procedure

---

Digimat-CAE/ANSYS Fluent is provided as a set of dynamic libraries. These libraries contain Digimat capabilities allowing to use Digimat materials in ANSYS Fluent analyses.

For more information concerning supported ANSYS Fluent releases and platforms, please refer to the appendix [II.3.1](#). In the following, XX.X denotes the number of a supported version of ANSYS Fluent, e.g. 17.0.

### Digimat-CAE/ANSYS Fluent for Windows

---

The Digimat-CAE/ANSYS Fluent interface for the Windows operating system is distributed in two parts. The first part contains third-party components as listed in the following:

- boost\_chrono-mt.dll
- boost\_filesystem-mt.dll
- boost\_regex-mt.dll
- boost\_system-mt.dll
- boost\_thread-mt.dll
- digimathdf5.dll
- digimathdf5\_cpp.dll
- digimathdf5\_hl.dll
- digimathdf5\_hl\_cpp.dll
- digimatMathTools.dll
- digimatPocoFoundation.dll
- impi.dll
- lapi.dll
- tinysqlSTL.dll

These files are found in the

DigimatCAE\exec\digi2Fluent

folder of the Digimat installation. The second part are dynamic libraries which are crucial for the installation process of the Digimat-CAE/ANSYS Fluent interface. These dynamic libraries depend on the ANSYS Fluent release and on the parallelization that will be used (Serial, MSMPI or PCMPI). They can be found in three different folders, related to a parallelization method, for each ANSYS Fluent release:

DigimatCAE\exec\digi2Fluent\XX.X\Serial  
DigimatCAE\exec\digi2Fluent\XX.X\MSMPI  
DigimatCAE\exec\digi2Fluent\XX.X\PCMPI

In order to enable the Digimat-CAE/ANSYS Fluent interface for a specific calculation, three manual operations are needed:

1. The third-party components listed hereinbefore must be copied in ANSYS Fluent working directory (see afterwards, for a definition of ANSYS Fluent working directory).
2. The folder matching the ANSYS Fluent release number and parallelization method must be copied in ANSYS Fluent working directory. For the sake of simplicity, this folder can then be renamed, e.g. "digi2Fluent".
3. The Digimat-CAE/ANSYS Fluent interface dynamic library must be loaded into ANSYS Fluent. Access the UDF Library Manager (see figure I.5.11) and **Load** the library using the copied folder name, e.g. "digi2Fluent" if renamed as in the previous operation (see figure I.5.12).




Figure I.5.11: Library manager opening (ANSYS Fluent 17.0)




Figure I.5.12: Digimat-CAE/ANSYS Fluent interface dynamic library loading

The ANSYS Fluent working directory depends on Fluent launch method. If ANSYS Fluent is launched from **ANSYS Workbench**, this directory is in the ANSYS Workbench project directory tree. For example, for the FluentHeat ANSYS Workbench project, the ANSYS Fluent working directory is:

\dir\FluentHeat\_files\dp0\FFF\Fluent

If **ANSYS Fluent** is launched as a standalone software, it is defined from ANSYS Fluent launcher window (see figure I.5.13).




Figure I.5.13: ANSYS Fluent 17.0 Launcher

It is worth noting that MSMPI and PCMPI Digimat-CAE/ANSYS Fluent interface folders can be used to run Serial calculations.





## **Part II**

# **Software**



# Software **II.1**

## New capabilities & changes in the software

---

II.1.1	Digmat 2019.1	178
	Digmat-MF	178
	Digmat-FE	178
	Digmat-MX	179
	Digmat-MAP	180
	Digmat-CAE	180
	Digmat-RP	181
	Digmat-VA	181
	Digmat-AM	182
II.1.2	Digmat 2019.0	182
	Digmat-MF	183
	Digmat-FE	183
	Digmat-MX	183
	Digmat-MAP	185
	Digmat-CAE	186
	Digmat-RP	186
	Digmat-VA	187
	Digmat-AM	187
II.1.3	Digmat 2018.1	187
	Digmat-MF	188
	Digmat-FE	188
	Digmat-MX	188
	Digmat-MAP	189
	Digmat-CAE	189
	Digmat-RP	189
	Digmat-VA	190
	Digmat-AM	190
II.1.4	Digmat 2018.0	191
	Digmat-MF	191
	Digmat-FE	191
	Digmat-MX	192
	Digmat-MAP	192
	Digmat-CAE	193
	Digmat-RP	194
	Digmat-VA	195
	Digmat-AM	195

II.1.5	Digmat 2017.1	196
	Digmat-MF	196
	Digmat-FE	196
	Digmat-MX	197
	Digmat-MAP	198
	Digmat-CAE	198
	Digmat-VA	199
	Digmat-AM	199
II.1.6	Digmat 2017.0	200
	Digmat-MF	200
	Digmat-FE	200
	Digmat-MX	201
	Digmat-MAP	202
	Digmat-CAE	202
	Digmat-RP	203
	Digmat-VA	204
	Additional information	204
II.1.7	Digmat 2016.1	204
	Digmat-MF	204
	Digmat-FE	205
	Digmat-MX	206
	Digmat-MAP	207
	Digmat-CAE	207
	Digmat-RP	208
	Digmat-VA	208
	Additional information	209
II.1.8	Digmat 2016.0	209
	Digmat-MF	209
	Digmat-FE	210
	Digmat-MX	210
	Digmat-MAP	211
	Digmat-CAE	211
	Digmat-RP	212
	Digmat-VA	212
	Additional information	212
II.1.9	Digmat 6.1.1	213
	Digmat-MF	213
	Digmat-CAE	213
	Digmat-RP	213
II.1.10	Digmat 6.0.1	213
	Digmat-MF	214
	Digmat-FE	214
	Digmat-MX	214
	Digmat-MAP	215
	Digmat-CAE	215
	Digmat-RP	216
	Digmat-VA	216
II.1.11	Digmat 5.1.2	217
	Digmat-MF	217
	Digmat-FE	218
	Digmat-MX	218
	Digmat-MAP	218

Digmat-CAE . . . . .	218
Digmat-RP . . . . .	219
II.1.12 Digmat 5.1.2 Student Edition . . . . .	<b>219</b>
Digmat-MF . . . . .	220
Digmat-FE . . . . .	220
II.1.13 Digmat 5.1.1 . . . . .	<b>221</b>
Digmat-MF . . . . .	221
Digmat-FE . . . . .	222
Digmat-MX . . . . .	223
Digmat-MAP . . . . .	224
Digmat-CAE . . . . .	225
Digmat-RP . . . . .	226
Bug fixes and minor improvements . . . . .	226
II.1.14 Digmat 5.0.1 . . . . .	<b>227</b>
Digmat Platfrom & GUIs . . . . .	227
Digmat-MF . . . . .	227
Digmat-MX . . . . .	228
Digmat-CAE . . . . .	228
Digmat-RP . . . . .	229
Examples Manual . . . . .	229
II.1.15 Digmat 4.5.1 . . . . .	<b>230</b>
Digmat-MF . . . . .	230
Digmat-MX . . . . .	230
Digmat-CAE . . . . .	230
II.1.16 Digmat 4.4.1 . . . . .	<b>231</b>
Digmat-MF . . . . .	231
Digmat-FE . . . . .	232
Digmat-MX . . . . .	232
Digmat-CAE . . . . .	232
Digmat-MAP . . . . .	233
Digmat Documentation . . . . .	234
II.1.17 Digmat 4.3.1 . . . . .	<b>235</b>
Digmat-MF . . . . .	235
Digmat-FE . . . . .	235
Digmat-MX . . . . .	236
Digmat-CAE . . . . .	236
Digmat-MAP . . . . .	236
Digmat Installation . . . . .	237
Digmat Documentation . . . . .	237
II.1.18 Digmat 4.2.1 . . . . .	<b>238</b>
Digmat-MF . . . . .	238
Digmat-FE . . . . .	238
Digmat-MX . . . . .	238
Digmat-CAE . . . . .	239
Digmat-MAP . . . . .	239
Digmat GUI . . . . .	240
Digmat Documentation . . . . .	240
II.1.19 Digmat 4.1.2 . . . . .	<b>241</b>
Digmat-MF . . . . .	241
Digmat-FE . . . . .	241
Digmat-MX . . . . .	241
Digmat-CAE . . . . .	242

### II.1.1 Digimat 2019.1

---

In this section of the documentation, you can find all major changes that are in Digimat 2019.1.

#### Digimat-MF

---

- Revised default failure models for SFRP and CFRP
  - Tsai-Hill 3D Transversely isotropic, strain based, for microstructures with matrix + inclusion (SFRP)
  - Multicomponent 2D for microstructures with continuous fibers (UD and woven 2D)
- New Tsai-Wu 3D orthotropic failure model improving failure modeling for FFF/FDM materials

#### Digimat-FE

---

- New additional solver within Digimat-FE/Solver, based on FFT technology
  - Reduced run time vs Finite Element Analysis based solver
  - Reduced memory consumption vs Finite Element Analysis based solver
  - Supported for mechanical analysis of RVE involving
    - \* Elasticity, elastoplasticity
    - \* Viscoelasticity, Elastoviscoplasticity
    - \* Hyperelasticity, crystal plasticity
- Improved SFRP geometry generation algorithm, enabling higher volume fraction and more accurate fiber orientation distribution
- More robust and efficient modeling workflow for UD stiffness and strength prediction
  - Improved microstructure generation for better randomness and high volume fraction
  - Extruded periodic meshing for robust and efficient run
  - New waviness definition for compression case simulation
  - New initial thermal loadcase to account for manufacturing stresses
  - Phase strength distribution
  - New Turon cohesive law to model fiber/matrix interface with more physics and better convergence (available with FE/Solver only)
- Improved RVE generation algorithm for strands enabling higher out-of-plane orientation distribution
- New crystal plasticity constitutive model available for polycrystal microstructures
  - Dedicated Metal microstructure definition through Polycrystal
  - Texture import & post-processing from Digimat-FE results
  - Supported for
    - \* Single phase polycrystal microstructure
    - \* FCC, BCC, HCP crystal symmetries
  - Available with FE/Solver (FEA and FFT approach)
  - Requires dedicated add-on licenses to Digimat-FE

## Digimat-MX

---

- Extended reverse engineering method, now supporting
  - Viscoelasticity models
  - Thermo-viscoelasticity models
- New Coefficient of Thermal Expansion reverse engineering
- New Poisson's ratio reverse engineering
- Through thickness plot of fiber orientation tensor
- New material suppliers
  - MarkForged
  - Sintratec
- New material data in public database
  - DSM
    - \* Updated models for:
      - Akulon Ultraflow K-FHG12
    - \* Additional models (fatigue, thermoplasticity) for several grades:
      - Akulon K224-HG7
      - Akulon S223-HG0
      - ForTii Ace MX53T
    - \* Additional Elastic models for all grades
  - DuPont Transportation and Industrial
    - \* Addition of new grades:
      - Zytel 73G50HSLA BK416
      - Zytel 73G40T BK416
      - Zytel 73G60HSLA BK416
  - Solvay Specialty Polymers
    - \* Updated models for:
      - Ixef 1022 at 23°C
      - Ketaspire KT-880 GF30 at 23°C
      - Ryton R-4-200
    - \* Addition of new grades:
      - Amodel A-4145HH BK311
      - Ketaspire KT-820 GF30
      - Ryton R-4-220
    - \* Addition of new grades for Additive Manufacturing (FFF):
      - NovaSpire PEKK AM Powder
  - Sumika Polymer Compounds
    - \* Addition of new models(fatigue, creep, ...) for existing grades:
      - Thermofil HP F610X99
      - Thermofil HP F611X99
      - Thermofil HP F711X99
      - Thermofil HP F811X99
      - Thermofil HP F911X99
  - Asahi-Kasei Corporation
    - \* Addition of new models(fatigue, creep, ...) for existing grades:
      - Leona 14G30
      - Leona 14G35
      - Leona 14G50
    - \* Addition of new a grade:
      - Leona SG104
  - Sintratec (new AM printer supplier)
    - \* Addition a grade:

- Sintratec PA12 Powder
- Solvay Engineering Plastics
  - \* Addition of new grades:
    - TECHNYL Red J V35 Black 21N
    - TECHNYL Red S V50 Black 21N
- RadiciGroup
  - \* Addition of new grades:
    - Radiflam A RV250HF 333 BK
    - Raditeck P ERV400K 1700 NT
    - Raditer B RV300 333 BK
    - Radilon DT RV300RKC2 306 BK
    - Radilon Aestus T1 RV300RKC 306 BK
    - Radilon Aestus T1 RV400RKC 306 BK

## Digmat-MAP

---

- New weld line angle filtering method
- New manufacturing data formats supported: Hexagon VISI Flow
- Extended data support for existing interfaces
  - Moldflow 3D / Microcellular analysis: support of varying bubble density
  - 3D TIMON Light 3D
- Extended mapping : 1D mapping for porosity now available

## Digmat-CAE

---

- Updated support of the existing interfaces for user subroutines for Windows & Linux (Red Hat 7 & Suse 11)
  - Abaqus 2017 / 2018 / 2019
  - ANSYS 19.2 / 19R1
  - LS-DYNA 9.3 / 10.1 / 10.2
  - PAM-CRASH 2016 / 2017 / 2018
  - Marc 2018 / 2018.1
  - Samcef V16.3 / V17.2
  - nCode 2018.1
- Improved robustness of Hybrid solution for strain-rate dependent j2-plasticity
- Simplified installation of Digmat with other user subroutines for Marc
- Full harmonic analysis now supported with ANSYS
- Support of RH6 OS for Abaqus, LS-DYNA and PAM-CRASH



---

**Digimat-RP**

---

- Improved superposition visualization for more confident mapping
- Simplified solution settings management
  - Settings are split between
    - \* Solution settings (application oriented, not requiring Hybrid parameters re-generation)
    - \* Advanced solver settings (solver oriented, requiring Hybrid parameters re-generation)
  - Previous templates are deprecated
- Updated solver for Digimat-RP/Moldex3D solver: upgrade from Moldex3D R16 to R16.1
- Extended SFRP fatigue post-processing capabilities
  - New plasticity correction method
  - FEA support extended to MSC Marc on top of Abaqus and ANSYS
- New SMC solution
  - New material type for compression molding
  - Support of SMC type of material model
    - \* Elasticity
    - \* Viscoelasticity
    - \* Failure and damage
  - Support of fiber orientation and weld line manufacturing data

---

**Digimat-VA**

---

- New Advanced PFA model
  - Providing more physics and accuracy through
    - \* LaRC failure criteria
    - \* Elastoplasticity behavior for shear
    - \* In-situ strength
    - \* Intralaminar fracture toughness
    - \* Effect of manufacturing stresses
    - \* Dedicated meshing approach
  - Available for
    - \* UD materials
    - \* Unnotched and open hole tests
- New delamination modeling
  - Available for UD and woven materials
  - Available with Standard and Advanced PFA
- New effect of defects workflow
  - Enabling study of the effect of
    - \* Interply porosity
    - \* Intraply porosity
    - \* Out-of-plane waviness
  - Available with Standard PFA
- Enhanced allowables computation
  - Outliers check
  - Normalization on stiffness/strength
  - Revised allowable formula
- Command line available for batch mode
- Improved boundary condition for unnotched test
  - New option to define free length
  - Reduced mesh sensitivity

---

## Digmat-AM

---

- Improved usability for results post-processing
  - Cut view
  - Custom reference plane definition for warpage evaluation
  - Pick node/element values
  - Manage user-defined views
  - Larger visualization window
  - Color scale exported with animation (GIF export)
- Enhanced computational performance
  - Thermal analysis
    - \* -90% result file size
    - \* -35% run time
  - Thermomechanical analysis
    - \* -85% result file size
    - \* -15% run time
  - Specific improvements with encrypted material models
    - \* -50% run time
    - \* -40% peak memory usage
- New remote job submission
  - Pre/post-processing with user interface on Windows only
  - Job run on Windows or Linux
  - Job submission: direct or via queuing system (PBS or LSF)
- Printer database update
  - FDM: New Stratasys Fortus 450mc
  - SLS
    - \* Sintratec Kit
    - \* Sintratec S1
    - \* Sintratec S2
- Support of Stratasys toolpath v2.2 : available from Insight 13.9 or GrabCAD Print 1.34
- Various enhancements
  - Improved physics in inherent strain preprocessing for FFF/FDM (energy conservation is ensured)
  - Project management
    - \* Save at exit when run completed / inherent strains have been computed
    - \* Working directory saved in the project
  - Licensing: user interface can be closed once job is launched, enabling the post-processing of another simulation result

---

### II.1.2 Digmat 2019.0

---

In this section of the documentation, you can find all major changes that are in Digmat 2019.0.

### Digimat-MF

---

- New strain rate dependent  $J_2$ -plasticity model
  - Straightforward piecewise-linear dependency function definition for  $J_2$ -plasticity model
  - First and second order homogenization are both supported
- Revised default settings for microstructures with matrix + inclusion
  - Number of angle increment = 12
  - Store pseudo-grain stress-strain history = on
  - Homogenization order = second
  - Default orientation type for inclusion phase = orientation tensor
  - Aspect ratio for inclusion = 20
- Engineering constants naming change: naming now follows the numerical notation for computed engineering constants
- Enhanced FPGF fatigue failure model
  - New FPGF fatigue multilayer failure trigger
  - New flexible FPGF fatigue failure indicator enabling full control of X, Y and S strength

*Remark:* Caution: legacy FPGF fatigue models created with Digimat 2018.1 or previous versions are not supported starting from Digimat 2019.0. If a material model is to be used with Digimat 2019.0, then it has to be created using Digimat 2019.0.

### Digimat-FE

---

- Filament decohesion modeling for Fused Filament Fabrication RVE
  - Definition of interface/interphase between filament
  - Unit cell duplication in X, Y and Z direction
- New foam microstructure
  - Open cell and closed cell foam types
  - Random, Kelvin and custom foam topologies
  - Applicable for small strain applications
- New geometry controls for more robust mesh generation
  - "Minimum distance to RVE face" to avoid inclusions too close to RVE face
  - "Minimum angle to RVE face" to avoid partial inclusions difficult to mesh
  - Non-geometrical 2nd order elements
- General improvements
  - Confirmation message upon loading large .t16 result files
  - Warning message for finite strain definition if applied strain is larger than 0.05
  - New default chordal ratio value = 0.1
  - Updated FE/Solver version

### Digimat-MX

---

- Enhanced SFRP fatigue reverse engineering
  - Support of multilayer failure trigger for improved accuracy
  - Support of any loading angle
  - Enhanced fatigue reverse engineering workflow enabling full user control of fatigue failure indicator parameters (previous identification method is not available anymore)
- SFRP stress localization factor for improved fatigue accuracy

- Specimen geometry definition
- Automated dumbbell FEA to compute stress localization
- New material data in public database
  - DSM
    - \* Additional conditions for several grades:
      - Akulon K224 (PG6,PG8)
      - Stanyl TW241F10
      - Stanyl TW200F6
      - Arnite AV2 390 XT
    - \* Addition of new grades for injection:
      - Akulon Ultraflow K-FHG12
      - ForTii Ace MX53T
      - Akulon K224-HG7
      - Akulon Ultraflow K-FHG0
    - \* Addition of new grades for Additive Manufacturing (FFF):
      - Novamid ID 1070
      - Novamid ID 1030
      - Novamid ID 1030-CF
      - Arnite ID 3040
  - SABIC
    - \* Addition of new grades:
      - Noryl FE1520PW
      - Noryl GFN2F
      - Noryl GFN3F
      - Thermocomp EC004APQ
      - Thercomcomp EC008APQ
  - DuPont Performance Materials
    - \* Addition of new grades:
      - Zytel 70G60HSLA BK099
      - Zytel 74G33W BK416
      - Crastin FR684NH NC010
      - Crastin SK605 NC010
  - Solvay Specialty Polymers
    - \* Additional conditions for several grades:
      - Ixef 1022
      - Ketaspire KT-880 GF30
      - Ryton R-4-200
    - \* Addition of new grades:
      - Amodel A-8950 HS
      - Ixef 1032
      - Ketaspire KT-820 GF30
      - Ryton BR42B
      - Ryton R-4-270
    - \* Addition of new grades for Additive Manufacturing (FFF):
      - KetaSpire PEEK-CF AM Filament
      - Radel PPSU AM Filament
  - Borealis (New material supplier)
    - \* Addition grades for injection:
      - Fibremod GB307HP
      - Fibremod GB402HP
      - Fibremod GB477HP
      - Fibremod GD577SF

- Sumika Polymer Compounds(New material supplier)
  - \* Addition grades for injection:
    - Thermofil F610X99
    - Thermofil F611X99
    - Thermofil F711X99
    - Thermofil F811X99
    - Thermofil F911X99
- Asahi-Kasei Corporation
  - \* Addition of new grades:
    - Leona 92G60
    - Leona SG105
    - Leona SG106
- Kuraray Co. Ltd.
  - \* Additional conditions for existing grades:
    - Genestar G1300A
    - Genestar G1301A
    - Genestar G1350A
    - Genestar G1500A
  - \* Addition of new grades:
    - Genestar G1352A
    - Genestar GN2330
    - Genestar G1300H
- Stratasys Inc.
  - \* Addition a new grade:
    - Nylon 12 CF
- Solvay Engineering Plastics
  - \* MMI database updated, new grades and new models.
  - \* 68 grades for injection.
  - \* 1 grade for AM process

## Digimat-MAP

---

- Support of porosity data from Volume Graphics
  - Support of macro porosity input (export to element set)
  - Support of diffuse porosity input (export to porosity file)
- Support 3D to 2D weld line mapping
- More robust weld line mapping procedure
  - Enhanced robustness of weld line mapping algorithm to reduce mesh sensitivity
  - New weld line radius option to control width of weld line area
- Enhanced support of symmetric Moldflow mid-plane data: data between [0, 1] are automatically extended to [-1, 1]

---

**Digmat-CAE**

---

- Updated support of the existing interfaces for user subroutines
  - Abaqus: 6.14-1 / 2016 / 2017 / 2018
  - ANSYS: 18.2 / 19.0 / 19.1 / 19.2
  - LS-DYNA: 9.1 / 9.2 / 9.3
  - PAM-CRASH: 2015 / 2016 / 2017 / 2018
  - Marc: 2017.1 / 2018
  - Samcef: V16.3 / V17.2
  - nCode: 2018.1
- Automatic Fiber Placement enhancements
  - Local thickness export to Samcef
  - New output for UD: stress in the material frame
- Simplified installation of Digmat with other user subroutines: available for Abaqus
- Improved accuracy of Hybrid solution for accumulated plastic strain failure indicator

---

**Digmat-RP**

---

- Extended Digmat-RP/Moldex3D microstructure estimation
  - Weld line location now available for 3D mesh
  - Fiber orientation now available for 2D mesh
- Updated solver for Digmat-RP/Moldex3D solver
  - Upgrade from Moldex3D R14 to R16
  - New BLM meshing strategy requiring no mesh control
- New SFRP fatigue post-processing capabilities
  - Lifetime computation for constant amplitude loading
  - Various post-processing methods available
  - Support of Abaqus and ANSYS FEA results
- Composite output management: control of output for indicator of alignment, achieved potential stiffness and first eigenvalue for orientation tensor
- New default settings
  - Hybrid solution template set by default: enforced for models using EP strain rate, TEP, EVP, VEP and TVEP with interaction law and failure (except if Macro solution is available)
  - Micro + Hybrid failure template is not available anymore
- Nonlinear macro solution for LS-DYNA
  - Direct input of macroscopic EP and EVP LS-DYNA material cards based on Digmat material model
  - Max/min principal strain failure indicator
  - Support of LS-DYNA/Explicit only
  - Support of both shell and solid elements
- Support of fiber reinforced polymer for FFF and FDM processes: fiber orientation distribution defined through toolpath file

### Digimat-VA

---

- New parametric study workflow
  - Available for material, layups and some test parameters
  - Dedicated post-processing and 2D plots
- New in-plane shear test
  - V-notch or  $\pm 45^\circ$  tests
  - Matrix shear strength now available as model parameter
- Extended CLT analysis
  - Direct analysis of unnotched laminates for
    - \* Stiffness
    - \* Strength (1st ply failure)
    - \* Coefficient of thermal expansion
    - \* Coefficient of moisture expansion
  - Available for variability and parametric studies
- Interface to MaterialCenter
  - Import of ply properties stored in MaterialCenter for material model calibration
  - Export of laminate virtual allowables from Digimat-VA to store in MaterialCenter for data management at the enterprise level
- General enhancements
  - Mean values, standard deviation and coefficient of variations are now reported at batch level
  - Export variability for the carpet plot
  - Automatic rerun of analysis with increased applied strain when failure is not reached in carpet plot workflow

### Digimat-AM

---

- Thermo-viscoelasticity model for thermomechanical analysis to simulate relaxation effect
  - Available for FFF, FDM and SLS
  - New cooling time process parameter
- Support remote database
  - Access to remote database is enabled to load and save data
  - Configuration of remote database is accessible
- Support remote database
  - Access to remote database is enabled to load and save data
  - Configuration of remote database is accessible
- Support of Stratasys toolpath v2.1 for FDM: now includes geometrical transformation information (scaling and rotations) to ensure workflow consistency between physical and virtual print
- -40% reduced file size for thermomechanical analysis
- Enhanced thermomechanical solver robustness
- Improved temperature modeling for FFF/FDM application using thermal or thermomechanical analysis

### II.1.3 Digimat 2018.1

---

In this section of the documentation, you can find all major changes that are in Digimat 2018.1.

---

**Digmat-MF**

---

- Fabric fatigue modeling
  - Extension of UD fatigue model to fabric microstructures
  - Support of basic woven 2D only

---

**Digmat-FE**

---

- Improved workflow efficiency
  - Fabric generation geometry time is reduced by a factor 10
  - RVE with spherical inclusions can now reach up to 70
- Extended range of fabrics: support of Non-Crimp Fabrics (NCF)
  - Definition of UD and stitching yarn
  - Conformal and voxel meshing
- Support of wavy continuous fiber for UD microstructures
  - New type of inclusion shape: curved cylinders
  - Dedicated meshing algorithm (mesh-cutting)
- Multi-material yarns
  - Definition of different materials for different yarns in fabric RVE
  - Support of woven 2D and woven 3D microstructures
- Support of batch workflow under Linux
  - Geometry generation
  - Meshing and job creation
  - Job launch
  - Post-processing

---

**Digmat-MX**

---

- DMA reverse engineering
  - Support of DMA experimental data (tensile or torsional)
  - Dedicated reverse engineering method for viscoelastic model
- Automatic reverse engineering enhancements: switch to 2nd order homogenization for non-linear stiffness performance
- SFRP failure localization evaluation for improved failure accuracy
  - Specimen geometry definition
  - Automated dumbbell FEA to compute failure localization
- Generic MXDB maintenance
  - Elastoplastic and thermo-elastoplastic SFRP models now use 2nd order homogenization
  - Elastoplastic and thermo-elastoplastic SFRP models now propose a FPGF failure model
- New material data in public database
  - Asahi Kasei: 4 new grades (available on request)
  - DSM
    - \* 3 new grades
    - \* 11 new models (some available on request)
  - Dupont
    - \* 3 new grades (available on request)



- \* 1 new model (available on request)
- Radici:
  - \* 4 new grades
  - \* 3 new models (available on request)
- Solvay Engineering Plastics:
  - \* 2 new grades
  - \* 86 new models (some available on request)
- Solvay Specialty Polymers: 1 new grade (available on request)
- Stratasy: 1 new grade (available on request)

### Digimat-MAP

---

- Support of Cadmould data for injection molding
  - Support of binary and ASCII Cadmould formats
  - Support of solid receiving mesh
- Support of Marc export for element set mapping for microstructure submodeling : export of nodes, element, node sets and element sets data
- Support of nodal thickness in LS-DYNA
  - Visualization of local thickness
  - New mapping method to support various shell integration methods: Lobatto, Gauss and uniform

### Digimat-CAE

---

- Progressive failure of reinforced plastics
  - Improved convergence with shell elements and implicit FEA
  - Additional damage law: power law
  - Smart time stepping for implicit FEA
- Updated support of the existing interfaces for user subroutines
  - Abaqus: 6.13-4 / 6.14-1 / 2016 / 2017 / 2018
  - ANSYS: 18.2 / 19.0 / 19.1
  - LS-DYNA: 7.1.2 / 8.1.0 / 9.0.1 / 9.1.0 / 9.2.0
  - PAM-CRASH: 2015 / 2016 / 2017
  - Marc: 2016.0 / 2017.0 / 2017.1
  - Samcef: V16.3 / V17.2
  - nCode: 12 / 13

### Digimat-RP

---

- Embedded superposition for efficient mapping of manufacturing simulation results
  - Visualization of manufacturing and component mesh superposition
  - Automatic or interactive superposition
  - Management of transformation tasks: reset, undo, reset, export and import transformation file
- More robust gate definition in Digimat-RP/Moldex3D: gate location is now defined based on closest node from point pick

- Support of Cadmould data for injection molding
  - Support of fiber orientation data
  - Support of solid component mesh only
- Advanced density definition for SMC NVH using Nastran SOL400
  - Composite density is varying spatially due to the fiber volume fraction variation
  - Support of elastic and viscoelastic material models
- Support of nodal thickness in LS-DYNA
  - Visualization of local thickness for structural model
  - New mapping method to support various shell integration methods: Lobatto, Gauss and uniform
- Support of membrane sections in Nastran SOL1XX & Optistruct (Linear solution): automatic assignment of microstructure and material properties to membrane sections based on adjacent solid data
- Enhanced efficiency for Abaqus Linear solution
  - Improved material properties discretization for shell elements
  - Improved preprocessing time
  - Improved post-processing robustness

### Digmat-VA

---

- Support of unbalanced woven for PFA
  - New material type: woven unbalanced (based on warp and weft rates)
  - Dedicated Digimat model calibration procedure
- Identification of ply shear properties from stress-strain curve
  - Import of shear stress-strain curve when defining ply properties for calibration
  - Automatic identification of  $F_{12,0.2\%}$  and  $F_{12}$  values needed for Digimat model calibration

### Digmat-AM

---

- Thermal and thermo-mechanical analysis with advanced solver
  - Available for FFF, FDM and SLS
  - Local material temperature can be predicted and analyzed
  - Local impact of printing process (strategy, speed) can be directly taken into account
  - Warpage and residual stresses predictions are improved
  - Additional field post-processing: temperature, crystallinity
  - New history plot for temperature and crystallinity evolution over printing time

---

## II.1.4 Digimat 2018.0

---

In this section of the documentation, you can find all major changes that are in Digimat 2018.0.

---

### Digimat-MF

---

- Accumulated plastic strain failure indicator
  - Critical accumulated plasticity as a function of stress triaxiality
  - Also available for structural analysis with Digimat-CAE and Digimat-RP
- Improved workflow for microstructure definition of fabrics: dedicated microstructure type
- New lattice microstructure type
  - Applicable to model Fused Filament Fabrication dense microstructures
    - \* Filament cross section definition and visualization
    - \* Filament orientation
  - Supports Standard failure definition (Composite level)

---

### Digimat-FE

---

- More efficient post-processing through automatic computation of engineering stress-strain curve. Available for all RVE applications, including void phases and/or cohesive elements
- Custom weave pattern definition for woven 3D materials
  - Available for 3D interlock
  - Graphical editor for weave pattern definition
- Improved workflow for microstructure definition of fabrics: dedicated microstructure type
- New lattice microstructure type
  - Flexible infill definition
    - \* Aligned (Fused Filament Fabrication application)
    - \* Sparse (Fused Filament Fabrication application)
    - \* Double dense sparse (Fused Filament Fabrication application)
    - \* Hexagonal (Fused Filament Fabrication application)
    - \* Custom 2D (Fused Filament Fabrication application): custom definition of microstructure via beams and junctions
    - \* Custom 3D (All applications): custom definition of microstructure via beams and junctions
  - Available for non-reinforced and reinforced materials
  - Available for elasticity and plasticity constitutive models
- User defined failure indicator (only available with Digimat-FE/Solver)
  - Custom failure library to be built by user
  - Instantaneous stiffness reduction is available
- Enhancements for microstructures including curved spherocylindrical inclusions
  - Phase definition now available based on inclusion size, diameter and number of inclusions (leading to inclusion volume fraction computation)
  - More robust geometry and mesh visualization for very large microstructures. Geometry visualization through 1D beams and manual mesh generation if estimated mesh size is higher than 1.7M elements
  - Cohesive element definition now possible between matrix and inclusion phase. Available for Abaqus, Marc and FE/Solver
- New visco-hyperelasticity model. Available for Abaqus, Marc and FE/Solver

- Abaqus models
  - \* Neo-Hookean
  - \* Mooney-Rivlin
  - \* Ogden
  - \* Storakers
- Marc and FE/Solver models
  - \* Neo-Hookean
  - \* Mooney-Rivlin
  - \* Ogden

## Digmat-MX

---

- Naming update: the reverse engineering method "Tensile" is now named "Static and dynamic".
- Handle shear data
  - New experimental data loading: shear
  - Experimental data usable for reverse engineering with Static and dynamic method as well as for failure indicator reverse engineering
- Data ordering filtering: new filtering possibilities in Digimat-MX tables (Grades, Digimat Analysis Files, ...) accessible via direct right-click.
- Reverse engineering for LFRP: new through-thickness definition of fiber aspect ratio and fiber volume fraction in multilayer microstructure definition.
- Reverse engineering for multiple multilayer
  - Enhanced flexibility for microstructure definition associated to each experimental curve used during reverse engineering
  - Each experimental data can be associated to a different multilayer microstructure
- Update of public database
  - Asahi Kasei: new material supplier
  - DSM: 11 new grades
  - Dupont:
    - \* 15 new grades
    - \* 20 new models for existing grades
  - Radici Performance Plastics: 4 new grades
  - Sabic: 2 new models for existing grades
  - Solvay Specialty Polymers: 8 new grades
  - Stratasy Inc: New supplier for additive manufacturing

## Digmat-MAP

---

- Manufacturing data support update
  - Molding
    - \* Moldflow 3D results
      - Weld line and weld surface data
      - Fiber length
      - Porosity
    - \* 3D TIMON results: fiber length
    - \* Moldflow UDM mesh format
    - \* Residual stresses. Export extended to LS-DYNA and Marc

- Additive manufacturing: Stratasys Insight results (toolpath in text format)
- Weld line mapping: export of Digimat weld line file now available in addition to element set export
- Automatic Fiber Placement
  - Loading and visualization of IGES files from AFP manufacturing software
  - Mapping to shell receiver meshes to account for defects (gaps)
    - \* Thickness modification (soft tooling)
    - \* Fiber volume fraction (hard tooling)
    - \* Fiber orientation
  - Export of mapped results
    - \* Thickness: Abaqus only
    - \* Fiber volume fraction and fiber orientation: all FEA
- Air gaps mapping from toolpath files
  - Identification of local air gaps present in a toolpath on a receiving mesh
  - Export of element set corresponding to mapped gaps location. Available for Abaqus, ANSYS, LS-DYNA, Marc, PAM-CRASH and Radioss.
- Support of degenerated SOL186 elements (ANSYS) for receiving mesh

## Digimat-CAE

---

- CAE maintenance: supported version update
  - Abaqus: 6.13-4, 6.14-1, 2016, 2017
  - ANSYS, 17, 17.2, 18
  - LS-DYNA, 7.1.2, 8.1, 9.0.1, 9.1
  - Marc: 2015, 2016
  - Nastran SOL1XX: 2016 or older, 2016.1, 2017.0, 2018.0
  - Optistruct: V13, V14
  - PAM-CRASH: 2014, 2015, 2016
  - PERMAS: 16
  - Samcef: V16, V17
  - nCode: 12, 13
- Initial stresses extension
  - Now supported with the Hybrid solution
  - Extended supported of FEA software
    - \* LS-DYNA
    - \* Marc
- Weld line strength. Definition of a strength degradation factor when using a weld line mapped file in the manufacturing data.
- Strain rate filtering
  - New parameter to filter spurious oscillations of strain rate values during strain rate dependent FEA runs
  - Available with the Hybrid solution only
  - Applicable to failure models using a (V-)EVP material model
- Stiffness reduction extension
  - Revised formulation to remove time step sensitivity
  - Control on linear softening behavior. Definition of equivalent strain from failure initiation to final stiffness reduction
  - Available for
    - \* Implicit & explicit FEA
    - \* Solid & shell elements
- Fused Filament Fabrication failure modeling
  - Available for unfilled polymer materials
  - Available with the Hybrid solution

- Support of encrypted files in ACT. Encrypted material models now supported via direct assignment method
- Bug fix: Teading of orientation file during FEA run:
  - Erroneous behavior: when using an orientation file which does not contain information for all integration points and using the Hybrid solution (using the default keyword `hybrid_minimize_memory = on`), orientation data used for integration points beyond first integration point could be erroneous
  - Fix: orientation file data are now read correctly for any integration point even if orientation file does not contain data for each integration point
- Notice
  - Digi2marc libraries are now directly available from the Digimat installer. No linking operation is required anymore
  - Fluent interface is now available on-request. Contact [digimat.support@mscsoftware.com](mailto:digmat.support@mscsoftware.com) to obtain the installer.
  - Virtual.lab interface maintenance is dropped. Users willing to access the Virtual.lab interface are advised to use Digimat 2017.1 or previous versions.

## Digmat-RP

---

- New user interface
  - New look and feel
  - Revised workflow
    - \* Structural model / Digimat material / Manufacturing data / Solution settings
    - \* User guidance from component definition
      - Manufacturing data type
      - Material type
- Extended support of molding manufacturing data
  - Weld line data (SFRP/LFRP)
  - Fiber length distribution (LFRP)
  - Fiber volume fraction distribution (LFRP)
  - Residual stresses (SFRP/LFRP)
- Support of additive manufacturing
  - FFF
    - \* Material: unfilled polymer
      - From Digimat-MX
      - From file
    - \* Performance (Hybrid solution only)
      - Linear stiffness
      - Elastoplasticity
      - Elastoplasticity + failure
    - \* Manufacturing data
      - Toolpath (gcode)
      - Residual stresses
  - FDM
    - \* Material: unfilled polymer
      - From Digimat-MX (Stratasys materials only)
      - From file (Stratasys materials only)
    - \* Performance (Hybrid solution only)
      - Linear stiffness
      - Elastoplasticity
      - Elastoplasticity + failure
    - \* Manufacturing data

- Toolpath (Insight)
- Residual stresses
- SLS
  - \* Material: unfilled polymer, bead reinforced polymer
    - From Digimat-MX
    - From file
  - \* Performance (Hybrid solution only)
    - Linear stiffness
    - Elastoplasticity
    - Elastoplasticity + failure
  - \* Manufacturing data
    - Global printing direction definition
    - Residual stresses
- Extension of linear solution
  - Abaqus now available on top of Nastran Sol1XX, Optistruct and PERMAS
  - Support of thermoelasticity
- Control of number of material cards: new linear template in Solution settings to control maximum number of material cards: reduction level.

### Digimat-VA

---

- PFA formulation enhancement for Unidirectional materials. Available for filled hole and bearing tests
- User defined material model
  - Custom material model library to be built by user (full procedure described in Digimat documentation)
  - Definition of input parameters and outputs results in Digimat-VA user interface
  - Applicable to variability scenarios
- First ply failure material model
  - Available for Unidirectional composites
  - Based on Tsai-Hill 3D Transversely Isotropic failure indicator
  - Dedicated post-processing
    - \* Failure indicator output
    - \* Critical ply identification
    - \* Driving failure mode output
- Additional process-related variability : ply misalignment (angle standard deviation definition)
  - Aligned plies
  - Non-aligned plies

### Digimat-AM

---

- New FDM manufacturing type: provides access to Stratasys applications
  - Fortus 900mc printer
  - ULTEM 9085 material (available on-request)
- Support failure modeling (FFF/FDM)
  - Visualization of support location
  - Definition of interface strength in Material model definition
  - Definition of failure modeling approach

- \* Failure index
  - \* Decohesion
  - Output of failure index value in Results
- Chamber temperature definition (FFF/FDM/SLS)
  - Enhanced definition of chamber temperature
    - \* Constant
    - \* Variable
  - Variable temperature definition via two interpolation models
    - \* Linear
    - \* Exponential
  - Inherent strain computation based on extrema chamber temperatures
  - Visualization of part temperature in results
- Data management
  - Support of encrypted material models for Digimat-AM
  - Inherent strain management
    - \* Can now be saved in Digimat-MX. Characterized via user-defined comments
    - \* Can now be loaded from Digimat-MX
- Anchor pin definition for warpage minimization (FFF/FDM): in Manufacturing step, definition of anchor pin location and diameter

### II.1.5 Digimat 2017.1

---

In this section of the documentation, you can find all major changes that are in Digimat 2017.1.

#### Digimat-MF

---

- Improved robustness and accuracy of advanced material models
  - Crash: viscoelastic-viscoplastic model (VEVP): improved accuracy when using large Plastic Strain Multiplier value
  - Creep: (Thermo-)elastoviscoplastic model ((T-)EVP)
    - \* Improved convergence with Interaction law
    - \* Improved convergence at very low strain rate
  - Effect of porosity for crash of short fiber reinforced polymers: new default for elastoviscoplastic model including void phase: Incremental instead of discrete affine
- Extension of Short Fiber Reinforced Plastic failure model (FPGF) to microstructures including spherical void phase

#### Digimat-FE

---

- New grain inclusion type for polycrystalline materials: specific algorithm for high volume fraction of polyhedral inclusions
- New algorithm for long wavy fiber reinforced matrix RVE
  - Available for 2-phase microstructures defined as



- \* Matrix phase
  - \* Curved sphero-cylindrical inclusion
    - Associated to new meshing technique: mesh cutting (tetra)
- New random fiber perturbation algorithm to reach high volume fraction of inclusions in unidirectional microstructure
  - Up to 90% volume fraction
  - Available for unidirectional reinforced material microstructures
    - \* Continuous fiber inclusion
    - \* Sphero-cylindrical inclusion
- Direct definition workflow for unit cell geometries (available via random fiber perturbation option). Available for unidirectional reinforced material microstructures
  - Continuous fiber inclusion
  - Sphero-cylindrical inclusion
- Enhanced boundary condition definition for Marc and FE/Solver
  - Periodic: default tolerance is now loosened
  - Dirichlet: default tolerance is now tighter
- Extended material model for thermomechanical analysis of woven RVE
  - Yarn can now be modeled as thermo-elastoplastic if matrix is defined as thermo-elastoplastic. Available for Abaqus, Marc and FE/Solver
  - Yarn can now be modeled as thermoelastic if matrix is defined as thermoelastic. Available for Abaqus, Ansys, Marc and FE/Solver
- Improved robustness for failure simulation including damage upon failure
  - Marc: elasticity only is available
  - FE/Solver: elasticity and elastoplasticity are available, with revised damage computation for faster simulation run time
- Extended loading definition: off-axis loadings can be defined for uniaxial1 testing. Theta / phi loading angles can now be fully user defined

## Digimat-MX

---

- Extended support of interactive reverse engineering of material models
  - Crash: V EVP model
    - \* Easy step-by-step workflow for viscoelasticity and viscoplasticity parameters optimization
    - \* On-the-fly choice of viscous model
  - Creep: (T-)EVP model with new Creep submethod
    - \* Easy step-by-step workflow for elasticity, plasticity and creep parameters optimization
    - \* On-the-fly choice of viscous model
- New merge tool of isothermal models: enables easy creation of thermomechanical model from several mechanical models of a same grade at different temperatures. On-the-fly definition of per-phase coefficients of thermal expansion
- Update of MXDB
  - DSM
    - \* Additional conditions for several grades: Akulon K224 (HG0,HG6,PG6,PG8) and for Stanyl TW241F10
    - \* Addition of new grades: Akulon Ultraflow K-FHG0, Akulon S223-HG0, Akulon Diablo HDT 2500 and Stanyl Diablo HDT 2700
    - \* Models are available with hybrid parameters
  - Solvay Engineering Plastics
    - \* MMI database updated
    - \* Addition of new grade for SLS: TECHNYL Powders PA6 6300 HT 110 Natural
  - Radici
    - \* Models updated for Radilon A RV300W, ARV350W and S RV300W

- \* Addition of new grade: Radilon A RV500RW
- Kuraray Co. Ltd.
  - \* Addition of 3 new PA9T grades: Genestar N1001A-M41, N1006A-M41, N1006D-H31
  - \* 3 new PA9T reinforced glass fiber grades: Genestar G1350A-M42, GX1500A-M61, G1301A-M61
  - \* Experimental data for different temperature are available
- Sumitomo Chemical Europe :
  - \* Addition of SUMIKASUPER E6007LHF grade
  - \* Several models are available on request
- e-Xstream engineering
  - \* Addition of generic data for additive manufacturing

## Digmat-MAP

---

- Mapping of toolpath information for structural analysis of additive manufactured parts (FFF)
  - Loading and visualization of .stl file
  - Loading and visualization of .gcode file
  - Superposition of geometry/toolpath with structural mesh
  - Mapping of toolpath to structural mesh
  - Export of an orientation file for further structural analysis with Digimat-CAE
- Mapping of residual stresses from Digimat-AM for structural analysis of additive manufactured parts (FFF/SLS)
  - Loading and visualization of Digimat-AM mesh (.dat)
  - Loading and visualization of Digimat-AM residual stresses (.xml)
  - Superposition of Digimat-AM mesh with structural mesh
  - Mapping of residual stresses
  - Export to FEA
    - \* Abaqus
    - \* Ansys
- Support of fiber volume fraction data from 3D TIMON
  - 3D/3D mapping
  - 3D/2D mapping

## Digmat-CAE

---

- Structural analysis of additive manufactured polymer parts
  - FFF
    - \* Unfilled polymer
    - \* Performance (Hybrid solution only): Linear and non-linear stiffness
    - \* Connection to manufacturing: Toolpath information from .gcode file
  - SLS
    - \* Unfilled & reinforced polymers (bead or fiber)
    - \* Performance: Linear and non-linear stiffness + failure
    - \* Connection to manufacturing: homogeneous printing direction defined in material model
- Extension of the Hybrid method
  - MuCell & metal casting: support of the effect of porosity volume fraction on material behavior
    - \* Unfilled & reinforced matrices (bead or fiber)

- \* Performance: linear stiffness (elasticity), non-linear stiffness + failure (elastoplasticity) and crash (elastoviscoplasticity)
- \* Failure model accessible with the Hybrid solution: linear function of porosity volume fraction on the strain at failure
- \* Creep: Thermo-elastoviscoplasticity model is now supported
- Bug fix for stiffness reduction/element deletion in implicit FEA
  - \* PFP output (percentage of failed integration points) computation is now corrected when non-convergence can occur
  - \* Fix residual stiffness computation for specific configurations

### Digimat-VA

---

- New countersunk fastener geometry: available for filled hole and bearing tests
- CPU time reduction & improved solver convergence: average 50% CPU time reduction for UNT/C & OHT/C tests

### Digimat-AM

---

- Create printing project
  - \* Visualize and select printer
    - Generic SLS
    - Generic FFF
  - \* Define Component
    - Load geometry (.stl)
    - Define material: select from database or create new
- Define Manufacturing
  - \* Define part orientation (SLS only)
  - \* Define warpage compensation
    - Apply anisotropic scale factor
    - Load modified geometry (.stl)
  - \* Load and visualize toolpath (FFF only / .gcode format)
  - \* Define other process parameters
- Run simulation
  - \* Generate voxel mesh: coarse/medium/fine/user defined mesh size
  - \* Define material model settings: Warpage computation approach: inherent strain
    - On-the-fly computation of inherent strain via micromechanical modeling
    - Direct user input: mechanical and thermal or total
    - From previous project
  - \* Submit job
    - Review project definition
    - Prepare job: define working directory and number of CPUs
    - Launch job (local run only)
    - Monitor job
- Post-process
  - \* View results
    - Field visualization: displacement, stress and warpage indicator
    - Visualization format on voxel mesh or on stl

- Warpage visualization tools: scale factor for deformed shape and superimpose undeformed shape
- Export results
  - \* Warped shape (.stl file with user defined scaling factor)
  - \* Residual stresses (Digimat XML format for further usage in Digimat-MAP)
- Transversal aspects
  - Project management
    - \* New
    - \* Save
    - \* Load

## II.1.6 Digimat 2017.0

---

In this section of the documentation, you can find all major changes that are in Digimat 2017.0.

### Digimat-MF

---

- New SFRP fatigue model for improved lifetime predictions: Model extended to viscoelasticity
- Extended range of available woven 3D weave patterns
  - Weave depth definition in the case of 3D orthogonal woven materials
  - Automated definition of standard weave patterns : diagonal, plain, satin and twill
  - Irregular weave step through a vector
- Improved accuracy of Drucker-Prager model
  - Revised sensitivity to Plastic Strain Multiplier (PSM) ensures consistency with J2-plasticity model
  - Drucker-Prager material models from previous Digimat releases using modified spectral method, and  $PSM > 1$  require a new calibration

### Digimat-FE

---

- Improved microstructure generation for SFRP
  - Higher volume fraction can be reached for all types of fiber orientations
  - Microstructure is generated faster
  - Available for 2-phase microstructures defined as
    - \* Matrix phase
    - \* Sphero-cylindrical inclusions
- Failure model for Discontinuous Fiber Composites
  - Inter-strand delamination failure mode can be modeled to predict RVE ultimate strength
  - Available for
    - \* FE solver
    - \* Marc
    - \* Abaqus
- Extended range of available woven 3D weave patterns (similar to Digimat-MF)

- Weave depth definition in the case of 3D orthogonal woven materials
- Automated definition of standard weave patterns : diagonal, plain, satin and twill
- Irregular weave step through a vector
- Improved weave pattern definition via additional control parameters
  - Yarn crimp to control tortuosity between warp and weft
  - Yarn spacing ratio to control matrix pocket size between yarns
- Conforming meshing for woven 2D geometries: Obtain detailed description of local stress & strain fields thanks to conforming approach
- Extended modeling of SFRP fiber tips
  - Coatings can now be applied only on lateral faces of cylindrical inclusions
  - Suppressed contact condition between fiber tips and matrix
- GUI improvements
  - Woven definition step has been reviewed to avoid the need to scroll to enter all parameters
  - Post-processing of orientation tensor of generated RVE: user now has access to tensor values with 4 decimal digits (was 2 in previous version)
  - "Generate geometry" button is now greyed out during geometry generation

## Digimat-MX

---

- CFRP automatic reverse engineering to speed up and simplify material model creation
  - Import composite datasheet
  - Turn composite datasheet into Digimat material model in 1 click
  - Available for UD and woven 2D materials (Glass and carbon fibers)
  - Available performances
    - \* Linear elasticity
    - \* Progressive Failure Analysis
- Improved SFRP failure reverse engineering procedure: manual definition of strain localization factor
- IT
  - DAKOTA new version
  - Support of white space in working directory
- New material data in public database
  - DSM
    - \* Akulon Diablo HT-HG0
    - \* Akulon K224-HG6
    - \* Akulon K224-HG7
    - \* Akulon K224-HG8
    - \* Akulon K224-PG8
    - \* Akulon S223-HG6
    - \* Akulon S223-HG7
    - \* Arnite AV2 390 XT
    - \* Arnite TV4 261
    - \* Akulon K224-HG0
    - \* ForTii MX3
    - \* ForTii Ace MX53
    - \* Akulon S223-HG0
    - \* Akulon K224-PG6
    - \* Fortii MX1
    - \* Stanyl Diablo OCD2100
    - \* Akulon Diablo HT-HG0
    - \* Akulon Diablo HT-HG6

- \* Stanyl TW241F10
- Dupont
  - \* Crastin HR5315HFS NC010 (New Temperature and humidity levels available)
  - \* Crastin HR5330HFS NC010
  - \* Zytel 70G30HSLR BK099 (New Temperature and humidity levels available)
  - \* Zytel 70G35HSLRA4 BK267 (New Temperature and humidity levels available)
  - \* Zytel 70G35HSLX BK357
  - \* Zytel 70G35HSRX BK099
  - \* Zytel 70G50HSLA BK039B (New Temperature and humidity levels available)
  - \* Zytel FE270099 BK099
  - \* Zytel HTN51G35HSLR BK420
  - \* Zytel PLS95G35DH1 BK549
  - \* Zytel XT70G35HSL BK044A

## Digmat-MAP

---

- Warpage mapping for injection molding
  - Mapping of displacement fields predicted by injection molding simulation
    - \* Moldflow mid-plane
    - \* Moldflow 3D
  - Export of boundary condition card for receiver mesh
    - \* Abaqus
    - \* Samcef
    - \* PERMAS
- Extended mesh support
  - Optistruct (.fem)
  - PERMAS (.dat, .uci)
- New general mapping and data manipulation capabilities
  - FEA result files mapping
    - \* Load FEA results, select and visualize fields
    - \* Map to receiving mesh
    - \* Available for Abaqus
  - New data operation to easily perform manual correction of large files
    - \* Apply scale factor on data loaded on a given mesh
    - \* Perform any linear combination of 2 similar data type files loaded on a given mesh
  - Element set mapping
    - \* Map element sets from donor to receiver mesh
    - \* Supported for 3D/3D and 2D/2D mapping
- 2nd order elements are now supported for donor mesh

## Digmat-CAE

---

- Progressive failure of SFRP for ultimate strength predictions
  - Evaluate consequences of failure initiation in quasi-static simulations
    - \* Isotropic damage (all implicit FEA solvers)

- \* Element deletion (Abaqus, LS-DYNA/Implicit, Marc)
    - Available when using the Hybrid solution
    - Check documentation for best practices on achieving FEA convergence up to ultimate failure
- Additional default outputs for SFRP to ease post-processing
  - Triaxiality (if using material model including tension/compression differentiation)
  - Damage (if activating stiffness reduction upon failure)
  - Percentage of failed integration points (if considering failure model)
- Extension of viscoelastic-viscoplastic Hybrid solution for improved accuracy
  - Yield stress can now be strain rate dependent
  - Material support has been extended from SFRP to include UD and woven 2D
- Reduced CPU time for CFRP Progressive Failure Analysis with Explicit FEA and solid elements
  - 4-5x faster computation
  - Available for UD and woven 2D materials
  - Link to manufacturing data (draping) is not supported
  - LS-DYNA and MSC Nastran SOL700 are not supported, CPU time is only available when using shell elements for those FEA codes
- Extended PAM-CRASH interface
  - Support 3rd party user materials: Digimat now uses plug-in MAT85 and MAT185 approach to allow multiple user subroutines to be used in the same FEA analysis
  - Export of Digimat outputs in State Variables for solid & shell elements (only for hybrid method)
- Improved lifetime predictions for fatigue analysis
  - Material behavior can now be modeled as non-linear and frequency dependent (viscoelastic constitutive model)
  - Fatigue failure model response is now dependent on the local load ratio
- Updated support of the existing interfaces for user subroutines
  - Abaqus: 6.13-4 / 6.14-1 / 2016
  - ANSYS: 16.0 / 16.2 / 17.0 / 17.2
  - LS-DYNA: 7.1.2 / 8.1
  - Radioss: 13.0 / 14.0
  - Marc: 2015.0 / 2016.0
  - Samcef: 16.3 / 17.2
- Improved accuracy of Hybrid solution for very ductile materials: Micro/Hybrid consistency for non-linear response is now automatically ensured
- New progress bar and time estimation during Hybrid solution pre-processing
- Improved estimation of transverse shear stiffness: value is now computed on composite material instead of stiffest phase properties
- Bug fix in Hybrid strain based failure / shell: Failure criteria value is now computed correctly

## Digimat-RP

---

- Extension of supported FEA interfaces
  - Radioss / shell is added to support both solid & shell
  - Optistruct / solid & shell: Elastic material model only / weak coupling
  - Permas / solid & shell: Elastic material model only / weak coupling
- Extended support of FEA input deck
  - Input decks with same identical assigned to solid and shell elements can now be loaded in Digimat-RP (no Digimat material model can be assigned for that specific material)
  - Input decks with multi-material definitions in composite section can now be loaded in Digimat-RP (no Digimat material model can be assigned for that specific composite section)
- Bug fix: Corrected visualization of ellipsoidal plot of orientation tensors

---

## Digmat-VA

---

- New bearing test is available for a wide range of configurations
  - Single shear bearing: Two pieces, Single-fastener
  - Tension
    - \* Unstabilized
    - \* Stabilized
  - Compression (stabilized only): Double-fastener
  - Tension
    - \* Unstabilized
    - \* Stabilized
  - Compression (stabilized only): One piece (tension, unstabilized only)
  - Double shear bearing (tension, unstabilized only)
- CPU time reduction: New option to enable adaptive time stepping to minimize number of time steps and reduce overall CPU time. Available for unnotched and open-hole tests (i.e. tests which do not involve contact modeling)
- Remote job submission for efficient computation of large VA campaigns
  - Test matrix preparation and post-processing is performed on desktop application (Digmat-VA user interface), and FEA computations can now be sent to remote cluster
  - Job monitoring can be performed from desktop application
  - Type of job submission
    - \* No queuing system
    - \* LSF
    - \* PBS

---

## Additional information

---

- Support of Windows 10
- New license format in accordance with MSC template to minimize license administration for paid-up schemes. Version ID in a feature line is now turned into a maintenance end date

---

## II.1.7 Digmat 2016.1

---

In this section of the documentation, you can find all major changes that are in Digmat 2016.1.

---

## Digmat-MF

---

- Improved robustness of Drucker-Prager model
  - Convergence improvement
  - Default value change: dilatation angle set to 0 by default



- New harmonic analysis
  - Definition of frequency dependent viscoelastic material properties
  - Definition of harmonic loadings
    - \* Harmonic strain
    - \* Harmonic stress
  - Homogenization and plot of frequency dependent properties
    - \* Real part
    - \* Imaginary part
- New relative tolerance for homogenization schemes to improve convergence
  - New default parameter
  - Independence of tolerance value regarding implicit/explicit CAE
- Revised pseudo-grain fatigue failure indicator definition
  - Migration of reverse engineering capability to Digimat-MX
  - Definition of failure indicator via pseudo-grain S-N curves
  - Retro-compatibility ensured for Digimat analysis files from previous versions: automatic reverse engineering still performed in Digimat-MF
- Improved SFRP fatigue analysis
  - Full equivalency of amplitude and cycle based loadings
  - Support of mean-stress sensitivity model with amplitude loadings
  - New default log-linear extrapolation between minimum and maximum number of cycles to improve robustness of reverse engineering

## Digimat-FE

---

- Extension of Digimat-FE/Modeler
  - Internal mesher (conforming and voxel) now also available for
    - \* Abaqus/Standard
    - \* ANSYS
    - \* LS-DYNA/Implicit
  - Including support of fabrics and discontinuous fiber composites
  - Export of FEA model and job monitoring
  - Full workflow available in command line
  - Limitation: post-processing for LS-DYNA is not available inside Digimat-FE
- New failure capabilities to predict strength of RVE
  - Available for Marc and FE solver
  - Definition of stress based failure indicators at the material level
    - \* Component
    - \* Von Mises
    - \* Tsai-Hill 3D transversely isotropic
    - \* Tsai-Wu 3D transversely isotropic
    - \* Hashin 3D
  - Computation of damage based on failure indicator
  - New outputs post-processing
    - \* Failure indicator
    - \* Damage
  - Available for all microstructures, including fabrics
- User interface robustness improvement: enhanced stability
- Usability improvement
  - Centralization of all geometry parameters in a single screen to simplify successful geometry definition
  - New default geometry parameters to improve meshing step
    - \* Minimum relative distance between inclusion set to 5%

- \* Minimum inclusion relative volume set to 5%
  - Simplified workflow to define discontinuous fiber composites: definition of new type of phase: strand
- New plasticity model for yarn to model non-linear behavior of fabrics
  - Yarn plasticity model automatically defined based on matrix elastoplastic model, fiber elastic model and yarn microstructure
  - Available for Abaqus/Standard, ANSYS, FE solver and Marc
  - Available for all fabric types
- New auto-save of Digimat-FE session to ensure backup of model setup
  - Material definition
  - Geometry
  - Mesh
- Support of pressure dependent plasticity material model for Abaqus/Standard: definition of Drucker-Prager model
- New meshing option for improved mesh quality
  - Continuous meshing strategy (shared node) available for conforming mesh
  - Applicable to basic RVE geometry
  - Not available for RVE involving coatings and interfaces
- Support of SMP with FE solver (identical licensing as DMP)

## Digmat-MX

---

- New automatic reverse engineering to speed up and simplify material model creation
  - Fully automatic reverse engineering methodology
  - Required input data required limited to experimental data (stress-strain curves). No need of a Digimat analysis file template
  - Available for experimental data associated to SFRP materials fibers ("chopped fibers (short)" type of grades)
  - Available performances and related models
    - \* Linear stiffness / elasticity
    - \* Non-linear stiffness / plasticity
    - \* Non-linear stiffness + failure / plasticity + FPGF
  - Speed-up of reverse engineering via support of multiple CPUs
  - Review of model parameters with reverse engineering report
  - Previously existing reverse engineering methodology renamed as "interactive"
- Extension of interactive reverse engineering
  - Drucker-Prager model for calibration of pressure dependent plasticity model
    - \* Optimization restricted to yield function coefficient
    - \* Yield stress exponent and dilatation angle are set to recommended value to ensure model robustness
  - Speed-up of reverse engineering via support of multiple CPUs
- Simplification of local database installation and usage
  - Installation of local database when installing Digimat
  - Direct access to database content when opening Digimat-MX. Database management tools accessible inside the main Digimat-MX window
- New fatigue capabilities
  - Import and plot of S-N curves
  - Import and plot of SFRP pseudo-grain fatigue material model
  - Reverse engineering of SFRP pseudo-grain fatigue failure model: migration from Digimat-MF to Digimat-MX
- Extension of unit conversion tool: support of material models including Hybrid parameters
  - Non crypted
  - Encrypted
- Database content: Solvay Engineering Plastics (Material models now available every 5°C instead of 10°C)

### Digimat-MAP

---

- Revised mapping algorithm to reduce mapping CPU time
  - 70-95% reduction of CPU time for mapping
  - Applicable to all type of elements and data
- New data merge tool to create a single file from multiple files of same type of data
- Improved graphical performance when displaying large models. Instabilities may be observed for graphical configurations using old driver versions that do not support OpenGL 3.3
- Support of new elements
  - Abaqus: C3D10I/C3D10HS (orientation data stored at element level in 2016.0, now stored at integration point level)
  - ANSYS: SOLID285
  - LS-DYNA
    - \* Type 16 and 17 (10 nodes tetrahedral with 5 integration points)
    - \* Type 16 (fully integrated shell elements)
- New draping capabilities
  - Extension of mapping to multilayer draping files & UD orientation files
  - Visualization of yarn shear angle when displaying orientation data for woven
  - New interface to Aniform
- Interface to PAM-RTM
  - Mapping of porosity data to receiver mesh
  - Available for 3D models only
    - \* PAM-RTM
    - \* receiving mesh
- Support of odd number of layers in shell models

### Digimat-CAE

---

- Support of SMP parallelization scheme
  - Support of implicit FEA codes
    - \* Abaqus/Std
    - \* Ansys
    - \* Marc
  - Reduced memory consumption
  - Support of mixed DMP/SMP parallelization scheme
  - Identical licensing as for DMP
- New pressure sensitive elastoplasticity model
  - Available with the Hybrid solution for efficient and robust coupling with FEA
  - Drucker-Prager model from Digimat-MF required as input
- New basic SFRP fatigue solution
  - Fatigue failure indicator (number of cycles to failure) available as output state variable in Digimat coupled analysis
  - Available for all implicit FEA codes
  - Available for solid and shell elements
- Reduced CPU time in explicit/shell/Hybrid configurations: 10% CPU time reduction
- Revised thermo-elastoplasticity model for the Hybrid solution
  - Improved accuracy of CTE (Coefficient of Thermal Expansion)
  - Constituent CTE used as input for the Hybrid solution must have been reverse engineered from a thermo-elastic model

- Extension of NVH capabilities with Marc: anisotropic and frequency dependent damping based on local microstructure
- Support of new versions of the existing interfaces
  - Abaqus 2016
  - ANSYS 16.2 and 17
  - PAM-CRASH 2015
  - Marc 2015.0
- Support of new elements
  - Abaqus: C3D10I/C3D10HS (orientation data stored at element level in 2016.0, now stored at integration point level)
  - ANSYS: SOLID285
  - LS-DYNA :
    - \* Type 16 and 17 (10 nodes tetrahedral with 5 integration points)
    - \* Type 16 (fully integrated shell elements)
- Interface to Ansys Fluent
  - Computation of local SFRP thermal conductivities based on local microstructure
  - Available in command line only

## Digmat-RP

---

- Automatic reverse engineering
  - Available for SFRP
  - Import of stress-strain data curves
    - \* Text file
    - \* Copy/paste
  - Available performances and related material models
    - \* Linear stiffness / elasticity
    - \* Non-linear stiffness / plasticity
    - \* Non-linear stiffness + failure / plasticity + FPGF $\mu$
  - Speed up of reverse engineering via support of multiple CPUs
  - Review of material model parameters
- Orientation file merge tool available for mapped orientation files
- Extension of unit conversion tool: support of material models including Hybrid parameters
  - Non crypted
  - Encrypted
- Support of SOL108 and SOL111 for Nastran 2016.1
  - 15% faster SOL108 solution compared to Digimat 2016.0 + Nastran previous versions
  - 500-600% faster SOL111 solution compared to Digimat 2016.0 + Nastran previous versions
- Support of SMP: choice between SMP and DMP scheme upon job submission
- Support of new SFRP fatigue capabilities
  - Loading and visualization of fatigue material model
  - Definition of fatigue related parameters for standalone Digimat fatigue analysis
- Updated Moldex3D API for Digimat-RP/Moldex3D: upgrade to Moldex3D R14

## Digmat-VA

---

- New filled hole test
  - Bolt or countersunk fastener type
  - Tension and compression loading
- New smart analysis stop upon load drop
- New VADB migration tool: import data from previous VADB during Digimat installation

---

**Additional information**

---

Shift to new FlexLM version (v11.13) for license server (available under Linux and Windows)

---

**II.1.8 Digimat 2016.0**

---

In this section of the documentation, you can find all major changes that are in Digimat 2016.0.

---

**Digimat-MF**

---

- Multi-layer failure controls for SFRP
  - Multilayer RVE failure can be controlled based on
    - \* First layer failure
    - \* All layers failure
    - \* Given thickness fraction of failed layers
    - \* Average value of failure indicator across thickness
    - \* Specific layer failure
  - Improved failure description of skin/core microstructures
- Progressive failure of woven composites: available for 2D woven composites
- 3D woven
  - Available predefined weaving patterns
    - \* 3D orthogonal
    - \* Interlock woven
  - Material performance: elasticity
- Improved user workflow for woven and braided model creation
  - Single fabric item instead of woven or braided definition
  - Automatic creation of RVE if required
- Carpet plot generation
  - Available for UD and woven composites
  - Explore layup design space with
    - \* Stiffness carpet plot
    - \* First ply failure carpet plot
- Failure envelope generation
  - Visualization of the failure model predictions for biaxial loads
  - Stress or strain envelopes
  - Available for SFRP, UD and woven composites
- Fatigue mean-stress correction
  - Scope of application of the pseudo grain fatigue model enhanced to varying load ratios
  - Definition of Haigh like diagram at pseudo grain level to predict R-ratio sensitivity of SN curves of SFRP

## Digmat-FE

---

- Support of thermo-elastoplastic material model
  - Analyze non-linear thermo-mechanical response of any microstructure
  - Capability available for FE solver, Marc, Abaqus
- Improved user workflow for woven/braided model creation
  - Single fabric item instead of woven or braided definition
  - Automatic creation of fabric RVE if required
- Definition of multi-layer 2D woven microstructure
  - Periodic RVE implies restrictions on
    - \* Layer dimensions
    - \* Yarn orientation
  - Support of multimaterial for multilayer definition: Homogeneous material, UD, woven, SFRP,
- Definition of multi-phase microstructures involving woven: Support of inclusions in matrix phase of woven microstructure
- New periodic boundary conditions
  - In-plane periodic boundary conditions with stress free boundary conditions through thickness
  - Recommended for multilayer microstructures
- 3D woven: Available predefined weaving patterns
  - 3D orthogonal
  - Interlock woven

## Digmat-MX

---

- Automatic update of MXDB: 1-click update of MXDB to 2016.0 database structure
- Addition of NCAMP and AGATE data in public database
  - Ready-to-use progressive failure model
    - \* Tensile calibrated stiffness with asymmetric failure
    - \* Compression calibrated stiffness with asymmetric failure
    - \* Available for various conditions: CTD, RTD, ETW,...
  - AGATE
    - \* NCT321 G150 / Unidirectional
    - \* G30-500 7740 / Unidirectional
    - \* T700GC 2510 / Unidirectional
    - \* T700 E765 / Unidirectional
    - \* 7781GF-8HS 2515 / Woven
    - \* T650-8H 7740 / Woven
    - \* T650-PW 7740 / Woven
    - \* T700-PW 2510 / Woven
    - \* T300-5HS E765 / Woven
  - NCAMP
    - \* AS4 8552 / Unidirectional
    - \* 6781 S2 MTM45-1 / Unidirectional
    - \* IM7 8552 / Unidirectional
    - \* AS4 8552 / Woven
    - \* T650 5320-1 / Woven
    - \* NCT4708 MR60H / Woven
    - \* G30-500 MTM45-1 / Woven

### Digimat-MAP

---

- Support of FEA input files including include commands
  - Available for all FEA codes supported by Digimat
  - Transformation commands (translation, rotation) are supported for Abaqus and LS-DYNA
- Iterative mapping for 1-click mapping
  - Improved efficiency of mapping process for dissimilar meshes
  - Automatic progressive increase of mapping tolerance
- Support of 3D TIMON/shell data
  - Fiber orientation only
  - 3D TIMON/shell 3 layers data structure requires usage of a 3 layers shell definition
  - 1D mapping available for FEA codes which require 5 layers
    - \* RADIOSS
    - \* PAM-CRASH
- Support of Moldflow 3D weld line
- Support of ProCAST porosity file

### Digimat-CAE

---

- Improved Hybrid solution accuracy
  - Plasticity model is closer to Micro solution (affects EP model and EVP)
  - Improved stress based failure surface
- Reduced Hybrid solution memory consumption in implicit FEA. Gain is proportional to orientation file size and number of processors used for parallel computation
- Improved user workflow for Hybrid parameters generation: No user interaction (settings definition) required to generate Hybrid parameters
  - Automatic temperature discretization for thermo-mechanical models
  - Improved discretization for strain-rate dependent models
- Progressive failure analysis of 2D woven
  - Support of basic and advanced 2D woven (Orthogonal woven only)
  - Link to draping process is not supported
  - Support of optimized algorithm for explicit FEA/shell elements configurations
- 3D woven
  - Elastic model only
  - Link to the draping process is not supported
- NVH analysis: Improve predictivity of composite NVH analysis with frequency dependent stiffness and frequency dependent anisotropic damping
  - Supported materials: SFRP, UD, woven
  - Support of mechanical small strain models: E, EP, EVP, VEP, VE
  - Available for Marc and Abaqus
    - \* Marc: Frequency dependent stiffness
    - \* Abaqus 6.14: Frequency dependent stiffness for every integration point and Anisotropic and frequency dependent damping tensor
    - \* Abaqus 6.13 and previous: Frequency dependent stiffness
- Support of 3D TIMON/shell data
  - 3 layers data by default
  - 5 layers data available with 1D mapping in Digimat-MAP for the required FEA codes
    - \* PAM-CRASH
    - \* RADIOSS
- FEA interface maintenance
  - PAM-CRASH 2014.0
  - RADIOSS/Optistruct/HyperMesh 13.0

## Digmat-RP

---

- Support of FEA input files including include commands
  - Available for all FEA codes supported by Digmat
  - Transformation commands (translation, rotation) are supported for Abaqus and LS-DYNA
- Access to NVH analysis with Abaqus and Marc
- NVH analysis with MSC Nastran SOL1XX
  - Dynamic analysis (MSC Nastran SOL108 and SOL111) with Digmat viscoelastic model
    - \* Perform MSC Nastran computations with anisotropic elastic and damping properties corresponding to VE properties at a given frequency
    - \* Perform MSC Nastran computation accounting for full frequency dependency of VE properties
  - Static analysis (MSC Nastran SOL101 and SOL 103) with Digmat viscoelastic model: Perform MSC Nastran computations with elastic properties corresponding to VE properties at a given frequency.
- Support of 3D TIMON/shell orientation file

## Digmat-VA

---

- Support of 2D woven material
  - Definition of woven material
  - On-the-fly Digmat model calibration based on datasheet input
  - Progressive failure analysis of UNT/C and OHT/C tests
- Effect of environmental conditions
  - Predict ply properties at a given environmental conditions (temperature, humidity) based on existing data at another environmental condition
  - Available for UD material
- Carpet plot generation
  - Available for UD and woven composites
  - Explore layup design space with
    - \* Stiffness carpet plot
    - \* Strength carpet plot
- Per-layer visualization of FEA results

## Additional information

---

- Support of Windows 8.1
  - Graphical user interfaces in Tools and Solutions
  - Solvers (Except for LS-DYNA 7 interface)
- Support of MSC One licensing
  - Token based licensing scheme providing access to MSC Software's simulation portfolio
    - \* Based on pool of tokens
    - \* Each individual feature requires a certain number of tokens to run
    - \* Tokens are checked out once a feature is called
    - \* Tokens are returned to the pool after each feature use
  - All Digmat products are available in MSC One except Digmat-RP/Moldex3D
  - User can choose between classical licensing (EXLM) or MSC One
    - \* During installation of Digmat product
    - \* After installation, via the Digmat platform in Settings/License



---

## II.1.9 Digimat 6.1.1

---

In this section of the documentation, you can find all major changes that are in Digimat 6.1.1.

### Digimat-MF

---

Bug Fix: Corrected computation of failure criteria used in global axis and at phase level.

### Digimat-CAE

---

- Support of ANSYS 16.0
  - Windows/Linux
  - ACT plug-in for ANSYS workbench
- Support of LS-DYNA 7.1.2 (Windows/Linux)

### Digimat-RP

---

- Fiber orientation estimator powered by Moldex3D
  - Analysis setup in Digimat-RP:
    - \* Geometry extraction from mesh
    - \* Rheological model selection
    - \* Gate definition
    - \* Mesh level selection
    - \* Fiber orientation model definition
  - Mesh and model generation in Moldex3D OEM: eDesign mesh
  - Injection simulation solver
    - \* Local run
    - \* Parallel computation supported
  - Injection molding post-processing in Digimat-RP:
    - \* Fiber orientation
    - \* Melt front time
    - \* Melt front time animation
- Bug Fix: Support of hybrid solution for thermo-viscoelastic models

---

## II.1.10 Digimat 6.0.1

---

In this section of the documentation, you can find all major changes that are in Digimat 6.0.1.

---

**Digmat-MF**

---

- Failure indicators: temperature dependent strengths in failure criteria:
  - Similar capabilities to strain rate dependencies
  - Thermo-elastic and thermo-elastoplastic models
- Progressive failure
  - New multi-component 2D failure indicator
  - Independent damage law per sub-failure indicator
- Drucker-Prager: new formulation of isotropization for enhanced robustness
- Curing:
  - Johnston-Hubert model for UD materials
  - Access to curing state allowing to define specific dependences of material parameters for thermo-elastic and thermo-viscoelastic models
  - No chemical shrinkage
  - Constant CTE definition above and below glass transition temperature
- Outputs: new option allowing to select the number of digits in the output files

---

**Digmat-FE**

---

- Discontinuous long fiber composites: specific RVE generation algorithm allowing to generate DLF microstructures
- Automatic stiffness generation: new options allowing to automatically compute orthotropic engineering moduli (stiffness and conductivities)
- Curing:
  - Available with FE solver
  - Johnston-Hubert model
  - Computation of chemical shrinkage
  - Constant CTE definition above and below glass transition temperature
  - Access to curing state allowing to define specific dependences of material parameters for thermo-elastic and thermo-viscoelastic models
- Additional material models:
  - Thermo-viscoelastic in Marc and FE solver
  - Drucker-Prager in Abaqus
- CPU improvements when post-processing Marc and FE solver results files
- Interface to J-Octa: user definition of inclusions' positions and orientations
- Licensing: mesh generation and visualization now accessible with DIGIMAT\_FE\_MODELER

---

**Digmat-MX**

---

- Reverse engineering of Tsai-Wu 3D transversely isotropic failure criterion
- Improved algorithm for reverse engineering:
  - Local method
  - Global method
- New grades:
  - Radici:
    - \* RADILON A RV300W

- \* RADILON A RV350W
- \* RADILON S RV300W
- Solvay Specialty Polymers
  - \* Veradel AG-330
  - \* Ryton R-4-200BL
  - \* Amodel AS-1145
  - \* Amodel A-6135
  - \* Amodel A-1133
  - \* Ixef 1622
  - \* Ixef 1521
  - \* Ixef 1022
  - \* Amodel AS-1933
  - \* Amodel FC-1150
  - \* Amodel FC-1140
  - \* Amodel AS-4145
  - \* Amodel AS-1945
- Trinseo
  - \* PULSE 979
  - \* VELVEX 5250
  - \* PULSE 630GF
  - \* ENLITE PP LGF 6002 + 67
  - \* ENLITE PP LGF 6002 + 50
  - \* ENLITE PP LGF 6002 + 33
  - \* ENLITE ABS Alloy LGF 6001 + 42
- SABIC
  - \* NORYL FE1630PW
  - \* STAMAX 20YK270E
  - \* STAMAX 30YK270E

---

## Digimat-MAP

- New automatic mesh superposition algorithm with improved robustness (advanced method)

---

## Digimat-CAE

- Progressive failure
  - Multiple damage laws with a single failure indicator
  - Significant CPU time reduction for UD/shell/explicit simulation configurations
- Hybrid Solution
  - Minimization of the number of state variables
  - Support of unbalanced woven
  - Thermally dependent failure strengths in TE and TEP
  - Support of thermo-viscoelastic models
  - Hybrid parameter reader and viewer allowing to compare hybrid and micro responses

- Failure: strain based failure criterion allowing to differentiate tension and compression based on triaxiality
- General CPU time reduction:
  - \* Significant for shell elements
  - \* Minor for solid elements
- New outputs for UD materials: fraction of failed/non-failed integration points through the thickness of shell elements
- Interfaces to FEA
  - MSC Nastran SOL400/SOL700: support of version 2016.0 (Windows / Linux 64 bits)
  - Abaqus: support of version 6.14 (Windows / Linux 64 bits)
  - LS-DYNA:
    - \* Support of version 6.1.2 (Linux 64 bits)
    - \* Support of version 7.1.1 (Windows / Linux 64 bits)
    - \* General robustness improvements
    - \* Correction of energy computation
  - Ansys: ACT plugin for Ansys Workbench

## Digmat-RP

---

- Graphical engine:
  - Improved CPU and memory performance
  - Visualization of orientation using vector/ellipsoidal plots
- Mapping
  - New mesh superposition algorithm with improved robustness
  - 1D mapping to define the desired number of layers in shell structural mesh
  - Improved flexibility for loading of orientation files: each element must have at least one information defined
- Interfaces:
  - PAM-CRASH 2013
  - Nastran SOL1XX: weak coupling for 2-phases elastic models
  - Marc: switch between Intel-MPI and MS-MPI in Settings Manager

## Digmat-VA

---

- Prediction of allowables
  - UD materials
  - Unnotched tension/compression and open-hole tension/compression tests
- Test matrix preparation
  - Definition of materials, layups, tests, environment conditions
  - Definition of sampling (number of batches, panels and specimens)
- Simulation preparation:
  - Import of Digimat model including progressive failure
  - Calibration of Digimat model from datasheet
  - Definition of micro-level variability (Gaussian distributions)
  - Definition of FEA settings: mesh size, element type, meshing strategy, number of time steps
  - Generation of FEA models
    - \* Preview mesh
    - \* Preview random draws

- Simulation run:
  - Embedded solver for local run
  - Job management
    - \* Job prioritization
    - \* Monitoring
- Post-processing
  - Automatic extraction of stress-strain curve, stiffness and strength
  - Computation of A, B-basis and mean values for strength following CMH17 procedures
  - Strength and stiffness distribution plots
  - Visualization of stress, strain and damage fields on coupon model
  - Creation of a customized report
  - Export of raw results to Excel
- Additional functionalities
  - Save Digimat-VA project: light or complete
  - Management of working database: materials, layups, tests, conditions and FEA settings

## II.1.11 Digimat 5.1.2

---

In this section of the documentation, you can find all major changes that are in Digimat 5.1.2.

### Digimat-MF

---

- Corrected failure criteria formulation
  - Shear terms in strain based criteria
    - \* Tsai-Hill 3D Transversely Isotropic
    - \* Tsai-Wu 3D Transversely Isotropic
  - Hashin 3D linear expression
  - Tsai-Wu 3D linear expression
- Corrected phase homogenization order when using the multi-level method
  - Affects elastic and visco-elastic UD material models including voids
- Corrected specific heat capacity computation
- Improved robustness with custom output for clustering with failure model
- Improved robustness for woven/braided
  - More robust when switching from FE to MF
  - Improved reporting for incorrect inlays definition
  - Improved error messages
- Improved robustness for second order homogenization

---

**Digmat-FE**

---

- Improved Marc interface robustness
  - Corrected periodic boundary conditions formulation
  - Corrected shear13 periodic loading boundary condition
  - Corrected user thermal loading definition
- Improved GUI robustness
  - Affects only intensive GUI browsing
- Initial seed size taken into account when exporting to Abaqus
- Corrected handling of continuous fibers with diameter larger than 0.5
- Upgraded WiseTex engine for woven
  - Improved robustness for braided and inlay geometry generation

---

**Digmat-MX**

---

- Upgrade to Postgresql 9.3
  - Requires an upgrade of database (See Section ??)
- Corrected unit system conversion of strain rate dependent failure models

---

**Digmat-MAP**

---

- Improved robustness
  - Weld line mapping
    - \* Only hexa 20 elements were concerned
  - Automatic scaling
    - \* Removal of negative bounding box size ratios
  - Donor meshes with wedges
  - Porosity mapping procedure
    - \* Volume fraction now results from mapped size and mapped pore density

---

**Digmat-CAE**

---

- Digmat to RADIOSS:
  - Support of RADIOSS v12
  - Support of RADIOSS for UD and Woven
  - Support of 1 layer draping file
  - Hypermesh/Optistruct plugin v12
- Digmat to PAM-CRASH
  - Support of UD and woven with Micro and Hybrid solution
- Improved robustness when using
  - Porosity and variable aspect ratio files
  - Volume fraction files

- Element deletion triggering
  - All integration points must fail to trigger element deletion
  - Concerns LS-DYNA, Nastran/SOL700 and PAM-CRASH
- Digimat to Abaqus
  - Corrected computation of transverse shear stiffness for composites with transversely isotropic fibers
  - Corrected handling of multiple integration point elements when using Digimat Orientation File (.dof)
    - \* Each integration point has its actual orientation instead of the orientation of the first integration point
- Hybrid:
  - Convergence improvement on Current yield Norton law for implicit solver
  - Improved robustness:
    - \* Identification of hybrid parameters for TE and TEP materials
      - Correct non-linear behavior of TEP material for every temperature
      - Identification possible for 0°
    - \* Identification of hybrid parameters for EVP materials with failure criteria
- Porosity (Mucell)
  - Corrected license usage for 3 phases involving voids and porosity distribution file.

## Digimat-RP

---

- Support of aspect ratio distribution
- Support of all formats of 3D TIMON orientation files for solid elements
- Enhanced equivalence between material models output from RP and CAE
- ABAQUS:
  - Value of transverse shear stiffness now depends on thickness section
  - Density of materials now always written
  - Now supports ABAQUS input files with the following keywords (without spaces):
    - \* \*SOLIDSECTION, \*SHELLSECTION, \*ENDSTEP,
    - \*ELEMENTOUTPUT, \*TRANSVERSESHEARSTIFFNESS
- ANSYS
  - Corrected SVAR output request
    - \* Respect of user defined output frequency
  - Improve robustness for ANSYS models
    - \* For models containing several materials
    - \* For models with non-Digimat material preceding a Digimat material

## II.1.12 Digimat 5.1.2 Student Edition

---

In this section of the documentation, you can find all major changes that are in Digimat 5.1.2 Student Edition. A Student Edition version

- can be used during two years after the release.
- is Windows only.
- only contains Digimat-MF and Digimat-FE.

---

**Digmat-MF**

---

- Analysis
  - Only mechanical isothermal analysis
- Materials
  - Only elastic materials
- Phases
  - Only two phases used in a microstructure
  - Only matrix, inclusion, void and continuous fiber phases
  - Coatings are available
  - Clustering is not available
- Microstructures
  - Only one microstructure used in the RVE
- RVE
  - Single and multi-layer analysis
  - Woven are not available
- Failure
  - Static and dynamic failure are available
    - \* Stress and strain based
    - \* All failure indicators are available
      - Component
      - Tsai-Hill 2D, 3D and 3D transversely isotropic
      - Azzi-Tsai-Hill 2D
      - Tsai-Wu 2D, 3D and 3D transversely isotropic
      - Hashin-Rotem 2D
      - Hashin 2D and 3D
      - SIFT
      - User defined
      - Outputs
  - All outputs are available

---

**Digmat-FE**

---

- Analysis
  - Only mechanical isothermal analysis
  - Materials
    - \* Only elastic materials
  - Phases
    - \* Only two phases used in a microstructure
    - \* Matrix, inclusion, void and continuous fiber phases
    - \* All inclusion shapes are available
      - Ellipsoid
      - Cylinder
      - Sphero-cylinder
      - Prism
      - Icosahedron
      - Beam
      - Curved beam



- Platelet
  - From CAD file
  - \* Coatings are supported
  - \* Clustering is not supported
- Microstructures
  - \* Only one microstructure used in the RVE
- RVE
  - \* Single and multi-layer analysis
  - \* Woven are not available
- Geometry
  - \* Maximum of 10 inclusions
- Mesh
  - \* Conforming and voxel mesh
  - \* In-house mesher
  - \* Limited to 5000 nodes
- Solver
  - In-house solver
    - \* Computation on a single CPU
    - \* Limited to 5000 nodes
    - \* First order elements
  - Export to Marc, Abaqus and Ansys
- Output
  - All outputs are available

### II.1.13 Digimat 5.1.1

---

In this section of the documentation, you can find all major changes that are in Digimat 5.1.1.

#### Digimat-MF

---

- Advanced woven model: Enhanced modeling capabilities
  - 2<sup>1/2</sup>D Woven
  - 2D Braided
- Failure
  - Tension-Compression Differentiation based on the transversely isotropic Tsai-Wu model
  - Definition of user criteria, and link with Progressive Failure
  - SIFT (1st order formulation)
- Viscoelastic-Viscoplasticity (VEVP)
  - Material modeling solution for structural engineering to be used in combination with Hybrid solution technology
  - Reformulations in the homogenization engine: viscoelastic part of the VEVP model consistent with a pure viscoelastic formulation in tensile and shear tests and elastoplastic part of the VEVP model consistent with a pure elastoplastic formulation
  - Supported technology
    - \* Microstructure: Multi-Layer definition

- \* Plasticity: Modified spectral method
  - \* Viscous models: Norton, Prandtl
- Clustering
  - Nonlinear stiffness: Elastoplastic
  - Robustness: Elastic matrix in clusters
  - Enhancement: Support of mass fraction
  - Material modeling solution for structural engineering to be used with the Hybrid solution technology
- Coating : Nonlinear elastoplastic stiffness
- Fatigue : Macroscopic fatigue model applicable to UD composites
- GUI
  - Woven visualization based on XFG
  - Display of unit system in use

---

## Digimat-FE

- RVE
  - Generation based on Parasolid
    - \* Large Speed-Up
    - \* Improved Robustness
  - Import of custom inclusion shape: Parasolid & STEP
  - Export of generated geometries: Parasolid & STEP
- Meshing
  - Tetrahedral: 1st / 2nd order conforming meshes
  - Hexahedral: Mapping on voxelized RVE (specific license required)
- Solution
  - Analysis types
    - \* Mechanical
    - \* Thermo-mechanical: Isothermal material parameters
    - \* Thermal
    - \* Electrical
  - Internal solver
    - \* Speed-Up (Parallel computations supported)
    - \* Robustness (Choice between iterative & direct solvers)
  - Interfaces to external solvers
    - \* Marc: Support of version 2013.1
    - \* Ansys: Support of version 15.0
    - \* Abaqus
      - Support of version 6.13
      - Support of version 6.14
      - Geometry import: STEP & Parasolid (specific Abaqus license required)
- Post-Processing
  - Field visualization of results over RVE: User friendliness
    - \* Cutting plane capability
    - \* Snapshot

- Computation & visualization of result distributions over RVE
- Computation of representative (mean) properties
- Woven materials
  - Support via voxel solution
  - Yarn definition
    - \* Elastic material (Properties computed from resin & fibers)
    - \* Local material axes follow yarn's waviness
  - Enhanced modeling capabilities
    - \* 2<sup>1/2</sup>D Woven
    - \* 2D Braided
  - Speed-up (Faster generation of woven geometries)
- GUI
  - Solver type to be chosen at the beginning of the analysis
  - New rendering library used

## Digimat-MX

---

- Public Database
  - Lanxess
    - \* TEPEX dynalite 102-RG600(x)/47% - PA / GF47 elastoplastic
    - \* TEPEX dynalite 104-RG600(x)/47% - PP / GF47 elastoplastic
  - Victrex
    - \* Victrex 150GL30 - PEEK / GF30 elastic & elastoplastic
    - \* Victrex 150CA30 - PEEK / CF30 elastic & elastoplastic
    - \* Victrex 90HM40 - PEEK / CF40 elastic & elastoplastic
  - DuPont
    - \* Zytel HTN54G35HSLR BK031 - PA\* / GF35 thermo-elastoplastic
    - \* Zytel PLS95G50DH2 BK261 - PA\* / GF50 elastoplastic
    - \* Zytel 73G30HSL BK416 - PA6 / GF30 elastoplastic
    - \* Zytel 73G50HSLA BK416 - PA6 / GF50 elastoplastic
    - \* Zytel 70G30HSLR BK099 - PA66 / GF30 elastoplastic
    - \* Zytel 70G50HSLA BK039B - PA66 / GF35 elastoplastic
    - \* Zytel 70G35HSLRA4 BK267 - PA66 / GF35 elastoplastic
    - \* Zytel 80G33HSLR BK031 - PA66-I / GF33 elastoviscoplastic
    - \* Zytel FE5382 BK276 - PA612 / GF33 elastoplastic
    - \* Crastin HR5315HF NC010 - PBT / GF15 elastoviscoplastic
  - Solvay: Database available on demand for local use:
    - \* Full content
    - \* Encrypted grades
  - e-Xstream engineering: GENERIC MATERIALS
    - \* SFRP - PEEK / GF30 elastic & elastoplastic
    - \* SFRP - PEEK / GF35 elastic & elastoplastic
    - \* SFRP - PEEK / GF40 elastic & elastoplastic
    - \* SFRP - PEEK / CF30 elastic & elastoplastic

- \* SFRP - PEEK / CF35 elastic & elastoplastic
- \* SFRP - PEEK / CF40 elastic & elastoplastic
- \* SFRP - PEI / CF30 (thermo-) elastic
- \* SFRP - PEI / CF35 (thermo-) elastic
- \* UD - PEEK / CF55 elastic & elastoplastic
- \* UD - PEEK / CF65 elastic & elastoplastic
- Unit System Management
  - MPa / Pa / SI / CGS / FPS / psi / ksi
  - 2 additional unit systems can be defined by the user
  - Capabilities
    - \* Import & assign unit system
    - \* Convert between unit systems
    - \* Store & export with new unit system
- Reverse Engineering
  - Upgrade of the optimization engine (use of Dakota 5.4)
  - Improved algorithm for progressive failure
- Encryption
  - Encrypt for groups
  - Encryption of hybrid parameters
  - Support of unit system management

## Digmat-MAP

---

- Short Fiber Reinforced Plastics: Simpo Molding (.xml format)
- Long Fiber Thermoplastics: Read & map additional data
  - Variable aspect ratio
    - \* Moldex3D (3D elements)
    - \* Molflow (Midplane)
  - Variable volume fraction: Moldex3D (3D elements)
- Woven
  - Read & map warp / weft
  - Interfaces to draping simulations
    - \* PAM-FORM
    - \* Digimat open format (.xml based)
- Micro computer tomography ( $\mu$ -CT)
  - Read & map data from  $\mu$ -CT
    - \* Fiber orientation
    - \* Fiber concentration
  - Interface to Volume Graphics (VGStudio MAX)
- Casting
  - Interface to MAGMASOFT
  - Read & map data from casting simulations (Local pore concentration)
- Initial Stresses: Export to ANSYS

## Digimat-CAE

---

- Hybrid Solution
  - Speed-Up in the generation of Hybrid parameters: Parallelization of the Hybrid pre-processor
  - Support of material models
    - \* Viscoelasticity (with failure)
    - \* Viscoelastic-Viscoplasticity (with failure)
  - Support of failure models
    - \* Tension-Compression differentiation (Stress based)
    - \* Per-phase standard failure criteria (Multiple failure surfaces)
  - Reduced memory consumption
- Failure
  - Tension-Compression differentiation based on the transversely isotropic Tsai-Wu model
  - Progressive Failure
    - \* Speed-Up
    - \* Improved robustness
  - SIFT failure criteria
  - Usage of failure criteria: FPGF criteria (PGA/PGB/PGC) merged to one output
- SFRP: Simpo-Molding (Support of .xml file format)
- Long Fiber Thermoplastics (LFT)
  - Fiber bundling / nonlinear supported with the Hybrid solution method
  - Moldflow Midplane: coupled analyses based on variable aspect ratio
  - Moldex3D: coupled analyses based on variable aspect ratio & volume fraction (3D)
- Woven / Draping
  - Support of the advanced woven model with the Micro solution
    - \* 2<sup>1/2</sup>D Woven
    - \* 2D Braided
  - Interface to PAM-FORM: coupled analyses based on local warp / weft data
  - Use data in the Digimat open format: ASCII based exchange format for local warp / weft information to be transferred from any type of draping analysis (e.g., internal user solutions based on explicit solvers)
- Computer Tomography ( $\mu$ -CT): interface to Volume Graphics
  - Data export from VGStudio MAX – Fiber Composite interface (Greyscale image analysis of  $\mu$ -CT data)
  - Coupled analyses based on local fiber orientation & volume fraction
- Casting: interface to MAGMASOFT. Coupled analyses based on distribution of porosity.
- FE solvers
  - Marc
    - \* Large rotations (Solid elements, isothermal analyses)
    - \* Support of version 2012 (Linux 64bit)
    - \* Support of version 2013.1 (Windows / Linux 64bit)
  - Abaqus Support of version 6.13 (Windows / Linux 64bit)
  - ANSYS Support of version 15.0 (Windows / Linux 64bit)
  - PAM-CRASH
    - \* Support of version 2013 (Windows / Linux 64bit)
    - \* Support of UD / Woven
- GUI
  - Display of unit system in use
  - Usage of failure criteria simplified

## Digmat-RP

---

- Shell modeling
  - Templates for coupled analyses with SHELL
  - Visualization
    - \* Thickness
    - \* Layer-by-layer properties
- Unit System Management : MPa / Pa / SI / CGS / FPS / psi / ksi
- Stiffness & Failure
  - Parallel generation of Hybrid parameters
  - Tension – compression differentiation
- FEA solvers
  - SAMCEF
  - Radioss (SOLID modeling)
- Injection molding simulations
  - REM3D (support of .mtc file format)
  - SIMPOE (support of .xml file format)
  - Moldflow midplane (support of .xml and .ele file format)
  - Moldex midplane (support of .ele file format)
- GUI: New visualization engine

## Bug fixes and minor improvements

---

- Digimat-MF
  - Second-order homogenization: bug fix
  - Woven: engineering moduli only computed for orthotropic stiffnesses
  - Fatigue: Improved parameter definition (number of cycles, Sa, GUI) and Reverse Engineering capabilities
  - Coating: Correct density computation with coated voids
  - Thermo-Elastoplasticity & Thermo-Elastoviscoplasticity: Poisson ratio correctly handled as a function of the temperature
- Digimat-MX
  - Database handling
    - \* Status of created DB (started/stopped, with or without service)
    - \* Improve delete grade process (interesting for very large DB)
    - \* Improve update of DB with the use of service
  - Import: reset loading angle during import process
  - Reverse Engineering: Keep the initial orientation after RE
- Digimat-CAE
  - SFRP - HYBRID solution / explicit: convergence issues fixed
  - Woven - HYBRID solution: Improvement in the generation of parameters for small angles (around 45°)
  - Viscoelasticity: fix for non-constant Poisson's ratios
  - Progressive failure: fix for element deletion trigger
  - MuCell®: Support of shell elements
  - Interface to Abaqus Standard: fix for shell composites
  - Ansys PlugIn
    - \* Layer thickness correctly taken into account with .dof files
    - \* Improved management of layered sections

---

## II.1.14 Digimat 5.0.1

---

In this section of the documentation, you can find all major changes that are in Digimat 5.0.1.

### Digimat Platform & GUIs

---

- New platform design & structure
  - Tools
  - Solutions
  - eXpertise
- 2D plots - Improved Robustness
  - New GUI library

### Digimat-MF

---

- Standard Failure
  - Unified treatment of all failure indicators
    - \* Linear formulation that can easily be linked to the security factor
  - Termination of analysis
    - \* Based on critical value
- First Pseudo Grain Failure
  - Consistent formulation for pseudo grain counting (PGA) and averaging (PGC)
    - \* PGA / PGC normalized based on critical values
    - \* User choice to enforce threshold when using PGC
  - Termination of analysis
    - \* Based on critical value
- Progressive Failure
  - Failure
    - \* Hashin 2D
    - \* Hashin 3D
    - \* Hashin-Rotem 2D
  - Damage
    - \* Matzenmiller/Lubliner/Taylor (MLT)
    - \* Individual damage evolution functions
    - \* Stabilization control using viscous regularization
- Thermal Analyses
  - Conductivity with temperature dependent parameters

---

**Digmat-MX**

---

- Reverse Engineering – Enhanced Capabilities & Robustness
  - Failure – FPGF / Tsai-Hill 3D transversely isotropic
    - \* Stress based
    - \* Strain based
  - Thermo-mechanical
    - \* Thermo-elastic
    - \* Thermo-elastoplastic
- Transversely isotropic materials
- Public Data
  - Generic grades
    - \* Glass fiber reinforced epoxy
    - \* Carbon fiber reinforced epoxy

---

**Digmat-CAE**

---

- Woven Composites – Robustness & Speed-Up
  - Support of Hybrid solution method
  - Material
    - \* Elastic
    - \* Elastoplastic
    - \* Elasto-Viscoplastic
  - Microstructure definition
    - \* Basic & homogeneous yarns
  - Failure definition
    - \* Per-phase (matrix & fibers)
- Failure
  - Solution control independent from physical failure parameters
    - \* Numerical flag set when physical threshold parameter exceeded (criteria > critical value)
  - Actions initiated by numerical flag
    - \* Stop analysis - implicit (except for LS-DYNA)
    - \* Delete elements - explicit & implicit (LS-DYNA)
- Thermal & Thermo-Mechanical Analyses
  - Improved robustness – support of hybrid solution method
    - \* Thermo-elastic
    - \* Thermo-elastoplastic
  - FE solvers
    - \* Marc (thermo-mechanical analyses)
    - \* Abaqus Standard (thermal analyses)
- CAE software
  - MSC Nastran SOL 400
    - \* Support of version 2013.1 – delivered & licensed via MSC
  - MSC Nastran SOL 700
    - \* Support of version 2013.1 – delivered & licensed via MSC
  - LS-DYNA
    - \* Support of linear solution for shell elements
    - \* Support of version 6.1 – increased robustness



---

**Digimat-RP**

---

**NEW MODULE ADDED**

- Easy setup of 3D coupled analyses
- Processing
  - Types
    - \* Injection / Injection-Compression / Compression molding
  - Software
    - \* Moldflow3D
    - \* Moldex3D
    - \* Sigmasoft
    - \* 3D TIMON
- Material
  - 2-phase materials
  - Short & long fiber reinforced plastics
  - Input
    - \* Generic
    - \* From Digimat-MX
    - \* From Digimat-MF
    - \* From File (.daf & .mat)
  - Support of encryption
- FEM solvers
  - Marc
  - MSC Nastran (SOL400 & SOL700)
  - Abaqus (Standard & Explicit)
  - Ansys
  - LS-DYNA (Implicit & Explicit)
- Solution methods
  - Macro, Micro, Hybrid
  - User defined templates
- Job management
  - Submission
  - Monitoring

---

**Examples Manual**

---

- Examples Manual
  - Overview over all ready-to-run examples
  - Platform
    - \* Delivered by a separated installer
    - \* Consistent between common browser types
  - Examples added for
    - \* Digimat-MF
    - \* Digimat-FE
    - \* Digimat-CAE
    - \* Digimat-MAP
    - \* Digimat-RP
    - \* Digimat-HC

### II.1.15 Digimat 4.5.1

---

In this section of the documentation, you can find all major changes that are in Digimat 4.5.1.

#### Digimat-MF

---

- Improved application of loading conditions
  - Better prediction of experimental data for short fiber reinforced plastics and UD composites
    - \* Tension with off-axis oriented fiber
    - \* Shear

#### Digimat-MX

---

- Installation
  - MX database installed into Digimat working directory by default
- Public database
  - SOLVAY – new supplier, materials added
    - \* Ketaspire KT-880 GF30
    - \* Avaspire AV-651 GF30 BG20

#### Digimat-CAE

---

- Hybrid Solution
  - Improved accuracy for the anisotropic nonlinear hardening
    - \* Elastoplastic
    - \* Elasto-viscoplastic
- Post-Processing of short fiber reinforced plastics results as a function of the local fiber orientation
  - Micro & Hybrid solution procedures
  - Default output
    - \* First eigenvalue of orientation tensor  $a_{ij}$
    - \* Ratio between apparent stiffness (computed from local orientation) & ideal stiffness (computed in fiber direction)
  - User choice
    - \* Scalar product between the first eigenvectors of the orientation  $a_{ij}$  and the stress tensor  $\sigma_{ij}$
- Initial stresses
  - Support of ANSYS v14.5
- Support of FEA Software
  - Abaqus 6.12
    - \* Windows 32bit
    - \* Windows 64bit
    - \* Linux 64bit
  - Radioss v11

---

## II.1.16 Digimat 4.4.1

---

In this section of the documentation, you can find all major changes that are in Digimat 4.4.1.

### Digimat-MF

---

- Long Fiber Thermoplastics
  - Fiber bundling model: prediction of linear elastic stiffness
- Woven Composites
  - Advanced woven model: prediction of linear elastic stiffness based on weave pattern
  - Digimat GUI: advanced woven builder including
    - \* Yarn definition
    - \* Weave pattern definition
    - \* Visualization
- Creep
  - Digimat GUI: creep & relaxation loading
- Failure
  - Strain based Tsai-Hill-3D transversely isotropic failure criteria
  - Smoother behavior of FPGF model
    - \* Based on average failure criteria over all pseudo grains
  - Computation of 2D failure in the FPGF model performed in the most critical plane
  - Digimat GUI: improved & clarified workflow
- Fatigue
  - Pseudo grain based model: prediction of anisotropic  $S(N)$  curves enhanced to multilayered microstructures
  - Matrix based fatigue model: prediction of anisotropic  $S(N)$  curves dependent on fiber volumemass fraction
  - Digimat GUI: improved definition & display of  $S(N)$  curves
- Temperature dependencies
  - Plastic strain multipliers dependent on the temperature
- Time dependencies
  - General dependency of parameters in Digimat materials as a user defined function of time (e.g., to describe curing, crystallization, ...)
- Workflow & General Improvements
  - Loading: uniaxial direction defined via theta & phi angle
  - Microstructure: load layer definition from generic .csv formatted files
  - Export: isotropic material cards available for RADIOSS & PAM-CRASH

---

**Digmat-FE**

---

- RVE Generation
  - UD composites: periodic boundary conditions
- Interfaces
  - Support of ANSYS v14.5
- Workflow & General Improvements
  - Microstructure: load layer definition from generic .csv formatted files

---

**Digmat-MX**

---

- Public Database
  - Material suppliers: new data available
    - \* Evonik Industries
    - \* Sabic
  - Generic material models, (thermo-)elastic & (thermo-)elastoplastic
    - \* e-Xstream engineering
- Data import
  - Linear elastic: direct input of moduli
  - From Excel sheets: easy copy paste of general tabular data
- Reverse Engineering
  - Simplified procedures for non-material experts

---

**Digmat-CAE**

---

- Digmat LINEAR solution
  - Linear analyses based on
    - \* Direct engineering (input of matrixfiber properties)
    - \* Generic material data
    - \* Digmat analysis .daf files
  - No license blocked during coupled analysis runs
  - No license necessary to read local microstructure
- Micro Solution
  - Speed-Up: about 10 - 20 % gain in CPU for shell models
- Hybrid Solution
  - Speed-Up: about 30 - 50% gain in CPU
  - Memory consumption: decrease of about 40%
  - Improvements on failure modeling
    - \* Strain based failure
    - \* Full strain rate dependency

- Input: support of 2nd order homogenization
- Generation of Hybrid parameters
  - \* Multiple runs in the same folder
  - \* Re-running parameters by user choice
- Interfaces to FEA
  - MSC Nastran SOL400: new interface (single processor Windows)
  - Marc Mentat plug-in
  - Support of
    - \* ANSYS v14.5, Marc 2011, Marc 2012 (Win64bit), Nastran 2013 (Win64bit)
  - SAMCEF
    - \* Support of 2<sup>nd</sup> order solid elements
- Interfaces to Processing Software
  - Injection molding
    - \* SIMPOE: new interface (via MAP)
    - \* Moldex3D: enhancements for 3D (temperature fields, weld lines, initial stresses)
    - \* Moldex3D: new interface for 2D (fiber orientations)
  - Compression molding
    - \* Moldflow (3D analyses)
    - \* Moldex3D (3D analyses)
  - Injection-compression molding
    - \* Moldflow (3D analyses)
    - \* Moldex3D (3D analyses)
  - MuCell<sup>TM</sup>
    - \* Moldflow (2D analyses)
    - \* Moldex3D (3D analyses)
- Interfaces to Life Time Prediction Software
  - nCode DesignLife (2D & 3D analyses)
- Automated procedures
  - Mesh superposition by gravity center & axes of inertia
  - 3D Mapping

## Digimat-MAP

---

- Tools
  - Measurement of distance & angle between picked nodes
  - Mesh superposition by gravity center & axes of inertia
- Cross Mapping
  - From 3D volume to 2D shell meshes
- Meshes & Formats
  - Nastran, SAMCEF: support of 2<sup>nd</sup> order solid elements, SIMPOE
- Fiber Related Post Processing
  - Visualization of material properties at an integration point

---

**Digmat Documentation**

---

- New section
  - Map module: description of batch mode
- New guidelines: Reverse Engineering
  - Creep of SFRP with the elasto-viscoplastic material model
  - Failure of SFRP with the Tsai-Hill 3D transversely isotropic stress or strain based failure indicator using FPGF
- Example manual Platform
  - Updated & new examples
  - Project: Semi-automated procedures for RE of failure of SFRP with the Tsai-Hill 3D transversely isotropic stress or strain based failure indicator using FPGF

---

## II.1.17 Digimat 4.3.1

---

In this section of the documentation, you can find all major changes that are in Digimat 4.3.1.

### Digimat-MF

---

- Creep
  - Interaction law: new linearization method
- Thermo-Viscoelastic Material Model
  - For high strain rate dependency & creep behavior of composites
  - Three time shift functions (Arrhenius, WLF, piecewise linear)
- Thermo-Elasto-Viscoplastic Material Model
  - Time law for creep behavior of composites
- Failure
  - Stress based Tsai-Hill-3D transversely isotropic failure criterion
- Fatigue
  - Pseudo-grain fatigue model enhanced to full 3D description
- GUI
  - Clear distinction for strain rate dependent material models
    - \* High strain rates
    - \* Creep
  - Improvements in tooltips

### Digimat-FE

---

- Enhanced Flexibility in Phase Generation
- User Definition of Inclusion Positions
- Enhanced Clustering
- Interface to ANSYS
  - Support of v14.0
- GUI
  - New GUI structure
  - Improvements in tooltips

---

**Digmat-MX**

---

- New Database Tools
  - Advanced filter
  - Import data
- Enhanced Database Tools
  - Reverse Engineering
- GUI
  - New GUI structure

---

**Digmat-CAE**

---

- Failure
  - HYBRID failure available in combination with both solutions methods, MICRO and HYBRID
  - Recommended procedures for workflow between Tsai-Hill-3D transversely isotropic criterion and HYBRID failure
- HYBRID solution
  - Improvement in memory management leading to
    - \* Faster initialization of CAE analyses
    - \* Up to 50% decrease in memory consumption during CAE runs
- LMS Virtual.Lab Durability
  - Pseudo-grain based fatigue model available in interface to lifetime prediction software
- SAMCEF
  - HYBRID solution method available with Mecano solver
  - Support of Dynam method for vibrational analysis
- ANSYS
  - Support of v14.0
- GUI
  - Improvements in tooltips

---

**Digmat-MAP**

---

- Speed-Up
  - Increased mapping speed especially for large models (tetrahedral elements)
- Moldflow models
  - Automated scaling by factor 1000 (Dual view / superpose function)
- GUI
  - Improvements in tooltips



---

## Digimat Installation

---

- New installation procedures
  - 3rd party products installed independently from Digimat core product
  - 2 archives to download, one installer to lead through the full installation workflow

---

## Digimat Documentation

---

- Improved description of installation procedures
- Enhanced Example manual platform
- Recommended procedures for reverse engineering

---

## II.1.18 Digimat 4.2.1

---

In this section of the documentation, you can find all major changes that are in Digimat 4.2.1.

### Digimat-MF

---

- Fatigue model: prediction of orientation dependent SN curves for high cycle fatigue
  - 2 phase composite materials
  - Linear elastic material
  - Based on pseudo grain approach
- Improved description of FPGF failure criteria
  - Storage of full stress/strain data per pseudo grain
- Export of homogenization results as material cards ready to use with FEA solvers
  - Linear elastic / elastoplastic behavior (single curve)
  - Abaqus, ANSYS, Marc, LS-DYNA, RADIOSS and PAM-CRASH
- Improved user friendliness
  - Automated display of homogenization results per analysis (curve plot & stiffness)
  - Simplified input of special microstructures (short fibers, UD and woven composites)
  - Clear separation between static/dynamic and fatigue failure criteria
- General corrections:
  - Correction of the computation of shear elastic stiffness affecting linear behavior of small strain material models when using orthotropic closure.

### Digimat-FE

---

- Full pre-/post processing workflow available for computations using ANSYS Workbench

### Digimat-MX

---

- Redesign of database structure including
  - Handling data by user/ group permission
  - Sharing data between groups
- New GUI based reverse engineering tool including
  - Workflow user friendly oriented approach
  - Definition of one microstructure per experimental curve defined by an orientation tensor
  - Display of optimization progress
- Enhancements in the encryption technology

- Encrypted data in MXDB
  - Multi selection of data to encrypt
- Interface to Materiality database (provided by DatapointLabs)

## Digimat-CAE

---

- CPU Speedup through
  - New "HYBRID" solution method (focus on macroscopic material properties, available for elasto-plastic and elasto-viscoplastic material models)
  - Improvements in the handling of output data
- Macroscopic failure indicator taking advantage of the improvements in the FPGF failure description (available in combination with the new "HYBRID" solution method)
- Interface to LMS Virtual.Lab Durability for fatigue analysis
- Interface to Simulayt drapage technology
- Interface to LS-DYNA implicit
- Interface to Marc
- Enhancements in SAMCEF interface (multi-processor, 64-bit, Linux)
- Updated Sigmasoft interface (fiber orientation, residual stresses, weld lines)
- Enhancements in the encryption technology
  - Capability to add readable parameters to an encrypted file (e.g., failure indicators, analysis settings, ...)
- Support of Abaqus Part/Assembly data structure
- Support of ANSYS .inp data structure via the Workbench Plug-In

## Digimat-MAP

---

- Improved handling of orientation tensors including
  - (Automated) re-mapping for element set without orientation tensors after mapping
  - Manual setting of orientation tensors for element sets without orientation information after mapping
  - Enhancements of automated checks of physicality of orientation data (upon reading and writing of orientation files)
- Improved graphical display of 2nd order meshes
- New display options of element sets:
  - By material ID (with ANSYS .cdb file)
  - By section and element type (with Patran .pat file)
- Support of SAMCEF mesh format

**Digmat GUI**

---

- Improved user friendliness: automated graphical display of user input for
  - Material properties (e.g., stress/strain curve)
  - Microstructure information (e.g., aspect ratio, orientation tensor)

**Digmat Documentation**

---

- New structure with focused improvements on
  - Dedicated chapter: Detailed description of installation procedures & workflow
  - Appendices: Overview over capabilities & limitations of the software
- Available as PDF document

---

## II.1.19 Digimat 4.1.2

---

In this section of the documentation, you can find all major changes that are in Digimat 4.1.2.

---

### Digimat-MF

---

- Temperature dependent models: consistency between Digimat material models and output.
  - Thermal strain in thermo-elasticity: the initial strains are assumed to be zero as when using thermo-elastoplasticity or thermo-elastoviscoplasticity.
  - Display stiffness matrices and engineering data outputs at initial or final temperature/time when working with thermal or time dependencies.
- Enhanced management of default parameters in analysis settings:
  - Linearization method: discrete affine method automatically chosen as default for elastoviscoplastic and viscoelastic-viscoplastic material models.
  - Multi-inclusion homogenization: coatings automatically correctly handled with multi-level scheme.
- General corrections:
  - Automated warning that classical failure cannot be mixed with FPGF in the same .mat file
  - CTE output is given in the .dsf and .stf files.
  - Improved output management.

---

### Digimat-FE

---

- General corrections:
  - Restart analyses with modification in the analysis definition.

---

### Digimat-MX

---

- Multiple selections of Material Explorer and Data Explorer entries for deletion, selection, export or plot.
- Improved behavior of the Material Information frame when displaying the grade definition for modification or at import.
- General corrections:
  - When importing a thermo-dependent Digimat analysis, extracted Digimat materials contain the thermo-dependency functions of the parameters.
  - A database cluster can be created in a folder with a path name containing blank space.
  - Large comment information field can be modified.
  - PDF datasheet generation possible for grades containing large comment field.
  - Stabilized behavior for stopping the server after a reverse engineering analysis.
  - Digimat analysis files containing reinforcement by rigid inclusions can be imported.
  - Improvement of MX messages to the user.
  - Possibility to delete material trees containing more than 20 experimental data entries.

---

**Digmat-CAE**

---

- CPU time reduction: general improvements in the code and convergence schemes.
- Stiffness update delay (SUD): improved formulation for combination of SUD with elasto-viscoplastic materials.
- Convergence stabilization: improvement in the algorithm enforcing plane stress condition for shell elements leading to a better convergence rate. These improvements are particularly effective when using elasto-viscoplastic materials.
- Multi-layer material: Digmat material (.daf) files defined as multi-layers can be used to set up coupled analyses via Digmat-CAE and the Digmat plugins.
- Failure indicators: Local axis system can be used to define failure criteria in both phases of two-phase composites as well as on the macroscopic level.
- Interface to ANSYS:
  - Stabilization of installation on single partition
  - Compatibility with ANSYS 13.0.
  - Compatibility of ANSYS wizard with Digmat material (.daf) files from older Digmat versions (4.0.2 and below).
  - WB wizard support of Digmat material (.daf) files containing blank spaces in the filename.
- General corrections:
  - Handling of orientation tensor defined in the Digmat material (.daf/.mat) files.
  - Output of failure criteria for homogeneous materials.
  - Applying failure criteria for element deletion even if not requested as output.
  - Handling of encrypted mat files in Digmat-CAE GUI
  - RADIOSS: Element deletion triggered when all integration points have failed.

# Software **II.2**

## Supported systems

---

II.2.1	Licensing systems . . . . .	244
II.2.2	Operating systems . . . . .	244
II.2.3	Digimat GUI . . . . .	244
II.2.4	Digimat-CAE . . . . .	245

---

---

### II.2.1 Licensing systems

---

The current version of Digimat supports the MSC license manager 10.5. It enables both floating and node-locked (file based) licensing.

### II.2.2 Operating systems

---

Two different operating systems are supported for one or several of the Digimat products. Digimat products are supported on Windows 64 bits platforms as follows:

- Windows 7 64 bits and Windows 10 64 bits are supported.

In addition of those,

- Linux x86-64 bits: most distributions using GLIBC  $\geq 2.17$  and GLIBCXX  $\geq 3.4.19$ , including Red Hat 7.X and Suse  $\geq 11$  is also supported for the following products:
  - Digimat-MF (batch mode, no GUI)
  - Digimat-FE (batch mode, no GUI)
  - Digimat-CAE
    - \* Abaqus/Standard & Abaqus/Explicit
    - \* ANSYS Mechanical
    - \* LS-DYNA
    - \* Marc
    - \* MSC Nastran SOL1XX
    - \* MSC Nastran SOL400
    - \* OptiStruct
    - \* PAM-CRASH
    - \* PERMAS
    - \* SAMCEF
- Linux x86-64 bits: most distributions using GLIBC  $\geq 2.12$  and GLIBCXX  $\geq 3.4.13$ , including Red Hat 6.3 is also supported for the following products:
  - Digimat-MF (batch mode, no GUI)
  - Digimat-CAE
    - \* Abaqus/Standard & Abaqus/Explicit
    - \* LS-DYNA
    - \* PAM-CRASH

---

### II.2.3 Digimat GUI

---

Graphical user interfaces of all Digimat products are only available on Windows platforms with graphical card supporting OpenGL3.3. Update of graphical card driver can be necessary.



## II.2.4 Digimat-CAE

---

Digimat-CAE computations can be run both on Windows and Linux platforms. Virtual machine can be also used. Certain restrictions do however apply as to the supported software versions, the parallelization possibility and the type of processors that are used. The table below summarizes this information.

		Win64	Linux64
Digimat-CAE / Abaqus 2017, 2018, 2019	Sequential	Yes	Yes
	Parallel	Yes <sup>a</sup>	Yes <sup>b</sup>
Digimat-CAE / ANSYS 19.2, 2019R1 (aka 19.3)	Sequential	Yes	Yes
	Parallel	Yes <sup>c</sup>	Yes <sup>d</sup>
Digimat-CAE / ANSYS Fluent 17.0, 17.2, 18.0, 18.1	Sequential	Yes	No
	Parallel	Yes <sup>e</sup>	No
Digimat-CAE / LS-DYNA R9.3.0, R10.1, R10.2	Sequential	Yes	Yes
	Parallel	Yes <sup>c</sup>	Yes <sup>d</sup>
Digimat-CAE / Marc 2018.0, 2018.1	Sequential	Yes	Yes
	Parallel	Yes <sup>f</sup>	Yes <sup>g</sup>
Digimat-CAE / MSC Nastran SOL1XX 2014.0, 2014.1, 2016.0, 2016.1, 2017.0, 2018.0	Sequential	Yes	Yes
	Parallel	Yes	Yes
Digimat-CAE / MSC Nastran SOL400 Unknown <sup>h</sup>	Sequential	Yes	Yes
	Parallel	Yes	Yes
Digimat-CAE / OptiStruct 13.0, 14.0	Sequential	Yes	Yes
	Parallel	Yes	Yes
Digimat-CAE / PAM-CRASH 2016.0, 2017.0, 2018.01	Sequential	Yes	Yes
	Parallel	Yes <sup>b</sup>	Yes <sup>b</sup>
Digimat-CAE / PERMAS V16	Sequential	Yes	Yes
	Parallel	Yes	Yes
Digimat-CAE / SAMCEF 16.3, 17.2	Sequential	Yes	Yes
	Parallel	Yes	Yes
Digimat-CAE / nCode DesignLife 2018.1	Sequential	Yes	No
	Parallel	No	No

<sup>a</sup>DMP parallelization using MS-MPI.

<sup>b</sup>DMP parallelization using Platform-MPI.

<sup>c</sup>DMP parallelization using Intel-MPI, Platform-MPI or MS-MPI

<sup>d</sup>DMP parallelization using Intel-MPI or Platform-MPI

<sup>e</sup>DMP parallelization using Platform-MPI or MS-MPI

<sup>f</sup>DMP parallelization using Intel-MPI or MS-MPI.

<sup>g</sup>DMP parallelization using Intel-MPI.

<sup>h</sup>Since Digimat libraries are shipped with the Nastran installer after the Digimat release, please refer to the Nastran SOL400 documentation to know which Digimat version is supported.

Table II.2.1: Supported platforms for each Digimat-CAE product.

# Software **II.3**

## Supported CAE software

---

II.3.1	Digmat-CAE . . . . .	248
	Digmat-CAE/Abaqus . . . . .	248
	Digmat-CAE/ANSYS . . . . .	249
	Digmat-CAE/Marc . . . . .	250
	Digmat-CAE/MSC Nastran SOL400 . . . . .	251
	Digmat-CAE/SAMCEF . . . . .	252
	Digmat-CAE/LS-DYNA . . . . .	253
	Digmat-CAE/PAM-CRASH . . . . .	255
	Digmat-CAE/MSC Nastran SOL1XX . . . . .	256
	Digmat-CAE/OptiStruct . . . . .	257
	Digmat-CAE/PERMAS . . . . .	258
	Digmat-CAE/nCode DesignLife . . . . .	259
	Digmat-CAE/ANSYS Fluent . . . . .	260
II.3.2	Digmat-FE . . . . .	261
	Export to Abaqus/CAE . . . . .	261
	Export to ANSYS Workbench . . . . .	261
II.3.3	Digmat-MAP . . . . .	262
	File formats . . . . .	262
	Data types . . . . .	264
	Mesh formats . . . . .	266

---

### II.3.1 Digimat-CAE

---

#### Digmat-CAE/Abaqus

---

Digmat 2019.1 supports the following versions of Abaqus software:

- Abaqus 2017
- Abaqus 2018
- Abaqus 2019

The Digimat plug-in for Abaqus/CAE is supported for the following versions of Abaqus software:

- Abaqus 2017
- Abaqus 2018
- Abaqus 2019

Digmat 2019.1 supports the following platforms:

- Windows 7 (64-bit)
- Windows 10 (64-bit)
- Linux (64bit with Platform-MPI)

The following combinations/versions of Abaqus software are NOT supported with Digimat 2019.1:

- All Abaqus 201X-EFy versions or similar

The supported Abaqus/Standard formulations for shell elements are

- First order triangle STRI3, S3, S3R
- First order quadrangle S4, S4R, S4R5
- Second order triangle STRI65
- Second order quadrangle S8R, S8R5

The supported Abaqus/Explicit formulations for shell elements are

- First order triangle S3
- First order quadrangle S4, S4R

The supported Abaqus/Standard formulations for solid elements are

- First order tetrahedron C3D4, C3D4H
- First order pentahedron C3D6, C3D6H
- First order hexahedron C3D8, C3D8R, C3D8H, C3D8I
- Second order tetrahedron C3D10, C3D10M, C3D10MH, C3D10H, C3D10I, C3D10HS
- Second order hexahedron C3D20, C3D20R, C3D20H

The supported Abaqus/Explicit formulations for solid elements are

- First order tetrahedron C3D4
- First order pentahedron C3D6, C3D6H
- First order hexahedron C3D8, C3D8I
- Second order tetrahedron C3D10M

---

**Digmat-CAE/ANSYS**

---

Digmat 2019.1 supports the following releases of ANSYS software:

- ANSYS V19.2
- ANSYS 2019R1 (aka V19.3)

The ACT Digimat plug-in for ANSYS Workbench is supported for the following versions of ANSYS software:

- ANSYS V19.2 (Windows platform)
- ANSYS 2019R1 (Windows platform) (aka 19.3)

Digmat 2019.1 supports the following platforms:

- Windows 7 (64-bit)
- Windows 10 (64-bit)
- Linux (64-bit)

The supported ANSYS formulations for shell elements are

- First order triangle/quadrangle 181
- Second order triangle/quadrangle 281

The supported ANSYS formulations for solid elements are

- First order tetrahedron/hexahedron 185
- Second order tetrahedron/hexahedron/pentahedron 186
- Second order tetrahedron 187
- First order tetrahedron with nodal pressures 285

---

**Digmat-CAE/Marc**

---

Digmat 2019.1 supports the following releases of Marc software:

- Marc 2018.0
- Marc 2018.1

Digmat 2019.1 supports the following releases of Mentat software (for Digmat to Mentat plugin):

- Mentat 2018.0
- Mentat 2018.1

Digmat 2019.1 supports the following platforms:

- Windows 7
- Windows 10
- Linux (with Intel-MPI)

The following combinations/versions of Marc software are NOT supported with Digmat 2019.1:

- Marc using HP-MPI for parallel computations under Linux

The supported Marc formulations for shell elements are

- First order quadrangle 18, 75, 139, 140
- Second order quadrangle 22, 30, 72
- First order triangle 138, 158
- Second order triangle 49, 200

The supported Marc formulations for solid elements are

- First order hexahedron 7, 84, 117
- First order tetrahedron 134
- First order tetrahedron with Hermann formulation 157 (for creep application)
- Second order hexahedron 21, 57
- Second order tetrahedron 127, 184
- Second order tetrahedron with Hermann formulation 130 (for creep application)
- First order pentahedron 136
- Second order pentahedron 202
- First order 8-node composite brick element 149 (only for continuous fibers)
- Second order 20-node composite brick element 150 (only for continuous fibers applications)

---

**Digimat-CAE/MSC Nastran SOL400**

---

Since Digimat libraries are shipped with the Nastran installer after the Digimat release, please refer to the Nastran SOL400 documentation to know which Digimat version is supported.

Digimat 2019.1 supports the following platforms:

- Windows 7 (64-bit)
- Windows 10 (64-bit)
- Linux (64-bit)

The supported Nastran SOL400 formulations for shell elements are:

- CQUAD4
- CQUAD8
- CTRIA3
- CTRIA6

The supported Nastran SOL400 formulations for solid elements are:

- CPENTA
- CHEXA (8 and 20 nodes)
- CTETRA (4 and 10 nodes)

---

**Digmat-CAE/SAMCEF**

---

Digmat 2019.1 supports the following releases of SAMCEF software:

- SAMCEF 16.3 (a.k.a. 16.1-04) i8 64bits (Windows and Linux)
- SAMCEF 17.2 (a.k.a. 17.1-03) i8 64bits (Windows and Linux)

Digmat 2019.1 supports the following platforms:

- Windows 7 (64-bit with MS-MPI)
- Linux (64bit with MPICH)

Static libraries can be used for

- All above mentioned platforms / versions

The supported SAMCEF formulations for shell elements are

- Tri: 1<sup>st</sup> order (3-nodes) shell element
- Quad: 1<sup>st</sup> order (4-nodes) shell element

The supported SAMCEF formulations for solid elements are

- Tetra: 1<sup>st</sup> order (4-nodes) and 2<sup>nd</sup> order (10-nodes) 3D element
- Hexa: 1<sup>st</sup> order (8-nodes) and 2<sup>nd</sup> order (20-nodes) 3D element
- Wedge: 1<sup>st</sup> order (6-nodes) 3D element



## Digmat-CAE/LS-DYNA

---

Digmat 2019.1 supports the following releases of LS-DYNA software:

- LS-DYNA R9.1.0 (Windows 7 64-bit: single & double precision with Intel-MPI, Platform-MPI & MS-MPI)
- LS-DYNA R9.1.0 (Windows 10 64-bit: single & double precision with Intel-MPI, Platform-MPI & MS-MPI)
- LS-DYNA R9.1.0 (Linux 64-bit: single & double precision with Intel-MPI & Platform-MPI)
  
- LS-DYNA R9.2.0 (Windows 7 64-bit: single & double precision with Intel-MPI, Platform-MPI & MS-MPI)
- LS-DYNA R9.2.0 (Windows 10 64-bit: single & double precision with Intel-MPI, Platform-MPI & MS-MPI)
- LS-DYNA R9.2.0 (Linux 64-bit: single & double precision with Intel-MPI & Platform-MPI)
  
- LS-DYNA R9.3.0 (Windows 7 64-bit: single & double precision with Intel-MPI, Platform-MPI & MS-MPI)
- LS-DYNA R9.3.0 (Windows 10 64-bit: single & double precision with Intel-MPI, Platform-MPI & MS-MPI)
- LS-DYNA R9.3.0 (Linux 64-bit: single & double precision with Intel-MPI & Platform-MPI)

Digmat 2019.1 supports the following versions of LS-DYNA for Platform-MPI on Linux 64 bits:

```
LS-DYNA 9.1.0, Single, Platform-MPI:
ls-dyna_mpp_s_r9_1_113698_x64_redhat54_ifort131_sse2_platformmpi_sharelib
LS-DYNA 9.1.0, Double, Platform-MPI:
ls-dyna_mpp_d_r9_1_113698_x64_redhat54_ifort131_sse2_platformmpi_sharelib
LS-DYNA 9.2.0, Single, Platform-MPI:
ls-dyna_mpp_s_r9_2_119543_x64_redhat54_ifort131_sse2_platformmpi_sharelib
LS-DYNA 9.2.0, Double, Platform-MPI:
ls-dyna_mpp_d_r9_2_119543_x64_redhat54_ifort131_sse2_platformmpi_sharelib
LS-DYNA 9.3.0, Single, Platform-MPI:
ls-dyna_mpp_s_R9_3_0_x64_redhat54_ifort131_sse2_platformmpi_sharelib
LS-DYNA 9.3.0, Double, Platform-MPI:
ls-dyna_mpp_d_R9_3_0_x64_redhat54_ifort131_sse2_platformmpi_sharelib
```

Digmat 2019.1 supports the following versions of LS-DYNA for Intel-MPI on Linux 64 bits:

```
LS-DYNA 9.1.0, Single, Intel-MPI:
ls-dyna_mpp_s_r9_1_113698_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib
LS-DYNA 9.1.0, Double, Intel-MPI:
ls-dyna_mpp_d_r9_1_113698_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib
LS-DYNA 9.2.0, Single, Intel-MPI:
ls-dyna_mpp_s_r9_2_119543_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib
LS-DYNA 9.2.0, Double, Intel-MPI:
ls-dyna_mpp_d_r9_2_119543_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib
LS-DYNA 9.3.0, Single, Intel-MPI:
ls-dyna_mpp_s_R9_3_0_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib
LS-DYNA 9.3.0, Double, Intel-MPI:
ls-dyna_mpp_d_R9_3_0_x64_redhat54_ifort131_sse2_intelmpi-413_sharelib
```

Digmat 2019.1 supports the following platforms:

- Windows 7 (64-bit)
- Windows 10 (64-bit)
- Linux (64-bit)

Dynamic libraries are used for

- LS-DYNA Linux operating systems

Static libraries are used for

- LS-DYNA Windows operating systems

The following combinations/versions of LS-DYNA software are NOT supported with Digimat 2019.1:

- SMP computations

The supported LS-DYNA formulations for shell elements are:

- 1 (Hughes–Liu)
- 2 (Belytschko-Tsay)
- 4 (Triangular Shell)
- 6 (S/R Hughes–Liu)
- 16 (Fully integrated): only for quadrangular, not for triangular elements

The supported LS-DYNA formulations for solid elements are:

- -2 (fully integrated S/R solid intended for elements with poor aspect ratio, accurate formulation)
- -1 (fully integrated S/R solid intended for elements with poor aspect ratio, efficient formulation)
- 1 (Constant Stress)
- 2 (S/R Solid)
- 3 (Quadratic 8 nodes)
- 4 (S/R tetrahedron)
- 10 (1pt tetrahedron)
- 13 (1pt tetrahedron) with LS-DYNA R7.1.2
- 16 (4 or 5 pt second order tetrahedron)
- 17 (10-noded composite tetrahedron with 4 or 5 pt second order tetrahedron)

---

**Digmat-CAE/PAM-CRASH**

---

Digmat 2019.1 supports the following releases of PAM-CRASH software:

- PAM-CRASH 2016.0
- PAM-CRASH 2017.0
- PAM-CRASH 2018.01

Digmat 2019.1 supports the following platforms:

- Windows 7 (DMP 64-bit with Platform-MPI)
- Windows 10 (DMP 64-bit with Platform-MPI)
- Linux (DMP 64-bit with Platform-MPI)

Dynamic libraries are used for

- Windows 7 (64-bit)
- Windows 10 (64-bit)
- Linux (64-bit)

The following combinations/versions of PAM-CRASH software are NOT supported with Digimat 2019.1:

- SMP Parallel computation

The supported PAM-CRASH formulations for shell elements are:

- SHELL 4 nodes first order quadrangle/triangle
- TSHEL 4 nodes first order quadrangle/triangle
- MEMBR 4 nodes first order quadrangle/triangle

The supported PAM-CRASH formulations for solid elements are:

- SOLID 8 nodes first order hexahedron/tetrahedron/pentahedron
- PENTA6 6 nodes first order pentahedron
- TETR4 4 nodes first order tetrahedron
- TETRA and TETR10 10 nodes second order tetrahedron

---

**Digmat-CAE/MSC Nastran SOL1XX**

---

Digmat 2019.1 officially supports the following releases of MSC Nastran software:

- MSC Nastran 2014.0
- MSC Nastran 2014.1
- MSC Nastran 2016.0
- MSC Nastran 2016.1
- MSC Nastran 2017.0
- MSC Nastran 2017.1
- MSC Nastran 2018.0

Digmat should also work with older versions of MSC Nastran. However, these other versions have not been fully tested and, therefore, are not officially supported.

Digmat 2019.1 supports the same platforms as the above versions of MSC Nastran.

The supported Nastran SOL1XX formulations for shell elements are:

- CQUAD4
- CQUAD8
- CTRIA3
- CTRIA6

The supported Nastran SOL1XX formulations for solid elements are:

- CPENTA (6 and 15 nodes)
- CHEXA (8 and 20 nodes)
- CTETRA (4 and 10 nodes)

The supported Nastran SOL1XX element properties are:

- PSOLID for solid elements
- PSHELL and PCOMP for shell elements

---

**Digmat-CAE/OptiStruct**

---

Digmat 2019.1 officially supports the following releases of OptiStruct software:

- OptiStruct 13.0
- OptiStruct 14.0

Digmat should also work with older versions of OptiStruct. However, these other versions have not been fully tested and, therefore, are not officially supported.

Digmat 2019.1 supports the same platforms as the above versions of OptiStruct.

The supported OptiStruct formulations for shell elements are:

- CQUAD4
- CQUAD8
- CTRIA3
- CTRIA6

The supported OptiStruct formulations for solid elements are:

- CPENTA (6 and 15 nodes)
- CHEXA (8 and 20 nodes)
- CTETRA (4 and 10 nodes)

The supported OptiStruct element properties are:

- PSOLID for solid elements
- PSHELL and PCOMP for shell elements

---

**Digmat-CAE/PERMAS**

---

Digmat 2019.1 officially supports the following releases of PERMAS:

- PERMAS V16

Digmat should also work with older versions of PERMAS. However, these other versions have not been fully tested and, therefore, are not officially supported.

Digmat 2019.1 supports the same platforms as the above version of PERMAS.

The supported PERMAS formulations for membrane/shell elements are:

- 3-noded triangles of type: TRIA3, TRIM3, TRIMS3, TRIA3K, SHELL3
- 4-noded quadrangles of type: SHEAR4, QUAD4, QUAM4, QUAMS, SHELL4

The supported PERMAS formulations for solid elements are:

- tetrahedra with 4 to 10 nodes: TET4, TET10
- hexahedra with 8 to 27 nodes: HEXE8, HEXFO8, HEXE20, HEXE27
- pentahedra with 6 to 18 nodes: PENTA6, PENTA15, PENTA18
- 5-noded pyramids: PYRA5

The supported PERMAS materials are:

- homogeneous materials (\$MATERIAL)
- laminate materials (\$LAMINATE)

---

**Digimat-CAE/nCode DesignLife**

---

Digimat 2019.1 supports the following releases of nCode software:

- nCode 2018.1, which supports Abaqus 2017, Abaqus 2018, and ANSYS 19.1 FE results files as long as the Digimat-CAE/nCode DesignLife interface is concerned

Digimat 2019.1 supports the following platforms:

- Windows 7 (64-bit)
- Windows 10 (64-bit)

---

**Digmat-CAE/ANSYS Fluent**

---

Digmat 2019.1 supports the following releases of ANSYS Fluent software:

- ANSYS Fluent 17.0
- ANSYS Fluent 17.2
- ANSYS Fluent 18.0
- ANSYS Fluent 18.1

Digmat 2019.1 supports the following platforms:

- Windows 7 (64-bit)



---

## II.3.2 Digimat-FE

---

### Export to Abaqus/CAE

---

The Abaqus results post-processing capability is officially supported for Abaqus 2016 for Windows 64bits platform. ODB generated with newer versions of Abaqus are not supported.

### Export to ANSYS Workbench

---

The ANSYS results post-processing capability is officially supported for ANSYS V18.0 and higher.

### II.3.3 Digimat-MAP

---

#### File formats

---

##### FE software mesh files

- Abaqus (.inp) \*
- ANSYS (.cdb / .inp / .dat / .ans)
- CADMOULD 3D-F (.cfe)
- I-DEAS (.unv)
- LS-DYNA (.key / .k / .dyn)
- Marc (.dat)
- Moldflow (.pat / .udm)
- MSC Nastran (.bdf / .dat / .nas)
- OptiStruct (.fem)
- PAM-CRASH (.pc)
- PAM-FORM (\_M##)
- Patran (.pat)
- PERMAS (.uci, .dat)
- RADIOSS (.rad)
- REM3D (.t)
- SAMCEF (.dat)
- Simulayt (.layout)
- STL geometry (.stl)
- 3D TIMON (.msh)

\* Please note that only flat models are supported in Digimat-MAP, assemblies are not.

##### FE software result files

- Abaqus (.odb)

##### Injection molding software results files

- CADMOULD 3D-F (.txt, .car)
- Moldex 3D (.o2d)
- Moldex midplane (.ele.\*)
- Moldflow 3D (.nod, .xml)
- Moldflow midplane (.ele.\*, .str, .nod, .xml)
- REM3D (.mtc)
- SigmaSoft (.txt)
- Simpoe (.xml)
- 3D TIMON (.bou, .hou, .fou)
- 3D TIMON midplane (.dat)
- 3D TIMON Light3D (.unv, .tdr)
- VISI Flow (.xml)

##### (Injection) Compression molding software results files

- Moldex 3D (.o2d)
- Moldflow 3D (.xml)

**Liquid composite molding software results files**

- PAM-RTM (.erfh5)

**Casting software results files**

- Magmasoft (.inp, .xml)
- ProCAST (.ntl)

**Additive manufacturing data files**

- G-code toolpaths (.gcode)
- Insight toolpaths (.txt): versions up to 2.2 are supported

**Digimat internal file formats**

- Digimat (.dof): format with an orientation tensor (or other type or data) defined at each integration point, instead of having an averaged orientation tensor per element as it is the case with all processing proprietary formats.
- Digimat (.dsf, .stf): formats with stiffness information, written out of coupled FEA, which can be visualized in Digimat-MAP.

Please note that the .dof and the .dsf formats are binary formats with better compression than plain text.

**Digimat open file format for draping processes**

- Digimat (.xml): open format containing mesh information (nodes and elements) and continuous fiber orientation for each element or integration point.

## Data types

### Fiber orientation tensors

- CADMOULD 3D-F (surface mesh)
  - Data is typically provided on 5 layers of the surface mesh (external surface of the geometry).
  - Digimat-MAP layer numbering matches CADMOULD definition, e.g.: layer 5 is positioned on the surface of the model, and layer 1 is the inside-most. Typically, when considering two opposite and parallel faces of the geometry, layer 1 corresponds to the middle surface; consequently, orientation data is the same on both external faces for layer 1.
- Moldex 3D (solid and shell elements)
- Moldflow (solid and shell elements)
- REM3D (solid elements)
- SigmaSoft (solid elements)
- Simpoe (solid elements)
- 3D TIMON (solid and shell elements)
- 3D TIMON Light3D (3D TIMON solid mesh)
  - The full data set consists of an orientation data file (.unv) and a thickness direction file (.tdr, hidden file).
  - The orientation data file provides the components of the orientation tensor for 10 layers, distributed along the thickness direction. It is organized in ML\_ORIENTATION\_TENSOR\*T11T12T13 and ML\_ORIENTATION\_TENSOR\*T22T23T33 blocks (where \* stands for the layer ID). Each block provides the following informations:
    - \* on the 3 first lines, the name of the orientation components;
    - \* on the 4 next lines, some description about the load case, which is ignored;
    - \* several pairs of lines, each giving (on the first line) the **original** element ID, the number of components, then (on the next line) the tensor component values;
    - \* an ending line containing -1.
  - The thickness direction file provides, for each element, the direction considered as the thickness direction. It is used by the mapping algorithm to determine, for each source tetrahedron element, which facet will be extruded to form the temporary 3D mesh. Note that for "bulk" elements, this direction corresponds to the normal to the free facet; for "edge" and "vertice" elements, we extrude the free facet whose normal is closest to the thickness direction, with an angular tolerance of 46° between these two vectors.

The thickness direction file is organized similarly to the orientation file, but with a single THICKNESS DIRECTION block providing the three components of the thickness direction vector.
- Digimat-MAP layer numbering follows this convention:
  - \* layer 1 corresponds to the ML\_ORIENTATION\_TENSOR10\* blocks, and is positioned close to the external surface, e.g. at relative altitude  $Z = -1 + 1/40$  w.r.t the source free facet;
  - \* layer 10 corresponds to the ML\_ORIENTATION\_TENSOR1\* blocks, and is positioned close to the midsurface, e.g. at relative altitude  $Z = -1/2 + 1/40$  w.r.t the source free facet;
  - \* layer 11 to 20 are the symmetric to layers 10 to 1 (respectively) w.r.t. the midsurface.
- VISI Flow (surface mesh)
  - Data file is organized in <Element> blocks, which provide the following informations:
    - \* a link between two elements of the surface mesh, e.g. a "source" element (ID) and a "target" element (linkID);
    - \* for "source" element, orientation data for 11 imaginary data point disposed uniformly along the line between the two linked elements centroids;
    - \* for "target" element, orientation data at the element centroid.
  - For sake of comprehensiveness, the distinction between "source" and "target" element is ignored by Digimat-MAP field visualization tools.
  - Digimat-MAP layer numbering follows this convention:
    - \* layer 1 corresponds to the last <Data> set in the <Element> block, and is positioned at the centroid of the source element (e.g. at relative altitude  $Z=0$  w.r.t the source element);
    - \* layer 11 corresponds to the first <Data> set in the <Element> block, and is positioned at the centroid of the target element (e.g. at relative altitude  $Z=-1$  w.r.t the source element).
- Volume Graphics (.csv, also contains volume fractions)

**Initial stresses**

- Digimat XML (solid elements)
- Moldflow (solid and shell elements)
- Moldex3D (solid elements)
- SigmaSoft (solid elements)
- Simpoe (solid elements)
- Abaqus (export for CAE computation)
- ANSYS (export for CAE computation)

**Initial temperatures**

- Moldflow (solid and shell elements)
- Moldex3D (solid elements)
- Simpoe (solid elements)
- 3D TIMON (solid and shell elements)
- Abaqus (export for CAE computation)

**Weld lines**

- Moldflow (solid and shell elements)
- Moldex3D (solid elements)
- 3D TIMON (solid and shell elements)
- SigmaSoft (solid elements)

**Porosity**

- Moldflow (solid and shell elements)
- Moldex3D (solid elements)
- Magmasoft (.xml and .inp formats, solid elements and nodal data)
- ProCAST (solid elements and nodal data)
- PAM-RTM (solid elements and nodal data)

**Volume fraction**

- Moldex3D (solid elements, nodal data)
- Volume Graphics (.csv, also contains fiber orientation tensors)
- 3D TIMON (solid elements, nodal data)

**Fiber length**

- Moldflow (solid and shell elements)
- Moldex3D (solid elements)
- 3D TIMON (solid elements)

**UD orientation**

- Digimat XML (orientation vectors in global or local axis)
- PAM-FORM
- Aniform

**Woven orientation**

- Digimat XML (orientation vectors in global or local axis)
- PAM-FORM
- Aniform

## Mesh formats

---

### Abaqus

- Only 'flat' input files are supported, i.e., input files with neither assembly nor part instances definition.
- Element sets (\*Elset) are supported (for mapping between subsets of elements).
- Included files (\*Include) are supported as long as they are not encrypted.
- The following types of elements are supported:
  - Tri: S3(R,RS), STRI3
  - Quad: S4(R,RS,RSW), S4R5
  - Tetra: C3D4(H,T), C3D10(H,M,I,HS)
  - Hexa: C3D8(R,H,RH,I,IH), C3D20(R,H,RH)
  - Wedge: C3D6, C3D15
  - Pyra: C3D5

### ANSYS (\*.ans format)

- The following types of elements are supported:
  - Tri / Quad: ANSYS type 43, 63, 143, 181 and 281
  - Tetra / Hexa: ANSYS type 45, 64, 185, 186, 187 and 285

### ANSYS (\*.cdb, \*.dat, \*.inp format)

- Different element sets are created (for mapping between subsets of elements) based on the Real Id assigned to the elements.
- Included files are supported using the command /input, <file>, <ext>, <folder path>, <n>, or /input, <file path>, <ext>, , <n>,, where the file is read starting at line n. This last parameter is optional. Labels and /eof commands are not supported.
- The following types of elements are supported:
  - Tri / Quad: ANSYS type 41, 43, 63, 143, 157, 163 and 181
  - Tetra / Wedge / Hexa: ANSYS type 5, 45, 62, 64, 65, 70, 87, 90, 92, 95, 117, 122, 123, 164, 168, 185, 186, 187, 226, 227, 231, 232, 236, 237, 278, 279 and 285

Hexahedra degenerated to tetrahedra, pyra and wedge elements are supported, other degenerations are not supported.

### CADMOULD

- Only 3D-F (surface mesh) format is supported.
- The following types of elements are supported:
  - Tri: 3-nodes linear triangular elements
 Bar elements (2-nodes linear bar) are ignored.

### I-DEAS

- The following types of elements are supported:
  - Tri:
    - \* Element types 41, 51, 61, 71, 91 (linear)
  - Quad:
    - \* Element types 44, 54, 64, 74, 94 (linear)
    - \* Element types 45, 55, 65, 75, 95 (quadratic)
  - Tetra:
    - \* Element type 111 (linear)
    - \* Element type 118 (quadratic)
  - Hexa:
    - \* Element type 115 (linear)
    - \* Element type 116 (quadratic)
  - Wedge:
    - \* Element type 112 (linear)

**LS-DYNA**

- Different element sets are created (for mapping between subsets of elements) based on the Part Id assigned to the elements.
- Included files are supported (\*INCLUDE, \*INCLUDE\_PATH, \*INCLUDE\_PATH\_RELATIVE cards).
- \*INCLUDE\_TRANSFORM cards are partially supported (only node id offset, element id offset, part id offset and transformation id are taken into account).
- Option POS6P is not supported for \*DEFINE\_TRANSFORMATION cards.
- The following types of elements are supported:
  - Triangular and quadrangular (with reduced integration scheme) linear shells
  - Linear and quadratic (10 nodes-definition) tetrahedron elements; linear hexahedron (with reduced integration scheme) and linear wedge elements

**Marc**

- Element sets ("define element set") are supported (for mapping between subsets of elements).
- Included files ("include") are supported.
- The following types of elements are supported:
  - Tri: Marc element type 6, 37, 49, 138, 155, 158, 200 (linear)
  - Quad: Marc element type 11, 18, 22, 30, 39, 72, 75, 80, 85, 86, 139, 140, 154, 186 (linear and quadratic)
  - Tetra: Marc element type 127, 130, 133, 134, 135, 157, 184 (linear and quadratic)
  - Hexa: Marc element type 7, 21, 43, 44, 57, 71, 84, 113, 117, 120, 123, 188 (linear and quadratic)
  - Wedge: Marc element type 136, 137, 192, 202, 203, 205, 238 (linear and quadratic)
  - Pyra: Marc element type 216, 217, 218, 219 (linear and quadratic)

**Moldflow (\*.udm format)**

- The following types of elements are supported:
  - Tri: Element type TRI3 (linear)
  - Tetra: Element type TET4 (linear)

**MSC Nastran**

- Different element sets are created (for mapping between subsets of elements) based on the Property Id assigned to the elements.
- Included files using the simple include 'file.dat' command are supported. The file name/path must be explicit and be single-token (no include 'file' '.dat'). The quotes are optional only if the command is single-line. Other variants are not supported.
- The following types of elements are supported:
  - Tri: CTRIA3 (linear)
  - Quad: CQUAD4, CQUADR, CQUAD8 (linear and quadratic)
  - Tetra: CTETRA (linear and quadratic)
  - Hexa: CHEXA (linear and quadratic)
  - Wedge: CPENTA (linear)

**OptiStruct**

- Different element sets are created (for mapping between subsets of elements) based on the Property Id assigned to the elements.
- Included files using the simple include 'file.fem' command are supported. The file name/path must be explicit and be single-token (no include 'file' '.fem'). The quotes are optional only if the command is single-line. Other variants are not supported.
- The following types of elements are supported:
  - Tri: CTRIA3 (linear)
  - Quad: CQUAD4, CQUADR, CQUAD8 (linear and quadratic)
  - Tetra: CTETRA (linear and quadratic)
  - Hexa: CHEXA (linear and quadratic)
  - Wedge: CPENTA (linear)

**PAM-CRASH**

- Different element sets are created (for mapping between subsets of elements) based on the definition of Groups of elements.
- Included files are supported (INCLU / command).
- The following types of elements are supported:
  - Triangular and quadrangular linear shell elements
  - Linear and quadratic tetrahedron elements; linear hexahedron and wedge elements

**Patran**

- Different element sets are created (for mapping between subsets of elements) based on the element type and the cross section ID assigned of elements.
- The following types of elements are supported:
  - Tri: Patran element type 3 (linear)
  - Quad: Patran element type 4 (linear)
  - Tetra: Patran element type 5 (linear and quadratic)
  - Hexa: Patran element type 8 (linear and quadratic)
  - Wedge: Patran element type 7 (linear and quadratic)

**PERMAS**

- Element sets (ESET) are supported (for mapping between subsets of elements).
- The following types of elements are supported:
  - Tri: SHELL3, TRIA3, TRIA3K, TRIA3S, TRIM3, TRIMS3, TRIM6 and TRIMS6 elements (linear)
  - Quad: SHELL4, QUAD4, QUAD4S, QUAM4, QUAMS4, SHEAR4, QUAM8, QUAMS8, QUAM9 and QUAMS9 elements (linear)
  - Tetra: TET4 and TET10 elements (linear and quadratic)
  - Hexa: HEXE8, HEXFO8, HEXE20 and HEXE27 elements (linear and quadratic)
  - Wedge: PENTA6, PENTA15 and PENTA18 elements (linear)

**RADIOSS**

- Different element sets are created (for mapping between subsets of elements) based on the definition of parts ID.
- Included files (#include) are supported in the Starter file.
- The following types of elements are supported:
  - Tri: SH3N
  - Quad: SHELL
  - Tetra: TETRA4 (linear) & TETRA10 (quadratic)
  - Hexa: BRICK8 (linear) & BRIC20 (quadratic)

**REM3D**

- The following types of elements are supported:
  - Tetrahedral elements

**SAMCEF**

- Included files are supported using the simple input "file.dat" command. Other variants are not supported.
- The following types of elements are supported:
  - Tri: 1<sup>st</sup> order shell element
  - Quad: 1<sup>st</sup> order shell element
  - Tetra: 1<sup>st</sup> order and 2<sup>nd</sup> order 3D element
  - Hexa: 1<sup>st</sup> order and 2<sup>nd</sup> order 3D element
  - Wedge: 1<sup>st</sup> order 3D element



**STL geometry**

- Both ASCII and binary STL formats are supported.
- The triangularization is loaded without remeshing, elements are assigned consecutive IDs starting from 1, in the same order as listed in the triangularization.
- Nodes are assigned consecutive IDs starting from 1, in the same order as listed in the triangularization, with two nodes considered as identical if they have exactly the same coordinates.

**3D TIMON**

- The following types of elements are supported:
  - Triangular and quadrangular linear shell elements
  - Tetrahedral, hexahedral and wedge linear elements



## **Part III**

# **Windows Prerequisites**



# Windows Prerequisites **III.1**

## Installation of prerequisites on Windows platforms

---

III.1.1	Microsoft Windows SDK v7.1 and .NET Framework 4.0 . . . . .	<b>274</b>
	Step 0. Check if Microsoft Windows SDK v7.1 is installed. . . . .	274
	Step 1. Uninstall Microsoft Visual C++ 2010 x64 Redistributables - 10.0.40219. . . . .	277
	Step 2. Uninstall Microsoft Visual C++ 2010 x86 Redistributables - 10.0.40219. . . . .	277
	Step 3. Check if Microsoft .NET 4.0 is installed. . . . .	278
	Step 4. Uninstall more recent version of Microsoft .NET. . . . .	279
	Step 5. Install Microsoft .NET 4.0 . . . . .	283
	Step 6. Install Microsoft Windows SDK v7.1. . . . .	286
	Step 7. Re-install recent Microsoft .NET versions. . . . .	292
III.1.2	Microsoft Visual Studio Express 2012 for Windows Desktop . . . . .	<b>296</b>
III.1.3	Microsoft .NET Framework 4.6.2 . . . . .	<b>301</b>

---

### III.1.1 Microsoft Windows SDK v7.1 and .NET Framework 4.0

---

Installation of Microsoft Windows SDK v7.1 and .NET Framework 4.0 is needed to use Digimat to LS-DYNA interface in order to build LS-DYNA executables containing Digimat libraries.

It is advised to make all next installation steps on a Windows 7 platform. Installation on a Windows 10 platform can fail.

In this section, DIGIMAT\_INSTALL corresponds to the Digimat installation directory, e.g.:

`C:\MSC.Software\Digimat`

For installation of this software package please take the following steps.

#### Step 0. Check if Microsoft Windows SDK v7.1 is installed.

---

- From Windows Start menu, open control panel and select Uninstall a program (see Figure III.1.1) and look for existing Microsoft Windows SDK v7.1 installation (see figure III.1.2).
- If Microsoft Windows SDK v7.1 is installed, next steps can be skipped.
- If Microsoft Windows SDK v7.1 is not installed, it needs to be installed. Installer can be downloaded from [Microsoft homepage](#)
- Download the Microsoft Windows SDK v7.1 by clicking on the download button besides the file name winsdk\_web.exe. See Figure III.1.3.
- In the appearing window click on save button to save winsdk\_web.exe on your computer.




Figure III.1.1: Go in uninstallation programs procedure.





Figure III.1.2: Check installation of Microsoft Windows SDK v7.1.

## Microsoft Windows SDK for Windows 7 and .NET Framework 4



The Windows SDK provides tools, compilers, headers, libraries, code samples, and a new help system that developers can use to create applications that run on Microsoft Windows.

- [+ Details](#)
- [+ System Requirements](#)
- [+ Install Instructions](#)
- [+ Related Resources](#)

Figure III.1.3: Download the linker by clicking on the download button besides the file name winsdk\_web.exe.



---

**Step 1. Uninstall Microsoft Visual C++ 2010 x64 Redistributables - 10.0.40219.**

---

- From Windows Start menu, open control panel and select Uninstall a program. See Figure III.1.1.
- If present, right-click on Microsoft Visual C++ 2010 x64 Redistributables - 10.0.40219 and click on uninstall. See Figure III.1.4.
- Answer "Yes" to the asked question. See Figure III.1.5.




Figure III.1.4: Select Microsoft Visual C++ 2010 x64 Redistributables - 10.0.40219.




Figure III.1.5: Confirm uninstallation of Microsoft Visual C++ 2010 x64 Redistributables - 10.0.40219.

---

**Step 2. Uninstall Microsoft Visual C++ 2010 x86 Redistributables - 10.0.40219.**

---

- From Windows Start menu, open control panel and select Uninstall a program. See Figure III.1.1.
- If present, right-click on Microsoft Visual C++ 2010 x86 Redistributables - 10.0.40219 and click on uninstall. See Figure III.1.6.
- Answer "Yes" to the asked question. See Figure III.1.7.




Figure III.1.6: Select Microsoft Visual C++ 2010 x86 Redistributables - 10.0.40219.




Figure III.1.7: Confirm uninstallation of Microsoft Visual C++ 2010 x86 Redistributables - 10.0.40219.

### Step 3. Check if Microsoft .NET 4.0 is installed.

- Open the uninstallation program procedure (figure III.1.1) and look for existing Microsoft .NET 4.0 installation (see figure III.1.8).
- If Microsoft .NET 4.0 is installed, steps 4 and 5 can be skipped.
- If Microsoft .NET 4.0 is not installed, it needs to be installed. Installer can be found at [Microsoft .NET 4.0 download page](#).




Figure III.1.8: Check that .NET 4.0 is installed.

#### Step 4. Uninstall more recent version of Microsoft .NET.

---

To be able to install Microsoft .NET 4.0, it's needed to uninstall all Microsoft .NET versions that are more recent than 4.0 (4.5, 4.7, ...). Example of uninstallation process is given hereafter for Microsoft .NET 4.7. This operation needs to be repeated for each Microsoft .NET installation, e.g., Microsoft .NET 4.5, Microsoft .NET 4.5.1, Microsoft .NET 4.5.2... Those Microsoft .NET versions needs to be reinstalled after Microsoft .NET installation 4.0 will be installed. So, it is strongly advised to note which Microsoft .NET versions were installed.

- From Windows Start menu, open control panel and select Uninstall a program. See Figure III.1.1.
- Right-click on Microsoft .NET 4.7 and click on uninstall. See Figure III.1.9.
- Click on "Continue" (see Figure III.1.10)
- Microsoft .NET 4.7 is uninstalled (see Figure III.1.11). It can take a while.
- Close the uninstallation process (see Figure III.1.12)

In case of improper uninstallations of Microsoft .NET Framework superior to 4.0, Microsoft .NET Framework 4.0 cannot be installed. The Framework Repair Tool may help to identify those improper uninstallations. Microsoft .NET Framework Repair Tool can be downloaded at [Microsoft page](#).




Figure III.1.9: Select Microsoft .NET 4.7.




Figure III.1.10: Confirm uninstallation of Microsoft .NET 4.7.




Figure III.1.11: Microsoft .NET 4.7 is uninstalled.




Figure III.1.12: Uninstallation of Microsoft .NET 4.7 is finished.

### Step 5. Install Microsoft .NET 4.0

---

- Download Microsoft .NET 4.0 installer at [Microsoft .NET 4.0 homepage](#).
- Execute File "dotNetFx40\_Full\_setup.exe".
- Accept the license terms and click on "Install". See Figure III.1.13.
- Installation is in progress. See Figure III.1.14.
- Installation is complete. See Figure III.1.15.




Figure III.1.13: Accept license terms of Microsoft .NET 4.0.




Figure III.1.14: Installation of Microsoft .NET 4.0.






Figure III.1.15: End of installation of Microsoft .NET 4.0.

**Step 6. Install Microsoft Windows SDK v7.1.**

---

- Start the winsdk\_web.exe Downloaded at step 0.
- In the first window of the setup wizard click on next. See Figure III.1.16
- Accept the End-User license agreement. See Figure III.1.17.
- Keep the default installation location. See Figure III.1.18.
- Install only the required components. See Figure III.1.19.
- Click on next. See Figure III.1.20.
- Installation is on-going. See Figure III.1.21.
- Installation is performed. Click on Finish.



Figure III.1.16: Click on next.




Figure III.1.17: Accept the End-user license agreement.




Figure III.1.18: Keep the default installation location.




Figure III.1.19: Install only the required components.




Figure III.1.20: Click on next.




Figure III.1.21: Installation is on-going.

**Step 7. Re-install recent Microsoft .NET versions.**

- If several Microsoft .NET versions were previously installed, it is needed to reinstall Microsoft .NET versions from the oldest one to the newest one, e.g., starting with Microsoft .NET 4.5, then Microsoft .NET 4.7.
- Links for the different Microsoft .NET versions are listed hereafter:
  - [Microsoft .NET 4.5](#)
  - [Microsoft .NET 4.5.2](#)
  - [Microsoft .NET 4.7](#)
  - [General Microsoft .NET Framework page](#)
- Example of Installation process is given hereafter for Microsoft .NET 4.7.
  - Download Microsoft .NET 4.7 installer at [Microsoft .NET 4.7 homepage](#).
  - Execute file NDP47-KB3186497-x86-x64-AllOS-ENU.exe and let the extraction process progress (see Figure III.1.22)
  - Accept the license terms and click on "Install". See Figure III.1.23.
  - Installation is in progress. See Figure III.1.24.
  - Installation is complete. See Figure III.1.25.




Figure III.1.22: Run Microsoft .NET 4.7 installation.






Figure III.1.23: Accept license terms of Microsoft .NET 4.7.




Figure III.1.24: Installation of Microsoft .NET 4.7.




Figure III.1.25: End of installation of Microsoft .NET 4.7.

### III.1.2 Microsoft Visual Studio Express 2012 for Windows Desktop

Installation of Microsoft Visual Studio Express 2012 for Windows Desktop is needed to use Digimat to Samcef interface in order to build Mecano and Dynam executables containing Digimat libraries.

Microsoft Visual Studio Express 2012 for Windows Desktop can be downloaded from the [Microsoft homepage](#). It may be needed to create a Microsoft account to be able to access this page.

**FILTER BY PRODUCT FAMILY**

- ☐ Azure SDK 2.3
- ☒ Visual Studio 2012
- ☐ Visual Studio 2012 Update 1
- ☐ Visual Studio 2012 Update 2
- ☐ Visual Studio 2012 Update 3
- ☐ Visual Studio 2012 Update 4
- ☐ Visual Studio 2012 Update 5

**DOWNLOADS (14)** Sort by: Relevance

**Visual Studio 2012 SDK**

No key required Info Release date: 21/Sep/2012 x86 English EXE Download

**Visual Studio 2012**

No key required Info Release date: 15/Aug/2012 x86 English EXE Download

**Visual Studio 2012 Shell**

No key required Info Release date: 15/Aug/2012 x86 English EXE Download

**[Trial] Visual Studio Premium 2012**

Get Key Info Release date: 15/Aug/2012 x86 English DVD Download

**[Trial] Visual Studio Ultimate 2012**

Get Key Info Release date: 15/Aug/2012 x86 English DVD Download

Figure III.1.26: Select Visual Studio 2012 in product family.

#### Visual Studio Express 2012 for Windows Desktop

No key required Info Release date: 12/Sep/2012 x86 English EXE Download

Figure III.1.27: Download exe file of Visual Studio Express 2012 for Windows Desktop.




Figure III.1.28: Run the downloaded wdexpress\_full.exe file as an administrator.



Figure III.1.29: Agree the license terms and conditions, then click on "INSTALL".



Figure III.1.30: Wait for the installation to be completed (can take a while).



Figure III.1.31: Close the installation once it is completed.



### III.1.3 Microsoft .NET Framework 4.6.2

---

Microsoft .NET Framework 4.6.2 or higher is required to use Digimat-RP, Digimat-VA and Digimat-AM.

The availability of the Microsoft .NET Framework 4.6.2 can be checked from the Windows Control panel (see [III.1.32](#)). If it is not installed, it must be downloaded from the [Microsoft download page](#) and installed before using Digimat-RP, Digimat-VA or Digimat-AM.





Figure III.1.32: Check if Microsoft .NET Framework 4.6.2 is installed





*Copyright © 2019 MSC Software Belgium SA*

*All rights reserved*

© 2018 MSC Software Belgium SA. All rights reserved.

The e-Xstream and eXdigimat logos, e-Xstream engineering, eX, eXdigimat and Digimat are trademarks or registered trademarks of MSC Software Belgium SA. All other trademarks belong to their respective owners. e-Xstream engineering is a division of MSC Software Belgium SA.